

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Premium Solid Color Weatherproofing Wood Stain Cedar Naturaltone No. 50533	NFPA
Product Code:	50533	1
MSDS Manufacturer Number:	50533	
Manufacturer Name:	BEHR Process Corporation	
Address:	3400 W. Segerstrom Avenue Santa Ana, CA 92704	
General Phone Number:	(714) 545-7101	
General Fax Number:	(714) 241-1002	HMIS
Customer Service Phone Number:	(800) 854-0133 ext. 2	Health Hazard
CHEMTREC:	For emergencies in the US, call CHEMTREC: 800-424- 9300	Fire Hazard
Canutec:	In Canada, call CANUTEC: (613) 996-6666 (call collect)	Reactivity
MSDS Creation Date:	June 26, 2006	Personal
MSDS Revision Date:	September 30, 2011	Protection
MSDS Format:	According to ANSI Z400.1-2004	

0

0

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Water	7732-18-5	30 - 60 by weight
Water	//52-10-5	30 - 80 by weight
Propylene glycol	57-55-6	1 - 5 by weight
Proprietary	No Data	1 - 5 by weight
Nepheline Syenite	37244-96-5	10 - 30 by weight
C.I. Pigment Yellow 42 (Iron oxide)	51274-00-1	1 - 5 by weight
Acrylic polymer	No Data	10 - 30 by weight
2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate	25265-77-4	0.1 - 1 by weight

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:	Irritant.
Potential Health Effects:	
Eye:	May cause irritation.
Skin:	May cause irritation.
Inhalation:	Prolonged or excessive inhalation may cause respiratory tract irritation.
Ingestion:	May be harmful if swallowed. May cause vomiting.
Chronic Health Effects:	Prolonged or repeated contact may cause skin irritation.
Signs/Symptoms:	Overexposure may cause headaches and dizziness.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	None generally recognized.

SECTION 4 - FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point:	No Data
Lower Flammable/Explosive Limit:	Not applicable.
Upper Flammable/Explosive Limit:	Not applicable.
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
NFPA Ratings:	
NFPA Health:	1
NFPA Flammability:	1

SECTION 6 - ACCIDENTAL RELEASE MEASURES

0

NFPA Reactivity:

Personnel Precautions:	Use proper personal protective equipment as listed in section 8.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section.

SECTION 7 - HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
Hygiene Practices:	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

EXPOSURE GUIDELINES

SECTION 9 - PHYSICAL and	U CHEMICAL PROPERTIES
Physical State Appearance:	Liquid.

Product: Premium Solid Color Weatherproofing Wood Stain Cedar Naturaltone No. 50533 | Manufacturer: BEHR Process Corporation | Revison:9/30/2011, Version:0

Density:	10 - 12 Lbs./gal.
Vapor Density:	Greater than 1 (Air = 1).
pH:	No Data
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Flash Point:	No Data
VOC Content:	Material VOC: 25 gm/l (Includes Water) Coating VOC.: 61 gm/l (Excludes Water)

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.
Incompatible Materials:	Oxidizing agents. Strong acids and alkalis.

SECTION 11 - TOXICOLOGICAL INFORMATION

Propylene glycol :

RTECS Number:	TY2000000
Eye:	Eye - Rabbit Standard Draize test.: 100 mg Eye - Rabbit Standard Draize test.: 500 mg/24H (RTECS)
Skin:	Administration onto the skin - Rabbit LD50: 20800 mg/kg [Details of toxic effects not reported other than lethal dose value] Administration onto the skin - Rabbit LD50: 20800 mg/kg [Behavioral - Ataxia Behavioral - Tetany Lungs, Thorax, or Respiration - Respiratory depression] Administration onto the skin - Human Standard Draize test.: 500 mg/7D Administration onto the skin - Human Standard Draize test.: 104 mg/3D (Intermittent) Administration onto the skin - Standard Draize test.: 10 %/2D Administration onto the skin - Standard Draize test.: 30 %/96H (Continuous) Administration onto the skin - Open irritation test: 30 %/96H (RTECS)
Ingestion:	Oral - Rabbit LD50: 18500 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Guinea pig LD50: 18350 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - LD50: >2080 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Mouse LD50: 20300 mg/kg [Behavioral - Ataxia Behavioral - Tetany Lungs, Thorax, or Respiration - Respiratory depression] Oral - Guinea pig LD50: 19000 mg/kg [Behavioral - Ataxia Behavioral - Tetany Lungs, Thorax, or Respiration - Respiratory depression] Oral - LD50: 22000 mg/kg [Behavioral - Ataxia Behavioral - Tetany Lungs, Thorax, or Respiration - Respiratory depression] Oral - LD50: 22000 mg/kg [Behavioral - Ataxia Behavioral - Tetany Lungs, Thorax, or Respiration - Respiratory depression] Oral - LD50: 22 gm/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50: 20 gm/kg [Details of toxic effects not reported other than lethal dose value] Oral - Mouse LD50: 22 gm/kg [Details of toxic effects not reported other than lethal dose value]
Nepheline Syenite :	
RTECS Number:	QP9365000
2,2,4-Trimethyl-1,3-Pentanedi	ol Monoisobutyrate :
RTECS Number:	UF600000
Ingestion:	Oral - Rat LD50: 3200 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Mouse LD50: 3200 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

SECTION 12 - ECOLOGICAL INFORMATION		
Ecotoxicity:	No ecotoxicity data was found for the product.	
Environmental Fate:	No environmental information found for this product.	
ECTION 13 - DISPOSA	L CONSIDERATIONS	

SECTION 14 - TRANSPORT INFORMATION

DOT UN Number:	No Data
DOT Hazard Class:	No Data

SECTION 15 - REGULATORY INFORMATION

Propylene glycol :		
TSCA Inventory Status:	Listed	
State Regulations:	Listed in the Pennsylvania State Hazardous Substances List.	
Canada DSL:	Listed	
Nepheline Syenite :		
TSCA Inventory Status:	Not listed	
Canada DSL:	Listed	
C.I. Pigment Yellow 42 (Iron oxide):		
TSCA Inventory Status:	Listed	
Canada DSL:	Listed	
2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate :		
TSCA Inventory Status:	Listed	
Canada DSL:	Listed	

SECTION 16 - ADDITIONAL INFORMATION

HMIS Health Hazard:	1
HMIS Fire Hazard:	1
HMIS Reactivity:	0
HMIS Other:	x
MSDS Creation Date:	June 26, 2006
MSDS Revision Date:	September 30, 2011
MSDS Revision Notes:	Name change.
MSDS Author:	Actio Corporation
Disclaimer:	This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.
Trademark :	The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights Reserved.

 ${\tt Copyright} \circledast$ 1996-2011 Actio Corporation. All Rights Reserved.