



Care of closet & mirror doors

GENERAL CLEANING

Clean with mild soap and water

Wipe dry with lint-free dry cloth

Dry door with separate cloth.

For mirror surface you may use a window cleaner and paper towels.

DOOR SURFACE CLEANING & HARDWARE LUBRICATION LABEL

REMOVAL Slowly peel from one corner. If label tears or sticks, moisten with soapy water and gently scrape with plastic putty knife. Stubborn labels can be soaked with soapy water and covered overnight with plastic wrap. Gently remove with plastic putty knife. **STUBBORN STAIN REMOVAL** Commercial glass cleaning products may be necessary. • Apply small amount directly to the stain. Avoid spilling or dripping down the glass. • Some persistent stains may need higher strength cleaning solutions that contain active ingredient chemicals such as denatured alcohol or acetone. Special care must be taken when using these types of cleaners. • For oil and grease: try baking soda and water.

Clean door surface and maintain hardware any time doors are not opening or closing properly or at least biannually (monthly for coastal areas): • Clean dirt/debris with mild soap and water and rinse clean.

Replace damaged hardware **PRECAUTIONS** The following substances may damage protective finishes. Do not use: • Vinegar-based cleaners (use on glass only) • Citrus-based cleaners (lemon, etc.) • Paint removers • Window cleaners • Brick/siding washes • Any other industrial or abrasive cleaners

Folding doors: Tracks and Bearings Wipe visible track surfaces with a damp soft cloth and a mild detergent, then wipe dry with a clean cloth. Using a suitable applicator spread a small amount of clear petroleum jelly or similar lubricant where the carrier wheels pass so that it is distributed evenly along the track.

The lubrication reduces wear, improves operation and protects against corrosion. In severe environments, apply a thin film industrial lubricant. Hangers, Pivots and Brackets Exposed surfaces should be wiped down with warm soapy water and a soft rag, and then rinsed clean before applying new surface protectant. A light spray application of WD40®, followed by a light wipe with a dry cloth to remove any excess. Be careful not to get these compounds on any wood components as it may cause staining. Cleaning and lubrication help to maintain and restore smooth.

For a list of Colonial Elegance products or Installation Information, please visit our website: www.colonialegance.com