



QC CL-5400
QuietCool Original Classic Line

QC CL-5400 Specifications

Air Flow	Hi: 5,024 CFM / Low: 4,406 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3,950 CFM / Low: 3,240 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,675 SQFT to 2,512 SQFT
Energy Use	Hi: 634 Watts / Low: 525 Watts
Amps	Hi: 5.60 / Low: 4.55
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 51.2 / Low: 45.7
Minimum Attic Clearance	38"
Duct Diameter	20"
Duct Length	9 feet
Motor Head Diameter	20 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit
Warranty	10 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	6.7 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 30 1/4"
Removable Grille Outside Dimension	16" x 32"
Shipping Weight	75 lbs.
Box Dimensions	39" x 24" x 39"
In The Box	-QC CL-5400 Motorhead -Damper Box -Ceiling Grille -9 Foot Duct -Cut-out Template -Accessory Bag -Window Locks



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM