# Say Yes to LOCTITE

## CAULK & SEALANTS IDEAL FOR FINISHING & SEALING

#### **Common Projects**



**Exterior Projects** 

• Exterior sealants must be able to withstand extreme weather conditions and sunlight to provide a long lasting seal.



Window & Door

• Window & door sealants must be flexible to shift with the structure without cracking.



Multi-Purpose

 Multi-Purpose sealants must be weather resistant while also being low odor and paintable for indoor use.



Kitchen & Bath

 Kitchen & Bath sealants must be easy to apply and clean up while being low odor for indoor use.



Paint & Trim

 Paint & Trim sealants are paintable and easy to clean up to blend in seamlessly with interior trim.

### Guide

#### FORMULA TYPES

**LATEX** – Easy to apply and clean up. Fast curing. Low odor, not suitable for extreme temperatures or direct sunlight. Ideal for indoor use.

**SILICONE** – Permanently flexible and shrink resistant in all conditions. Solvent clean up, not paintable. Adheres best to non-porous surfaces.

**SOLVENT** - Weather resistant and strong final adhesion. Strong odor and tougher to apply, ideal for outdoor use.

**POLYURETHANE** – Strong adhesion to most surfaces, good flexibility and weather resistance. Poor UV resistance.

**POLYMERS/HYBRID** - Weather and UV resistant, low odor. Great for indoor or outdoor use.