

SDS Report No.: CANEC1710407901 Date: 12 Jun 2017 Page 1 of 2

HUIXIAN SUNRISE POWER SOURCE CO.,LTD WEST SUOKELOU,HUQIAO,HUIXIAN CITY HENAN CHINA

SGS Job No. : CP17-030174 - SZ

Sample Name : NI-MH RECHARGEABLE BATTERY

Model No. : NI-MH AA600mAh, AA

Client Reference Information : See Remark

Manufacturer : HUIXIAN SUNRISE POWER SOURCE CO.,LTD

Country of Origin : CHINA

End Uses : Solar lights, LED emergency lights, Cordless

telephones, Walkmans, Electronic tools and so on.

Composition/Ingredient of sample

(as per client submission)

See section 3 Composition/information on ingredients on the SDS report

Job Receiving Date : 06 Jun 2017

SDS Preparation Period : 06 Jun 2017 - 12 Jun 2017

Service Requested : Safety Data Sheet (SDS) for the sample with submitted composition.

Summary : As per request, the contents and formats of the SDS are prepared in

accordance with US Regulations Relating to Labor 29 CFR 1910.1200 (g),

and is provided per attached.

Remark:

The SDS is prepared based on the information provided by client.

* This sample is likely to be classified as article and is out of scope of a SDS as set out in 29 CFR Part 1910.1200. This SDS is generated for client's

reference only.

Signed for and on behalf of SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

Zm guan

Approved Signatory

Luguan



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

198 Kezhu Road Scientech Park Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075113 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075113 e sgs.china@sgs.com



SDS Report

No.: CANEC1710407901 Date: 12 Jun 2017 Page 2 of 2

Remark:

Ni-MH AA100mAh AA150mAh AA200mAh AA250mAh AA300mAh AA350mAh AA400mAh AA450mAh AA500mAh AA600mAh AA700mAh AA800mAh AA900mAh AA1000mAh AA1100mAh AA1200mAh AA1300mAh AA1400mAh AA1500mAh AA1600mAh AA1700mAh AA1800mAh AA1900mAh AA2000mAh AA2100mAh AA2200mAh AA2300mAh AA2400mAh AA2500mAh AA2600mAh

Ni-MH AAA100mAh AAA150mAh AAA200mAh AAA250mAh AAA300mAh AAA350mAh AAA400mAh AAA450mAh AAA500mAh AAA600mAh AAA700mAh AAA800mAh AAA900mAh AAA1000mAh

Ni-MH 2/3AA100mAh 2/3AA150mAh 2/3AA200mAh 2/3AA250mAh 2/3AA300mAh 2/3AA350mAh 2/3AA450mAh 2/3AA500mAh 2/3AA500mAh 2/3AA500mAh

Ni-MH 2/3AAA100mAh 2/3AAA150mAh 2/3AAA200mAh 2/3AAA250mAh 2/3AAA300mAh 2/3AAA350mAh 2/3AAA400mAh 2/3AAA450mAh 2/3AAA500mAh 2/3AAA500mAh

Ni-MH 4/5AA100mAh 4/5AA200mAh 4/5AA300mAh 4/5AA350mAh 4/5AA400mAh 4/5AA500mAh 4/5AA600mAh 4/5AA700mAh 4/5AA800mAh 4/5AA900mAh 4/5AA1000mAh 4/5AA1100mAh 4/5AA1200mAh 4/5AA1300mAh 4/5AA1400mAh 4/5AA1500mAh 4/5AA1600mAh 4/5AA1700mAh 4/5AA1800mAh 4/5AA1900mAh

Ni-MH 4/5SC600mAh 4/5SC700mAh 4/5SC800mAh 4/5SC900mAh 4/5SC1000mAh 4/5SC1100mAh 4/5SC1200mAh 4/5SC1300mAh 4/5SC1400mAh 4/5SC1500mAh 4/5SC1600mAh 4/5SC1700mAh 4/5SC1800mAh 4/5SC1900mAh 4/5SC2000mAh

Ni-MH SC600mAh SC700mAh SC800mAh SC900mAh SC1000mAh SC1100mAh SC1200mAh SC1300mAh SC1400mAh SC1500mAh SC1600mAh SC1700mAh SC1800mAh SC1900mAh SC2000mAh SC2000mAh SC2400mAh SC2600mAh SC2800mAh SC3000mAh

Ni-MH C1500mAh C1800mAh C2000mAh C2500mAh C3000mAh C3500mAh C4000mAh Ni-MH D3000mAh D3500mAh D4000mAh D4500mAh D5000mAh D6000mAh D7000mAh D8000mAh



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443 or email: CN.Doccheck@sgs.com

Printing date 06/13/2017 Reviewed on 06/12/2017

1 Identification

· Product identifier

· Trade name: NI-MH RECHARGEABLE BATTERY

· Recommended use of the chemical and restrictions on use:

· Application of the substance / the preparation:

Solar lights, LED emergency lights, Cordless telephones, Walkmans, Electronic tools and so on.

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: HUIXIAN SUNRISE POWER SOURCE CO.,LTD

· Full address: WEST SUOKELOU, HUQIAO, HUIXIAN CITY HENAN CHINA

· **Phone number:** +86-15903872362

· Email: mingyang.xu@xuridianyuan.com

· Other U.S. contact point: Not available

· Further information obtainable from: HUIXIAN SUNRISE POWER SOURCE CO.,LTD

· Emergency telephone number:

Poison Center

Tel: +1 800 222 1222

+86-13525005219 Mary Wang

· Reference Number: CP17-030174 - SZ, CANEC1710407901

· Remark:

* This sample is likely to be classified as article and is out of scope of a SDS as set out in 29 CFR Part 1910.1200. This SDS is generated for client's reference only.

2 Hazard(s) identification

· Classification of the substance or mixture

Classification according to OSHA Hazard Communication Standard (29 CFR 1910.1200)



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 06/13/2017 Reviewed on 06/12/2017

Trade name: NI-MH RECHARGEABLE BATTERY

(Contd. of page 1)

· Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of OSHA Hazard Communication Standard (29 CFR 1910.1200).

· Classification system:

The classification is according to the latest edition of OSHA Hazard Communication Standard (29 CFR 1910.1200), and extended by company and literature data.

- · Label elements
- · Labelling according to OSHA Hazard Communication Standard (29 CFR 1910.1200)
- · Hazard pictograms







GHS05 GHS07 GHS0

- · Signal word Danger
- · Hazard-determining components of labeling:

nickel dihydroxide

potassium hydroxide

lanthanum, compound with nickel (1:5)

sodium hydroxide

· Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

· Precautionary statements

P260 Do not breathe dusts or mists.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

 $\cdot \textit{Hazards not otherwise classified (HNOC)} \ \textit{No further relevant information available}.$

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture of the substances listed below with nonhazardous additions.

For the wording of the listed hazard statements refer to Section 16.

(Contd. on page 3)

Printing date 06/13/2017 Reviewed on 06/12/2017

Trade name: NI-MH RECHARGEABLE BATTERY

| | (Contd | . of page |
|-------------|---|-----------|
| Composition | n: | |
| 1310-58-3 | potassium hydroxide | 31.6% |
| | Skin Corr. 1A, H314; | 1 |
| 12054-48-7 | nickel dihydroxide | 20.0% |
| | Resp. Sens. 1, H334; Muta. 2, H341; Carc. 1A, H350; Repr. 1B, H360; STOT RE 1, H372; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317 | |
| 7732-18-5 | water | 18.3% |
| 1345-25-1 | iron oxide | 16.7% |
| 12196-72-4 | lanthanum, compound with nickel (1:5) | 8.0% |
| | 🍅 Flam. Sol. 2, H228; 🍪 Carc. 1B, H350; 🕚 Skin Sens. 1A, H317 | |
| 1310-73-2 | sodium hydroxide | 2.8% |
| | 🔗 Skin Corr. 1A, H314 | 1 |
| 7782-42-5 | Graphite | 2.6% |

4 First-aid measures

- · Description of first aid measures
- · General description:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Special protective equipment and precautions for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Printing date 06/13/2017 Reviewed on 06/12/2017

Trade name: NI-MH RECHARGEABLE BATTERY

(Contd. of page 3)

· Methods and material for containment and cleaning up:

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

7 Handling and storage

· Precautions for safe handling:

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

For the general occupational hygienic measures refer to Section 8.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

| 8 Exposure | controls/personal protection |
|-------------|---|
| · Component | s with limit values that require monitoring at the workplace: |
| 1310-58-3 р | potassium hydroxide (31.6%) |
| REL (USA) | Ceiling limit value: 2 mg/m³ |
| TLV(USA) | Ceiling limit value: 2 mg/m³ |
| 12054-48-7 | nickel dihydroxide (20.0%) |
| PEL (USA) | Long-term value: 1 mg/m³ as Ni |
| REL (USA) | Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A |
| 1345-25-1 i | ron oxide (16.7%) |
| REL (USA) | Long-term value: 1 mg/m³ as Fe |
| TLV (USA) | Long-term value: 1 mg/m³ as Fe |
| 1310-73-2 s | odium hydroxide (2.8%) |
| PEL (USA) | Long-term value: 2 mg/m³ |
| REL(USA) | Ceiling limit value: 2 mg/m³ |
| TLV(USA) | Ceiling limit value: 2 mg/m³ |
| 7782-42-5 (| Graphite (2.6%) |
| PEL (USA) | Long-term value: 15 mppcf* mg/m³ *impinger samples counted by light field techn. |
| REL (USA) | Long-term value: 2.5* mg/m³ *respirable dust |
| TLV (USA) | Long-term value: 2* mg/m³ all forms except graphite fibers;*resp. fraction |

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Printing date 06/13/2017 Reviewed on 06/12/2017

Trade name: NI-MH RECHARGEABLE BATTERY

(Contd. of page 4)

- · Based on the composition shown in Section 3, the following measures are suggested for occupational safety measure.
- · Appropriate engineering controls:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

See Section 7 for information about design of technical facilities.

- · Personal protective equipment:
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

Form: Solid
Color: Mixed

Odor: Odorless

Odor threshold: Not available

• **pH-value**: 12

· Change in condition

Melting point/Melting range:Not availableFreezing point:Not availableBoiling point/Boiling range:Not available

(Contd. on page 6)

Printing date 06/13/2017 Reviewed on 06/12/2017

Trade name: NI-MH RECHARGEABLE BATTERY

| | | (Contd. of page |
|-------------------------------------|--|-----------------|
| · Flash point: | Not available | |
| · Flammability (solid, gaseous): | Not available | |
| · Auto-Ignition temperature: | Not available | |
| Decomposition temperature: | Not available | |
| · Explosion limits: | | |
| Lower: | Not available | |
| Upper: | Not available | |
| · Vapor pressure: | Not available | |
| · Density: | Not available | |
| · Relative density | Not available | |
| · Vapor density | Not available | |
| Evaporation rate | Not available | |
| · Solubility in / Miscibility with | | |
| Water: | Not available | |
| Partition coefficient (n-octanol/wa | ter): Not available | |
| · Viscosity: | | |
| Dynamic: | Not available | |
| Kinematic: | Not available | |
| · Other information | No further relevant information available. | |

10 Stability and reactivity

- · Reactivity: Data not available
- · Chemical stability: Data not available
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: Not available
- · Skin corrosion/irritation: Strong caustic effect on skin and mucous membranes.
- · Serious eye damage/irritation:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· Respiratory or skin sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

(Contd. on page 7)

Printing date 06/13/2017 Reviewed on 06/12/2017

Trade name: NI-MH RECHARGEABLE BATTERY

(Contd. of page 6)

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Carcinogenic.

· Carcinogenic categories

| · IARC (International Agency for Research on Cancer) | |
|---|---|
| 12054-48-7 nickel dihydroxide | 1 |
| 12196-72-4 lanthanum, compound with nickel (1:5) | 1 |
| · NTP (National Toxicology Program) | |
| 12054-48-7 nickel dihydroxide | K |
| 12196-72-4 lanthanum, compound with nickel (1:5) | K |
| · OSHA-Ca (Occupational Safety & Health Administration) | |
| None of the ingredients is listed. | |
| | - |

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| · UN-Number | | |
|----------------------------|---------------------------------|--|
| · DOT, IMDG | UN3496 | |
| · IATA | Not applicable | |
| · UN proper shipping name | | |
| $\cdot DOT$, $\dot{I}MDG$ | Batteries, nickel-metal hydride | |
| \cdot IATA | Not applicable | |

(Contd. on page 8)

Printing date 06/13/2017 Reviewed on 06/12/2017

Trade name: NI-MH RECHARGEABLE BATTERY

(Contd. of page 7)

· Transport hazard class(es)

· DOT, IMDG



· Class 9 Miscellaneous dangerous substances and articles

· Label 9

 \cdot IATA

· Class Not applicable

· Label

· Packing group

· **DOT**, **IMDG**, **IATA** Not applicable

· Environmental hazards:

· Marine pollutant: Yes

· Special precautions for user Not applicable.

· EMS Number: F-A,S-I

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

12054-48-7 nickel dihydroxide

12196-72-4 lanthanum, compound with nickel (1:5)

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

12054-48-7 nickel dihydroxide

12196-72-4 lanthanum, compound with nickel (1:5)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 06/13/2017 Reviewed on 06/12/2017

Trade name: NI-MH RECHARGEABLE BATTERY

(Contd. of page 8)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

12054-48-7 nickel dihydroxide

A1

· NIOSH-Ca (National Institute for Occupational Safety and Health)

12054-48-7 nickel dihydroxide

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

16 Other information

· Relevant hazard statements

H228 Flammable solid.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

The contents and format of this SDS are in accordance with 29 CFR 1910.1200(g)

DISCLAIMER OF LIABILITY

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in anyway connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Remark:

* This sample is likely to be classified as article and is out of scope of a SDS as set out in 29 CFR Part 1910.1200. This SDS is generated for client's reference only.

· Date of preparation / last revision 06/13/2017 / -

(Contd. on page 10)

Printing date 06/13/2017 Reviewed on 06/12/2017

Trade name: NI-MH RECHARGEABLE BATTERY

(Contd. of page 9)

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

Flam. Sol. 2: Flammable solids – Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 1A: Carcinogenicity - Category 1A

Carc. 1B: Carcinogenicity - Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

End of document

USA