

Model #516


65' Hose

Model #518

100' Hose



Self-Winding Retractable Wall Mounted Hose Reel Owner's Manual



**VISIT OUR WEBSITE: WWW.LIBERTYGARDENPRODUCTS.COM
OR CALL US TOLL FREE AT 1-866-820-5805**

LIBERTY GARDEN PRODUCTS, INC
1161 SOUTH PARK DRIVE, KERNERSVILLE, NC 27284

IMPORTANT: READ THE OWNER'S MANUAL BEFORE ASSEMBLING


PRE-ASSEMBLY

Estimated Assembly Time : 5 minutes (not including mounting the hose reel)

TOOLS REQUIRED:



Hammer
Drill



Phillips Head
Flat Head
screwdriver
or bits for an
electric drill




Electric
Drill




Stud
Finder

HARDWARE INCLUDED



AA. Wood Screw (4)



BB. Wall Anchor (4)

HARDWARE NOT INCLUDED

CC. Concrete Screws and Washers(4)


Note: Hardware not shown to actual size.

PARTS LIST

A. Reel (1)

B. Mounting Hub (1)

C. Pivot Bar (1)



IMPORTANT: LAY OUT ALL PARTS AND FASTENERS. MAKE SURE ALL PARTS ARE ACCOUNTED FOR. IF ANY PART IS MISSING PLEASE CONTACT LIBERTY GARDEN PRODUCTS AT **1-866-820-5805**.


DO NOT CONTACT THE RETAILER. VISIT OUR WEBSITE, WWW.LIBERTYGARDENPRODUCTS.COM OR E-MAIL CUSTOMERSERVICE@LIBERTYGARDENPRODUCTS.COM FOR MORE INSTRUCTIONS.

ASSEMBLY

1. Secure Mounting Hub (B) to the wall following the installation instructions on page 5, using the Mounting Hardware (AA) or optional Mounting Hardware. (CC)


NOTE: Ensure the Mounting Hub (B) is positioned with the proper distance to reach the outdoor faucet. Check for leaks before mounting.

Step 2





2. Lift up handle on the Hose Reel (A).

3. Holding the Reel (A) and Handle slide the Hose Reel onto the Mounting Hub (B). Align the rear of the Hose Reel with the two verticle holes on the Mounting Hub.



Step 4

4. Insert the Pivot Bar (C) through the Mounting Hub (B) at the rear of the Hose Reel (A) as shown.





Step 3

ASSEMBLY

5. Connect the attached leader hose to outdoor spigot.

NOTE:


Do not over tighten leader hose.



NOTE:


Check for leaks prior to mounting.

Step 5



Step 6

6. To adjust the amount of hose you want to have extending from the Hose Reel (A) use a Phillips Head Screw Driver to loosen the screw on the Hose Reel Stopper. Slide the Stopper to your desired length.



Step 7

OPERATING INSTRUCTIONS



WARNING: In order to retract the hose safely, please ensure you keep hold of the hose end while walking towards the hose reel. Letting go of the hose, may result in injury.

7. This hose reel system has been equipped with an click-lock mechanism. To operate, pull the hose out to the desired length. When you stop pulling, the hose will automatically stop. To engage the automatic hose recoil, give it a short sharp pull and you will feel the hose automatically retract. You can interrupt this process by pulling the hose again. (Hose sprayer not included).

INSTALLATION

This hose reel must be mounted to a solid masonry wall or to wall studs.

Tip: Remember to use the correct size and quantity of hardware to support the total weight of the unit. A standard 100' length of garden hose weighs approximately 15 lbs. Filled with water, the additional weight can exceed 20 lbs. The mounting hardware must be able to support the combined weight of the unit, inside hose, plus water.

1. WOOD SCREWS

The following hardware **(included)** is recommended for installation:

(4) 7 or 8 mm x 60 mm wood screws (1/4" x 2 1/2")

- Using a stud finder, locate wood studs on your wall.

NOTE: If you are unable to locate wood studs, use optional wall anchors **(BB)** to secure mounting hub **(B)** to drywall or masonite.


- Position and hold your mounting hub **(B)** against the wood wall at a convenient height. Mark the position of each suspension hole on the wall. Remove the mounting hub **(B)**.

- Using an electric drill, drill **(4)** pilot holes 1/8" in diameter at the marked positions on the wall.

NOTE: If applicable drill **(4)** 1/4" in diameter holes for wall anchors **(BB)**. Using a hammer, insert anchors **(BB)** into the drywall or masonite.

- Align the mounting hub **(B)** suspension holes with the pilot holes or anchors **(BB)**.

- Attach the mounting hub **(B)** to the wall using wood screws **(AA)** and tighten securely.



2. BRICK OR MASONRY SCREWS (Optional Mounting Method)

The following hardware **(not included)** is recommended for installation:

(4) 7 or 8 mm x 60 mm masonry screws **(CC)** (5/16" x 2 1/2")


(4) Washers

- Position and hold your mounting hub **(B)** against the brick/masonry wall at a convenient height. Mark the position of each suspension hole on the wall. Remove the mounting hub **(B)**.

- Using a hammer drill, drill pilot holes 1/4" in diameter at the marked positions on the wall.

- Align the mounting hub **(B)** suspension holes with the pilot holes.

- Attach the mounting hub to the wall using concrete screws with washers and tighten securely.



To learn more, visit our warranty and care section @ www.libertygardenproducts.com

CARE AND MAINTENANCE

WINTERIZING AND STORAGE

Drain the hose reel prior to the onset of freezing temperatures. If any trapped water freezes, it may cause damage to the hose reel, hose, and even your pipes.

Store the entire unit - including hose reel and hose - inside your garage or storage shed at above-freezing temperatures. Storing your hose reel inside during the winter is an excellent way of protecting your garden hose, leader hose and O-Rings.

When you install your hose reel, be sure the hose washers are in place and all fittings are secure. If you live in more temperate climates, be sure to drain the unit of any residual water before storing.

- **DO NOT EXPOSE UNIT TO FREEZING TEMPERATURES** while water remains in the plumbing system, this can damage the hose connections.

- **DO NOT** leave water running through the reel while not in use or unsupervised.

Your retractable hose reel is manufactured with the finest quality components available. This product will give you many seasons of reliable and functional hose storage. All components in the product are manufactured to rigorous quality standards not common in other consumer grade hose reels available today. In the case of wall mounted reels, be sure to use stainless steel mounting hardware. We recommend that you periodically inspect your reel for any surface damage. **NOTE: Liberty Basic's plastic hose reels use ultraviolet light stabilizers in our plastic, but over time, the plastic color, depending on the amount of sunlight, can fade.**



WARNING: Do not immerse the reel in the water to clean it.



IMPORTANT: The hose reel includes a medium-duty hose. After use, turn off the water. Sunlight can heat the water and damage the hose, which will cause the hose to be difficult to rewind. Therefore, it is best to turn the water off before retracting the hose. Do not leave the reel outside in cold temperatures. Do not allow the hose to come into contact with any chemical or substance, such as acetone, white spirits, lactic acid, etc.

WARNING: DO NOT consume water from garden hose; not fit for human consumption.



WARNING: Cancer and Reproductive Harm
- www.p65warnings.ca.gov

**CALL US AT 1-866-820-5805 IF YOU HAVE ANY QUESTIONS
REGARDING CARE AND MAINTENANCE**

LIBERTY GARDEN PRODUCTS LIMITED WARRANTY

(Effective December 16, 2019)

This limited warranty is applicable to each original end-customer (hereinafter "Customer") purchasing the model 516 and 518 Self-Winding Retractable Wall Mounted Basic Hose Reel.

1. LIMITED WARRANTY; EXCLUSIVE REMEDIES:

1.1. LIMITED WARRANTY ON PRODUCTS: Company warrants solely to the original Customer that (a) the Structural Frame will be free from defects in materials and workmanship under normal use for a period of three (3) YEAR(S) from the date of original retail purchase, and (b) the Non-Frame Parts (which consist of the crank handle, water connections, leader hose and will be free from defects in materials and workmanship under normal use for a period of ONE (1) YEARS from the date of original retail purchase. Notwithstanding the foregoing, the colors and finishes of the Products may vary within a reasonable scope due to unavoidable color variations in different production batches, and such variations shall not constitute a material defect. This limited warranty is limited solely to the original Customer with proof of purchase and is not transferable.

1.2. THE WARRANTY: During a covered Product's limited warranty period, Company will, at Company's sole option and discretion, (1) repair the defective component or product without charge or (2) replace the defective component or product without charge.

1.3. The foregoing limited warranty is subject to the Customer's proper storage, transportation, handling and use of the Products as the same are defined within Company's then-current published guides and instructions for use and care. The limited warranty does not include defects due to normal wear and tear, abuse or misuse, mishandling, neglect, accident, fire, lightning, sunlight or other natural hazard, delivery or transportation damage, failure to follow applicable directions or instructions, or improper or inadequate cleaning, maintenance, care, repairs, modifications, or use beyond a Product's intended use. Please note that since the Structural Frame is made from plastic, fading may occur over time. As such, this limited warranty does not include color fading or defects due to the same.

1.4. LIMITED WARRANTY CLAIMS PROCEDURE: To obtain performance under this limited warranty, Customer shall notify Company in writing (to Liberty Garden Products, Inc., 1161 South Park Drive, Kernersville, NC 27284, Attn: Customer Service / Warranty Department), by email (to customerservice@libertygardenproducts.com), or by telephone (to (336) 992-3595) with a full description of the defect that is covered by warranty and a copy of the dated proof of purchase of the applicable product. Our warranty is limited to items purchased in new condition from authorized distributors.

- Company shall review each such claim and issue Customer a return merchandise authorization ("RMA") in the event that the described defect or condition merits warranty review as determined by Company. Customers who have been issued a RMA shall, at Company's election, return the covered item to the same physical address listed above for reporting initial claims. Company shall not accept any returned product without a RMA.

- Upon receipt, Company will evaluate the returned product(s) to determine if there is a warranty claim and, if so, how Company wishes to remedy the same. During a covered product's respective limited warranty period, Company will, at Company's sole and absolute option and discretion, (1) repair the defective component or product without charge or (2) replace the defective component or product without charge. Refunds are not available pursuant to this limited warranty.

- Customer is solely responsible for transportation of the covered product(s) to the Company for evaluation (if applicable and requested by Company). In the event that Company determines that a claim under this limited warranty is justified, Company shall be responsible for transportation of the repaired, corrected, replaced or exchanged product back to Customer. Customer shall be solely responsible for the transportation of any product back to Customer if Company determines that a claim under this warranty is not justified.

- Any repaired, corrected, replaced or exchanged Products shall be subject to the Limited Warranty set forth to the duration of the original limited warranty period as set forth in Section 1.1. and not for any extended duration, following their repair, correction, replacement or exchange.

1.5. IF A COMPANY PRODUCT DOES NOT CONFORM TO THESE LIMITED WARRANTIES, THE PURCHASER'S SOLE AND EXCLUSIVE REMEDY IS, AT COMPANY'S SOLE AND EXCLUSIVE OPTION, THE (1) REPAIR OF ANY DEFECTIVE PRODUCT OR COMPONENT PART OR (2) REPLACEMENT OF ANY DEFECTIVE PRODUCT OR COMPONENT PART. THE LIMITED WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND MADE IN LIEU OF ALL OTHER WARRANTIES, REMEDIES, RIGHTS OR CONDITIONS, WHETHER ORAL OR WRITTEN, EXPRESS OR IMPLIED, EITHER IN FACT OR BY OPERATION OF LAW, STATUTORY OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. COMPANY SPECIFICALLY DISCLAIMS, WITHOUT LIMITATION, ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, OF ANY KIND. IF COMPANY CANNOT LAWFULLY DISCLAIM IMPLIED WARRANTIES UNDER THIS LIMITED WARRANTY, ALL SUCH WARRANTIES, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO THE DURATION OF THIS LIMITED WARRANTY. The Company does not assume or authorize any person to assume for them any other liability in connection with the Products.

LIBERTY GARDEN PRODUCTS LIMITED WARRANTY CONTINUED

2. EXCLUSION AND LIMITATION OF LIABILITY:

IN NO EVENT, WHETHER BASED ON CONTRACT OR TORT OR OTHER LEGAL THEORY, SHALL COMPANY BE LIABLE FOR ANY INDIRECT, INCIDENTAL, PUNITIVE, SPECIAL OR CONSEQUENTIAL DAMAGES, INCLUDING BUT NOT LIMITED TO, DAMAGES TO OTHER PROPERTY, INCONVENIENCE, DAMAGES FOR LOSS OF PROFITS, REVENUE, GOODWILL OR USE, INCURRED BY CUSTOMER OR ANY THIRD PARTY, WHETHER IN AN ACTION IN CONTRACT, TORT, STRICT LIABILITY, OR IMPOSED BY STATUTE, OR OTHERWISE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages or exclusions or limitations on the duration of implied warranties or conditions, so the above limitations or exclusions may not apply to Customer. In jurisdictions that limit the scope of or preclude limitations or exclusion of remedies or damages, or of liability, such as liability for gross negligence or willful misconduct or do not allow implied warranties to be excluded, the limitation or exclusion of warranties, remedies, damages or liability set forth above are intended to apply to the maximum extent permitted by applicable law. This limited warranty gives the Customer specific legal rights, and the Customer may also have other rights that vary by state, country or other jurisdiction.

3. SEVERABILITY:

If any provision of this limited warranty is held to be illegal, invalid or otherwise unenforceable, such provision will be enforced to the extent possible consistent with its stated intention, or, if incapable of such enforcement, will be deemed to be severed and deleted from this limited warranty, while the remainder of the terms of this limited warranty will continue in full force and effect.

4. DISPUTE RESOLUTION:

This Liberty Garden Products, Inc. Limited Warranty shall be governed by and construed in accordance with the laws of the State of North Carolina, without regard to its principles of conflicts of law. The parties acknowledge the exclusive jurisdiction of the federal and state courts of the State of North Carolina. Any claims or disputes under this Liberty Garden Products, Inc. Limited Warranty shall be heard exclusively in any state or federal courts sitting in Guilford County, North Carolina, and both parties expressly consent to the personal jurisdiction and venue of the North Carolina state and federal courts for such actions.



"Liberty" is a registered trademark of Liberty Garden Products, Inc. Kernersville, NC. All Rights Reserved 2019

Updated 12/16/2019