



Composite Thermal Expansion

BIG PROTECTION. COMPACT SIZE.

THERM TROL

For Tankless Water Heaters



THERMYTROL

The Therm-X-Trol ST-1 absorbs thermal expansion and water hammer in tankless and point-of-use water heaters to protect the heat exchanger. Simple to install, the ST-1 features a patented air cell and requires no precharge adjustment or maintenance. With a 304SS waterway and a 7-Year limited warranty, the ST-1 has big protection in a compact size.

7-Year Warranty

· Longest warranty in the industry.

Patented Air Cell

- Proprietary, sealed design never requires charging.
- Superior water hammer capacity.
- Entire air cell surface absorbs energy for greater protection.

Advanced Composite Material

- Durable and corrosion proof.
- Impact resistant polymer.

Worry-Free Longevity

- Patented technology eliminates sliding parts.
- No pistons or o-rings to wear out.

Specifications

Diameter: 3.4" Height: 4.0" System Connection: 1/2" NPTM Maximum Operating Temperature: 140°F Maximum Working Pressure: 150 psig Shipping Weight: 1 lb.



Typical Installation

Tankless Water

Heater

Т&Р

Relief

Hot Water

ST-1

THERM-X-TROL

Backflow Preventor Check Valve or

Pressure Reducing Valve

Cold

Water

Supply

1400 Division Road, West Warwick, RI USA 02893 T: 800.426.8765 www.amtrol.com



