



## Main

Product or component type	Load Center
Range of product	QO
Load center type	Fixed mains (back-fed main breakers)
Line Rated Current	60 A
Number of spaces	4
Short-circuit current	10 kA
Number of circuits	8
Number of tandem circuit breakers	4
Phase	1 phase

## Complementary

AWG gauge	AWG 8...AWG 2 (aluminium/copper)
NEMA degree of protection	NEMA 1 indoor
Cover type	Surface cover with door
Device composition	Grounding bar (ordered separately)
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Surface finish	Baked enamel grey
Box number	4
Product certifications	UL listed
Height	319 mm
Width	8.9 in (226 mm)

## Environment

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1411 - Schneider Electric declaration of conformity	Compliant - since 1411 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.