SAFETY DATA SHEET



1. Identification

Product identifier UNITED COATINGS ROOF MATE BASE COATING

Other means of identification

Product Code

Recommended use Acrylic elastomeric coating.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

Company name GAF

1 Campus Drive

Parsippany, NJ 07054 USA

Telephone 1-800–766–3411

Emergency phone number CHEMTREC [DAY OR NIGHT] 1-800-424-9300

Within USA and CANADA 1-800-424-9300 Outside USA and Canada: 1 703-741-5970

Collect Calls Accepted

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSensitization, skinCategory 1Environmental hazardsHazardous to the aquatic environment, acuteCategory 3

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. Harmful to aquatic life.

Precautionary statement

Prevention Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the

workplace. Avoid release to the environment. Wear protective gloves.

Response If on skin: Wash with plenty of water. Specific treatment (see this label). If skin irritation or rash

occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Calcium Carbonate		1317-65-3	20 to <30
Aluminum Trihydroxide		21645-51-2	10 to <20
Aqua Ammonia (10-30%)		1336-21-6	0.1 to <1

Material name: UNITED COATINGS ROOF MATE BASE COATING SDS US

Version #: 02 Revision date: 11-17-2015

Chemical name	Common name and synonyms	CAS number	%
CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER		10605-21-7	0.1 to <1
Chloro-2-methyl-4-isothiazolin-3-on e		26172-55-4	0.1 to <1
PARAFFINIC PETROLEUM OIL		64742-54-7	0.1 to <1
Non-Hazardous Ingredients			50 to <60

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Upper respiratory tract irritation. Irritation of eyes and mucous membranes. Coughing. Skin irritation. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

supervisory personnel of all environmental releases.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or

Material name: UNITED COATINGS ROOF MATE BASE COATING

sds us

7. Handling and storage

Precautions for safe handling Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged

exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid

release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Aqua Ammonia (10-30%) (CAS 1336-21-6)	PEL	35 mg/m3	
		50 ppm	
Calcium Carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Aluminum Trihydroxide (CAS 21645-51-2)	TWA	1 mg/m3	Respirable fraction.
Aqua Ammonia (10-30%) (CAS 1336-21-6)	STEL	35 ppm	
	TWA	25 ppm	
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
Aqua Ammonia (10-30%) (CAS 1336-21-6)	STEL	27 mg/m3	
		35 ppm	
	TWA	18 mg/m3	
		25 ppm	
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. **Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Liquid.

ColorNot available.OdorNot available.Odor thresholdNot available.pHNot available.

Melting point/freezing point 572 °F (300 °C) estimated

Initial boiling point and boiling

range

Not available.

Flash point 999.0 °F (537.2 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.00001 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 11.40 lbs/gal

Flammability class Combustible IIIB estimated

Percent volatile 47.74 % Specific gravity 1.37

VOC 6.633669 g/l Regulatory estimated

0.055359 lbs/gal Regulatory estimated 3.491367 g/l Material estimated 0.029136 lbs/gal Material estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Fluorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Irritation of eyes and mucous membranes. Upper respiratory tract irritation. Coughing. Skin

irritation. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Components Species Test Results

Aluminum Trihydroxide (CAS 21645-51-2)

Acute Oral

LD50 Rat > 5000 mg/kg

Aqua Ammonia (10-30%) (CAS 1336-21-6)

<u>Acute</u> Oral

LD50 Rat 350 mg/kg

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Rat 2000 mg/kg

Oral

LD50 Guinea pig > 5000 mg/kg

Mouse 11000 mg/kg
Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Components Species Test Results

Aqua Ammonia (10-30%) (CAS 1336-21-6)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 15 mg/l, 96 hours

SDS US 5 / 8

^{*} Estimates for product may be based on additional component data not shown.

Components Species Test Results

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)

Aquatic

Fish LC50 Channel catfish (Ictalurus punctatus) 0.009 - 0.015 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL

ESTER

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

1.52

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chloro-2-methyl-4-isothiazolin-3-one (CAS 26172-55-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Aqua Ammonia (10-30%) (CAS 1336-21-6) Listed. CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL Listed.

ESTER (CAS 10605-21-7)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

^{*} Estimates for product may be based on additional component data not shown.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Aqua Ammonia (10-30%)	1336-21-6	0.1 to <1	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)

US. Massachusetts RTK - Substance List

Aqua Ammonia (10-30%) (CAS 1336-21-6) Calcium Carbonate (CAS 1317-65-3)

US. New Jersey Worker and Community Right-to-Know Act

Aqua Ammonia (10-30%) (CAS 1336-21-6)

Calcium Carbonate (CAS 1317-65-3)

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Aqua Ammonia (10-30%) (CAS 1336-21-6)

Calcium Carbonate (CAS 1317-65-3)

US. Rhode Island RTK

Aqua Ammonia (10-30%) (CAS 1336-21-6)

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

3-(3,4 Dichlorophenyl)-1,1-Dimethylurea (CAS Listed: May 31, 2002

330-54-1)

DIPHENYL KETONE (CAS 119-61-9)

MONOAZO PIGMENT (CAS 13463-67-7)

Listed: June 22, 2012

Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Country(s) or region Inventory name On inventory (yes/no)*

KoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryNo

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 12-18-2014

 Revision date
 11-17-2015

Version # 02

HMIS® ratings Health: 2

Flammability: 0 Physical hazard: 0 Personal protection: D

NFPA ratings Health: 2

Flammability: 0 Instability: 0

Disclaimer This information relates to the specific material designated and may not be valid for such material

used on combination with any other materials or in any process. Such information is to the best of

our knowledge and belief accurate and reliable as of the date compiled. However, \boldsymbol{no}

representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or

damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information Product and Company Identification: Converted to GAF SDS

Yes