



Creating a bit of competition for Mother Nature
www.nantucketpavers.com

GENERAL PRODUCT INFORMATION

COLOR

The colors shown in our brochure are as accurate as printing and photographic processes allow. It is essential for the customer to select products they want by inspecting each item for their approval in color during the daylight.

EFFLORESCENCE

Every concrete product that contains a high cement content can suffer from Efflorescence. This is a natural phenomenon which is beyond our control. The product may form patches of white which gives the impression that the color is fading, however with time the patches will disappear as natural weathering takes place. Conditions where condensation or rising ground water can permeate the concrete over an extended period, followed by slow drying, will promote the formation of efflorescence. The efflorescence will be eroded by rain, which is slightly acidic. As nature causes the problem, nature sometimes holds the cure. Efflorescence does not affect the durability and performance of concrete in question. Nantucket Pavers can not be held responsible for this natural phenomenon.

REMOVAL OF EFFLORESCENCE

Efflorescence can be removed mechanically by dry brushing or washing with chemical masonry cleaner. Nantucket Pavers recommends Vexcon - Paver Reneu products for as chemical masonry cleaner. Paver Reneu Etch & Efflorescence Remover is recommended— follow the instructions that come with the bottle. Before attempting to remove efflorescence by these techniques it is recommended that trials should be carried out on samples, or a limited area, in order to assess the effect on the appearance.

DE-ICING SALT

De-icing Salt is not recommended for use on this product. The use of salt can affect both the durability and the looks of the paving during continual freezing and thawing. Nantucket Pavers is not responsible for any product damage resulting from the use of De-Icing Salt.

DEFECTIVE PRODUCT

Should a product reach you in an unsatisfactory condition, and other than a naturally occurring one as described above, the defect should have to be apparent prior to laying. It is at this point that the supplier should be notified of such a fault, allowing time for the rejected product to be replaced. If the complaint is raised after laying the product, no responsibility will be accepted for any delays, relaying or removing costs.

INSTALLATION

Nantucket Pavers recommends using a traditional “sand set” installation method for all of Nantucket Pavers products. With this method you have greater control over your base and easier placement of blocks that may become damaged over time. Nantucket Pavers **DOES NOT** recommend using Stone Dust/Quarry Dust base as an installation method. Stone Dust/Quarry Dust does not allow adequate drainage of water and has also caused damage to the product due to a substance in the dust. Nantucket Pavers is not responsible for any product that has been installed with Stone Dust/Quarry Dust.