BEHR PREMIUM® AEROSOL
METALLIC, HAMMERED, TEXTURED, AND SAND FINISHES

PRODUCT INFORMATION

BEHR PREMIUM® Aerosol features an enhanced formulation that combines paint and primer† in a single can, delivering a premium, durable finish. Designed for both indoor and outdoor use, BEHR PREMIUM Aerosol can be used on wood, metal, plastic, cast stone and wicker. Weather and corrosion resistant, it delivers a reliable, long-lasting finish. The unique, ergonomic shape of the BEHR PREMIUM Aerosol can and its comfort tip deliver a superior spray experience that fights fatigue so you can create a smooth finish every time.

†A primer coat may be needed on some surfaces.

RECOMMENDED USES:

Use on properly prepared surfaces such as:

• Wood • Metal • Plastic • Cast Stone • Wicker

COLOR AND SHEEN ON THE CAP IS REPRESENTATIVE OF THE PRODUCT.

PRODUCT SPECIFICATIONS:

Metallic:

B060144	Metallic Gold Gloss
B060244	Metallic Oil Rubbed Bronze Satin
B060444	Metallic Copper Gloss
B060544	Metallic Soft Iron Satin
B060644	Metallic Vintage Gold Gloss
B060744	Metallic Nickel Satin
B060844	Metallic Titanium Gloss
B061744	Metallic Champagne Gold Matte
B061844	Metallic Dark Steel Gloss
B062044	Metallic Antique Copper Gloss
B062244	Metallic Burnished Amber Matte
B062444	Metallic Rose Gold Satin
B062544	Metallic Blue Gloss
B063044	Metallic Red Gloss
B063144	Metallic Antique Brass Satin
B063244	Metallic Bronze Satin

Hammered:

B060944	Hammered Black Gloss
B061044	Hammered Brown Gloss
B061244	Hammered Burnished Amber Gloss
B061344	Hammered Antique Pewter Gloss
B061444	Hammered Dark Bronze Gloss
B061644	Hammered White Gloss
B062344	Hammered Chestnut Gloss
B062844	Hammered Copper Gloss
B062944	Hammered Gold Gloss

Textured:

B061544	Black Matte Textured

Sand:

B063544	Artisan Sand Matte
B063644	Mountain Stone Matte

Sheen:

Flat/Matte: < 5 @ 60°
Satin: 20 – 30 @ 60°
Gloss: > 85 @ 60°

Sheen level depends on porosity of surface and various surface irregularities.

Resin Type: Modified Alkyd

Net Weight: 12 oz / 340 g

***% Solids by Volume:** 17% ± 2%

***% Solids by Weight:** 21% ± 2%

Max Product Weighted MIR:
Metallic Gloss & Satin: 1.25
Metallic Matte & Textured Matte: 0.80
Hammered Gloss: 0.95

Coverage: 12 sq ft per can, depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:

- Cover adjacent areas to avoid overspray.
- Shake can vigorously for one minute after mixing ball begins to rattle and often during use.
- Hold can upright, moving from side-to-side while spraying lightly and evenly about 12" from area being painted.
- Always start and finish spraying off the object. Each spray pass should overlap the previous pass by half.
- Test your spray application technique on a scrap surface or inconspicuous area before starting the project.
- Apply multiple thin coats to prevent dripping and sagging. Two to three thin coats produce best results. Allow to dry between each coat.
- Dries to Touch in 15–30 min. Cooler Temperatures or higher humidity may prolong drying time.
- Use BEHR Primer for enhanced adhesion over bare wood and metal.

†**NOTE:** Use BEHR PREMIUM® Chalk Decorative Aerosol No. 714044 over glossy surfaces to create a matte finish.

Dry Time: @ 77°F (25° C) and 50% RH:
Allow to dry between each coat.

To Touch: 15 minutes

To Recoat: before 1 hour or after 24 hours

SURFACE PREPARATION:

- The surface must be clean, free of dust, grease, wax, peeling paint, mold and mildew. If washing is necessary, use a nonsoapy detergent or a TSP substitute. Rinse well and allow to dry.
- Scrape off loose paint and sand to a smooth surface.
- For maximum adhesion, sand glossy surfaces thoroughly before coating. For optimal adhesion to difficult surfaces apply a coat of primer such as BEHR® Interior/Exterior Bonding Primer, BEHR® Multi-Surface Interior/Exterior Primer & Sealer No. 436 or KILZ® Original Aerosol (for smaller areas).

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN-UP/DISPOSAL:

- Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released. If spray nozzle becomes clogged, remove and clean with VOC-compliant paint thinner or mineral spirits where allowed. Otherwise use acetone.
- Clean fresh overspray with VOC-compliant paint thinner or mineral spirits. Otherwise use acetone. Remove dried paint with paint remover, but test small area first to ensure paint remover does not damage substrate.
- Please consider donating any unused product. For recycling or disposal information contact your local household refuse collection service.

CAUTIONS/LIMITATIONS:

- Do not stick pins or wire into can opening.
- Ensure adequate ventilation when spraying indoors.
- For best results, apply when air, material and surface temperatures are between 50°F and 90°F. Avoid painting in direct sunlight. Temperature and humidity extremes can affect dry time and final appearance.
- Shelf life under normal conditions is two years unopened.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a Behr Paint Company representative, call 1-800-854-0133 or visit behr.com. ©2024 Behr Process Corporation, Santa Ana, CA 92705 U.S.A.

Revised 1/2024

*Values given here are from BEHR PREMIUM® Aerosol Gloss White.

BEHR PREMIUM® AEROSOL
METALLIC, HAMMERED, TEXTURED, AND SAND FINISHES

GENERAL INFORMATION:

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. CAUSES SERIOUS EYE DAMAGE. IRRITATES SKIN AND RESPIRATORY TRACT. VENTILATION REQUIRED: To avoid inhalation and combustion hazards (see below), DO NOT use this product unless you can achieve cross ventilation by opening windows and doors during application and drying. **MAY CONTAIN: ACETONE, BUTYL ACETATE, PROPANE, ISOBUTANE, N-BUTANE, 1-METHOXY-2-PROPANOL ACETATE, CALCIUM CARBONATE, METHYL ETHYL KETONE, 3-ETHOXYPROPIONIC ACID ETHYL ESTER, ALUMINUM, HYDROTREATED LIGHT DISTILLATES, STODDARD SOLVENT, ALIPHATIC PETROLEUM DISTILLATES, LIGHT AROM. SOLVENT NAPHTHA (PETROLEUM), HEAVY HYDROTEATED NAPHTHA (PETROLEUM), COBALT CARBOXYLATE, ZIRCONIUM CARBOXYLATE, CARBON BLACK, TITANIUM DIOXIDE AND CRYSTALLINE SILICA.** May affect the brain or nervous system causing dizziness, headache or nausea. **CAUSES SERIOUS EYE DAMAGE. IRRITATES SKIN, NOSE AND THROAT.** Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. **VAPORS MAY IGNITE EXPLOSIVELY.** Do not spray near sparks, heat or open flame. Do not smoke. Vapors are heavier than air and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. **WARNING-CONTENTS UNDER PRESSURE.** Do not puncture or incinerate container. Do not expose to heat or store at elevated temperatures above 120°F. Prolonged exposure to sun may cause bursting.

First Aid: If you experience difficulty breathing, leave the area to obtain fresh air. If difficulty continues,get medical attention immediately. If swallowed, call physician immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a Behr Paint Company representative, call 1-800-854-0133 or visit behr.com. ©2024 Behr Process Corporation, Santa Ana, CA 92705 U.S.A.

Revised 1/2024