





Gorilla Waterproof Patch & Seal Tape has an extra strong, extra thick adhesive **DIRECTIONS:** layer that helps conform to surfaces to seal out water, air and moisture. With For best results, apply the tape to a clean surface at room temperature. Waterproof Patch & Seal Tape can be applied in hot, cold, wet and dry conditions.

2. Remove the release liner and place tape over desired repair area. Tape cannot be repositioned once applied. At 4" wide, patch holes, cracks, gaps and tears!



Made in USA 🚟

DOMESTIC & IMPORTED MATERIALS 2019 THE GORILLA GLUE CO. CINCINNATI, OH 45241 1-800-966-3458 www.gorillatough.com

its UV resistant, waterproof backing, it can be used both indoors and out. Gorilla

1. Keeping liner on tape, cut tape to desired size. Tape size should be larger than the repair area, extending beyond all edges.

3. Rub entire surface of the tape aggressively, especially the edges.

STORAGE: Store tape on the top and bottom disc at room temperature. Edges of tape may be sticky.

SERVICE TEMP: -70°F-200°F

Performance will be dependent on surfaces & conditions. Surfaces must be clean, smooth and non-porous. Water must be pressed out from underneath tape. Not for use on seams, applications under pressure, or automotive applications under the hood. May not adhere to silicone or water-repellent materials. Do not use to hang. Permanent: may damage surface if removed.

Plastic Metal/Aluminum Rubber Wood Vinyl Glass Steel Acrylic

Roofing Gutters RVs/Campers PVC Pool Liners & Covers Windows DIY Projects





4 in. x 10 ft. Roll (10.16 cm x 3.04 m) 3.75 in