According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 6-Nov-2018Product name: Polymer Li-ion Battery PackPrinting date: 6-Nov-2018

1. Identification

(a) Product identifier

Product name: Polymer Li-ion Battery Pack

(b) Other means of identification

Product description: Model: SUM 301321

Nominal Voltage: 3.7V Ampere-hour: 0.06Ah Typical Capacity: 60mAh

Weight: 1.5g

Dimension: 30mm×13mm×23mm (L×W×T)

(c) Recommended use of the chemical and restrictions on use

Recommended use: LITHIUM ION BATTERIES.
Restriction on use: No information available.

(d) Details of the supplier of the product

Company name Dongguan SUM Electronics Technology Co., Ltd.

Address: C4 Zhongdingtongxun Industrial Park No.172 Huancun Road Jinxiaotang Zhutang

Village Fenggang Town Dongguan Guangdong

E-mail: 309495795@qq.com Telephone: +86-769-89332182

(e) Emergency phone number

+86-13620013950

2. Hazard(s) identification

(a) Classification of the chemical

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Skin sensitization	Category 1
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

(b) GHS Label elements, including precautionary statements

Emergency Overview

Signal word Danger

Hazard Statements

Harmful if swallowed

Causes severe skin burns and eye damage May cause an allergic skin reaction

Causes serious eye damage

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 6-Nov-2018Product name: Polymer Li-ion Battery PackPrinting date: 6-Nov-2018

Causes damage to organs through prolonged or repeated exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Precautionary Statements – Response

Specific measures (see .? on this label)

Immediately call a POISON CENTER or doctor/physician

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician.

if you feel unwell, Rinse mouth. Don't induce vomiting

Precautionary Statements - Storage: Store locked up

Precautionary Statements – Disposal: Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC): Not applicable

(c) Other information

Very toxic to aquatic life with long lasting effects;

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN Revision date: 6-Nov-2018 Product name: Polymer Li-ion Battery Pack Printing date: 6-Nov-2018

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

(d) Interactions with Other Chemicals

No information available.

3. Composition/information on ingredients

(a) Mixtures information					
Chemical name	CAS No.	Concentration%			
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	34.8			
Graphite	7782-42-5	18.9			
Phosphate(1-), hexafluoro-, lithium	21324-40-3	19.4			
Aluminum	7429-90-5	5.0			
Copper	7440-50-8	11.5			
Polyethylene	9002-88-4	4.1			
Polypropylene	9003-07-0	2.5			
Nylon	25038-54-4	3.8			

4. First-aid measures

(a) Description of first aid measures

General Advice First aid is upon rupture of sealed battery.

Eve contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye

wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to

do. Continue rinsing. Seek immediate medical attention/advice.

Skin contact: Wash off immediately with soap and plenty of water while removing all contaminated clothes and

shoes. Immediate medical attention is required. May cause an allergic skin reaction.

Inhalation: Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention

> immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen.

Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.

Ingestion: Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give

anything by mouth to an unconscious person. Call a physician or poison control center

immediately.

Self-protection of

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect the first aider: themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid

direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal

protective equipment as required. Wear personal protective clothing (see section 8).

(b) Most important symptoms/effects, acute and delayed

Most important Itching, Coughing and/ or wheezing. Burning sensation.

symptoms and

effects:

(c) Indication of any immediate medical attention and special treatment needed

Notes to Physician Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Product name: Polymer Li-ion Battery Pack

Revision date: 6-Nov-2018

Printing date: 6-Nov-2018

perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. Fire-fighting measures

(a) Extinguishing media

Suitable extinguishing media: Use foam, dry powder or dry sand, CO_2 as appropriate.

Unsuitable extinguishing media: No information available.

(b) Special hazards arising from the chemical

Under fire conditions, batteries may burst and release hazardous decomposition products when exposed to a fire situation. This could result in the release of flammable or corrosive materials. Hazardous combustion products: CO, CO₂, Metal oxides, Irritating fumes

(c) Special protective equipment and precautions for fire-fighters

Firefighters must wear fire resistant protective equipment and appropriate breathing apparatus. The staff must equip with filtermask (full mask) or isolated breathing apparatus. The staff must wear the clothes which can defense the fire and the toxic gas. Put out the fire in the upwind direction. Remove the container to the open space as soon as possible. Spray water on the containers in the fireplace to keep them cool until finish extinguishment.

6. Accidental release measures

(a) Personal precautions, protective equipment and emergency procedures

Personal Precautions In case of rupture. Attention! Corrosive material. Avoid contact with skin,

eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away

from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

(b) Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage

or spillage if safe to do so. Should not be released into the environment. Do not

allow to enter into soil/subsoil. Prevent product from entering drains.

(c) Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. Handling and storage

(a) Precautions for safe handling

Handling In case of rupture. Handle in accordance with good industrial hygiene and

safety practice. Avoid contact with skin, eyes or clothing. Use personal

protection equipment.

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 6-Nov-2018Product name: Polymer Li-ion Battery PackPrinting date: 6-Nov-2018

(b) Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect

from moisture. Keep out of the reach of children. Store away from other

materials.

Incompatible Products Acids. Bases. Oxidizing agent.

8. Exposure controls/personal protection

(a) Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TWA: 0.02 mg/m ³		
Graphite 7782-42-5	TWA: 2 mg/m3 respirable fraction all forms except graphite fibers	TWA: 15 mg/m3 total dust synthetic TWA: 5 mg/m3 respirable fraction synthetic (vacated) TWA: 2.5 mg/m3 respirable dust natural (vacated) TWA: 10 mg/m3 total dust synthetic (vacated) TWA: 5 mg/m3 respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m3 TWA: 2.5 mg/m3 respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m3 F	TWA: 2.5 mg/m3 F TWA: 2.5 mg/m3 dust (vacated) TWA: 2.5 mg/m3	
Copper 7440-50-8	TWA: 0.2 mg/m3 fume TWA: 1 mg/m3 Cu dust and mist	TWA: 0.1 mg/m3 fume TWA: 1 mg/m3 dust and mist (vacated) TWA: 0.1 mg/m3 Cu dust, fume, mist	IDLH: 100 mg/m3 dust, fume and mist TWA: 1 mg/m3 dust and mist TWA: 0.1 mg/m3 fume
Aluminum 7429-90-5	TWA: 1 mg/m3 respirable fraction	TWA: 15 mg/m3 total dust TWA: 5 mg/m3 respirable fraction (vacated) TWA: 15 mg/m3 total dust (vacated) TWA: 5 mg/m3 respirable fraction (vacated) TWA: 5 mg/m3 Al Aluminum	TWA: 10 mg/m3 total dust TWA: 5 mg/m3 respirable dust

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life

or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992) See section 15 for national exposure control parameters

(b) Appropriate engineering controls

Engineering Measures Showers

Eyewash stations
Ventilation systems

(c) Individual protection measures, such as personal protective equipment

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 6-Nov-2018Product name: Polymer Li-ion Battery PackPrinting date: 6-Nov-2018

Eye/Face Protection None required for consumer use. If there is a risk of contact:. Tight sealing safety

goggles. Face protection shield.

Skin and Body Protection None required for consumer use. If there is a risk of contact:. Wear protective gloves

and protective clothing.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits

are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat,

drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

Wash hands before breaks and immediately after handling the product. For

environmental protection, remove and wash all contaminated protective equipment

before re-use.

9. Physical and chemical properties

(a) Appearance Solid (b) Odor **Odorless** (c) Odor threshold Not available. (d) pH Not available. (e) Melting point/freezing point Not available. (f) Initial boiling point and boiling range Not available. (g) Flash point Not applicable. (h) Evaporation rate Not applicable. Non flammable. (i) Flammability (j) Upper/lower flammability or explosive limits Not available. (k) Vapor pressure Not applicable. Not available. (I) Vapor density (m) Relative density Not available. Insoluble in water. (n) Solubility(ies) (o) Partition coefficient: n-octanol/water Not available. (p) Auto-ignition temperature Not available. (q) Decomposition temperature Not available. Not available. (r) Viscosity

10. Stability and reactivity

(a) Reactivity

Stable under recommended storage and handling conditions.

(b) Chemical stability

Stable under recommended storage conditions.

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Product name: Polymer Li-ion Battery Pack

Revision date: 6-Nov-2018

Printing date: 6-Nov-2018

(c) Possibility of hazardous reactions

None under normal processing.

(d) Conditions to avoid

Exposure to air or moisture over prolonged periods.

(e) Incompatible materials

Strong oxidizer, strong acid.

(f) Hazardous decomposition products

Carbon oxides.

11. Toxicological information

(a) Information on the likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or

supplied information.

In case of rupture:

Inhalation: Specific test data for the substance or mixture is not available. Corrosive by

inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory

tract.

Ingestion: Specific test data for the substance or mixture is not available. Causes

burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea. May be harmful if swallowed.

Skin contact: Specific test data for the substance or mixture is not available. Corrosive.

(based on components). Causes burns. May be absorbed through the skin

in harmful amounts. Harmful in contact with skin.

Eye contact: Specific test data for the substance or mixture is not available. Causes

burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause

irreversible damage to eyes.

Component Information

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Product name: Polymer Li-ion Battery Pack

Revision date: 6-Nov-2018

Printing date: 6-Nov-2018

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite	> 10000 mg/kg (Rat)		
7782-42-5			
Aluminum	> 15000 mg/kg buy/rst)		> 0.000 mg/l // h/mt\
7429-90-5	> 15900 mg/kg bw(rat)		> 0.888 mg/L/4 h(rat)
Copper	> 2500 mg/kg bw(rat)	> 2000 mg/kg bw(rat)	=1.03 mg/L/4 h(rat)
7440-50-8	/ 2300 mg/kg bw(rat)	2000 mg/kg bw(rat)	-1.03 mg/ L/4 m(rat)

(b) Information on toxicological characteristics

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or

wheezing. Itching. Rashes. Hives.

(C) Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible person, May cause sensitization by

skin contact. May cause sensitization by inhalation.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as

a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide	A3	Group 2B		X
(CoLiO2)				
12190-79-3				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity

No information available

STOT - single exposure

No information available

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based

on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT

RE).

Chronic Toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth

followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects.

May cause adverse liver effects.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central

Nervous System (CNS). Central Vascular System (CVS). Kidney. Liver. Lungs.

Aspiration Hazard No information available.

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 6-Nov-2018Product name: Polymer Li-ion Battery PackPrinting date: 6-Nov-2018

12. Ecological information

(a) Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity	to	Daphnia Magn
			Microorganisms		(Water Flea)
Copper	96h EC50: 0.031 - 0.054	96h LC50: 0.0068 -			48h EC50: = 0.03 mg/L
7440-50-8	mg/L	0.0156 mg/L (Pimephales			
	(Pseudokirchneriella	promelas) 96h LC50: =			
	subcapitata) 72h EC50:	0.112 mg/L (Poecilia			
	0.0426 - 0.0535 mg/L	reticulata) 96h LC50: =			
	(Pseudokirchneriella	0.3 mg/L (Cyprinus			
	subcapitata)	carpio) 96h LC50: = 0.8			
		mg/L (Cyprinus carpio)			
		96h LC50: = 1.25 mg/L			
		(Lepomis macrochirus)			
		96h LC50: = 0.052 mg/L			
		(Oncorhynchus mykiss)			
		96h LC50: = 0.2 mg/L			
		(Pimephales promelas)			
		96h LC50: < 0.3 mg/L			
		(Pimephales promelas)			

(b) Persistence and Degradability

No information available.

(c) Bioaccumulative potential

No information available.

(d) Other adverse effects

No information available.

13. Disposal considerations

(a) Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations

California Hazardous Waste 141

Codes

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Toxic
Copper	Toxic

Safety Data Sheet According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN Revision date: 6-Nov-2018 Product name: Polymer Li-ion Battery Pack Printing date: 6-Nov-2018

7440-50-8	
Aluminum 7429-90-5	lgnitable powder

14. Transport information

Note:	The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as
	"Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"
UN number	
	3480&3481
DOT	NOT REGULATED
Proper Shipping Name Hazard Class	NON REGULATED
TDG_	N/A
· 	Not regulated
MEX	Not regulated
ICAO	Not regulated
IATA Braner Shinning Name	Not regulated NON REGULATED
Proper Shipping Name Hazard Class	
IMDG/IMO	N/A Net regulated
Hazard Class	Not regulated N/A
EmS-No.	F-A, S-I
RID	Not regulated
ADR	Not regulated
ADN	Not regulated
ADIN	Not regulated

15. Regulatory information

(a) Safety, health and environmental regulations specific for the product in question

CAS No. USA TSCA	USA	EU	Japan	Korea	China	Canada
	EINECS	ENCS	ECL	IECSC	DSL	
12190-79-3	Listed	Listed	Listed	Listed	Listed	Listed
7782-42-5	Listed	Listed	Not listed	Listed	Listed	Listed
21324-40-3	Not listed	Listed	Listed	Listed	Listed	Not listed

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN Revision date: 6-Nov-2018 Printing date: 6-Nov-2018

Product name: Polymer Li-ion Battery Pack

7429-90-5	Not listed	Listed	Listed	Listed	Listed	Not listed
7440-50-8	Listed	Not listed	Listed	Listed	Listed	Listed
9002-88-4	Listed	Listed	Listed	Listed	Listed	Listed
9003-07-0	Listed	Listed	Not listed	Listed	Listed	Listed
25038-54-4	Listed	Listed	Listed	Listed	Listed	Not listed

16. Other information, including date of preparation or last revision

(a) Preparation and revision information

Date of previous revision: Not applicable. Date of this revision: 6-Nov-2018

Revision summary: The first New SDS

(b) Abbreviations and acronyms

TSCA: Toxic Substances Control Act, The American chemical inventory.

DSL **Domestic Substances List**

European Inventory of Existing Commercial chemical Substances **EINECS:**

ENCS Japanese Existing and New Chemical Substances ECL: Existing Chemicals List, the Korean chemical inventory. IECSC: Inventory of existing chemical substances in China.

(c) Disclaimer

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard. The information in this SDS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This SDS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this SDS should make independent judgment for the applicability of this SDS under special conditions. In these special cases, we do not assume responsibility for the damage.

----- End of the SDS -----