Life Safety Support Products

For Immediate Identification







For Identification

Available in the most popular RACO® steel boxes and covers for general alarm and security applications. Allows an inspector or building owner to immediately identify alarm/fire or life safety systems.

- Accommodates local codes for easy identification of products containing cabling relative to life safety systems
- Prevents the need for painting or labeling on the job site
- For industrial, commercial or residential applications
- All products have UL Listed, durable red polyester powder finish
- Manufactured from .062 thick steel
- Approved for use in 2 hour fire rated walls

Large 66.7 Cu. In. Capacity Box gives you the RACO® advantage. This new design accommodates oversized alarm devices for use in industrial, commercial, or residential applications. **Catalog no. 911-15**.

4-11/16" sq. x 4" sq. adapter ring is raised 5/8" and accepts UFE safety appliances designed to mount to 4" sq. boxes.

Catalog no. 911-16.

4-11/16" sq. x 4" sq. adapter ring is raised 1-1/4" and accepts UFE safety appliances designed to mount to 4" sq. boxes.

Catalog no. 911-17.





Application

- RACO RETRO-RING® is used to position any depth, wall cavity
- RACO 205RAC is used to position life safety devices
- RACO 206RAC is used in old work installations where
- RACO NEW 911-19 RETRO-RING® is used to position rock covered, wall cavity - used to position life safet

Features

- Allows 4" square box to be quickly and easily mount
- Accommodates any depth, 4" square box
- Works with up to 1-1/2" deep, drywall applications
- Small foot print is easily covered by wall plate (any v 4-13/32" W x 4-3/4" H)
- · Steel old work wings allow for secure mounting of b
- Includes one wall template per carton for easy trace.
- Made from durable, .039" thick galvanized steel
- Can be used to mount low voltage devices without a
- Design allows for installation of steel low voltage pa
- One or two devices mount directly to RETRO-RING®

| RETRU-RING® FUR PUWER/DATA DEVICE(S), 4" | | | | |
|--|---|--|--|--|
| CAT. NO. | DESCRIPTION | | | |
| 205RAC | RETRO-RING for Life Safety Appliance Sup | | | |
| 206RAC | RETRO-RING for One or Two Device Applic | | | |
| 706RAC | Box Partition for RETRO-RING & 1-1/2" Dee | | | |
| 707RAC | Box Partition for RETRO-RING & 2-1/8" Dee | | | |
| 911-19 | RETRO-RING for Life Safety Appliance Sup | | | |

^{*} can be used without a box when in compliance with local building codes.

NG® CONSTRUCTION





4" square steel junction box in a sheet rock covered,

e one or two devices are required - with or without a box* on any depth, 4" square steel junction box in a sheet y devices - painted red for immediate identification

ed in old work application

vall plate or appliance greater than

ox and devices to wall

-&-cut-out

box*

rtition for power/data applications (206RAC only) (206RAC only)

| SQUARE BUX MUUNTING | | | | | | |
|---------------------|-----------|----------------|--|--|--|--|
| | STD. PKG. | UPC-A Barcoded | | | | |
| port | 20 | 50050169002051 | | | | |
| ations | 20 | 50050169002068 | | | | |
| p 4" Sq. Bx. | 25 | 50050169007063 | | | | |
| p 4" Sq. Bx. | 25 | 50050169007070 | | | | |
| port, Red | 20 | 50050169504357 | | | | |







Unique Design

THE INSIDER® allows the installer to run fire alarm cable through the knockout to the desired length before snapping the connector into the knockout. THE INSIDER® is a perfect grommet to protect fire alarm cable entering any 1/2" box knockout.

- Snap-in locking tab design for 1/2" Knockouts
- One piece nonmetallic construction
- Easy removal
- THE INSIDER® can be used in old or new work applications

Also For Power...

Use THE INSIDER® in dry locations to connect one or two runs of Nonmetallic Sheathed Cable (NMSC) to a box.

THE INSIDER® and NMSC can be used with Steel Boxes, Panel Boxes or Plastic Boxes with knockouts.

For use with Nonmetallic Sheathed Cable

| SINGLE | |
|--------------|--------------|
| 14-2 w/grnd. | 14-3 w/grnd. |
| 12-2 w/grnd. | 12-3 w/grnd. |
| 10-2 w/grnd. | 10-3 w/grnd. |

TWO CABLE COMBINATIONS (2)14-2's w/grnd. (1) 14-2 w/grnd. & (1) 12-2 w/grnd. (1) 14-2 w/grnd. & (1) 10-2 w/grnd.

SPECIFICATIONS

 Cat. No.: 4714
 Unit Carton Qty.: 100

 Trade Size: 1/2"
 Ship Carton Qty.: 100

 Color: Black
 Wt. Per 100 Pcs.: 0.861

Material: Thermoplastic

Unit Carton Dimensions: 6-1/4" x 4-1/2" x 4-1/4" Ship Carton Dimensions: 21-3/8" x 9-3/4" x 7-1/2" I Two of Five Bar Code Unit Carton.: 30050169047140 I Two of Five Bar Code Ship Carton.: 50050169047144



| Unpainted Base | Cu. In. | Knockouts Sides Cond. Bottom Cond. | | Std Pkg. |
|-------------------|------------|---|----------------------------------|-------------|
| 255 | 45.0 | (10) 1/2"- 3/4" Concentric | (4) 1/2"- 3/4" Concentric | 10 |
| 256 | 45.0 | (12) 1/2"-3/4" Concentric | (4) 1/2"-3/4" Concentric | 25 |
| 260 | 66.7 | (3) 1/2"- 3/4" TKO (2) 1" - 1-1/4" TKO (2) 1" - 2" Conc. KO | (2) 3/4"- 1" TKO (2) 1/2" TKO | 10 |
| | 66.7 | (3) 1/2"- 3/4" TKO (2) 1" - 1-1/4" TKO (2) 1" - 2" Conc. KO | (2) 3/4"- 1" TKO (2) 1/2" TKO | 10 |
| 855 | 8.3 | _ | _ | 25 |
| 859 | 16.0 | _ | _ | 12 |
| 205RAC | _ | _ | _ | 20 |
| Unpainted Base | Cu. In. | Knoc Sides Cond. | Std Pkg. | |
| 232 | 30.3 | (8) 1/2" & (4) TKO | (3) 1/2" & (2) TKO | 25 |
| 237 | 30.3 | (6) 1/2" & (3) TKO | (3) 1/2" & (2) TKO | 25 |
| 189 | 21.0 | (8) 1/2" & (4) TKO | (2) 1/2" & (2) TKO | 50 |
| 203 | 22.5 | (8) 1/2" & (4) 3/4" | _ | 50 |
| 752 | _ | _ | _ | 50 |
| 257 | 42.0 | (12) TKO | (1) 1/2" & (3) TKO | 25 |
| 832 | _ | _ | _ | 50 |

LISTINGS & PATENT INFORMATION

RACO® RACO® RETRO-RING® THE INSIDER®



LISTED NM Cable Connector 204G

U.S. PATENT 7,300,025 B2 U.S. PATENT 7,211,744

