

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

BEHR MARQUEE™ INTERIOR EGGSHELL ULTRA PURE WHITE No. 2450 Product Name:

Product Code: 2450 SDS Manufacturer Number: 2450

Manufacturer Name: **BEHR Process Corporation** 1801 E. St. Andrew Place Santa Ana, CA 92705 General Phone Number: (714) 545-7101 (714) 241-1002

General Fax Number: Customer Service Phone

Number:

(800) 854-0133 ext. 2

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300 In Canada, call CANUTEC: (613) 996-6666 (call collect) Canutec:

SDS Creation Date: February 05, 2014 SDS Revision Date: October 20, 2017

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Pictograms:

Signal Word:

GHS Class: Eye Irritant, Category 2B.

Skin Irritant, Category 2. Acute Oral Toxicity, Category 4

Hazard Statements: Causes eye irritation.

Causes skin irritation. Harmful if swallowed.

Wear protective clothing, gloves, eye, and face protection. Do not eat, drink or smoke when using this product. Precautionary Statements:

Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling.

Collect spillage and avoid release to the environment.

Dispose of unused contents, container, and other contaminated wastes in accordance with local, state, federal, and provincial regulations.

If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists.

If on skin: Wash with plenty of soap and water.
If swallowed: Rinse mouth and get medical attention if you feel unwell.

Emergency Overview: Irritant.

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye: Causes eye irritation. Skin: Causes skin irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation.

Signs/Symptoms: Overexposure may cause headaches and dizziness. Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing

Conditions:

None generally recognized.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CA S#	Ingredient Percent	EC Num.
Titanium dioxide	13463-67-7	10 - 30 by weight	236-675-5
Nepheline Syenite	37244-96-5	5 - 10 by weight	
Anhydrous aluminum silicate	66402-68-4	5 - 10 by weight	266-340-9

Amorphous silica 7631-86-9 1 - 5 by weight 231-545-4

21645-51-2 244-492-7 Aluminum hydroxide 1 - 5 by weight

Ethylene glycol 107-21-1 1 - 5 by weight 203-473-3

Note: The remaining components of this product are non-hazardous or are in a small enough quantity as to

not meet regulatory thresholds for disclosure.

SECTION 4: FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of

the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.

Skin Contact: Immediately wash skin with soap and plenty of water.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

personnel. Seek immediate medical attention

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give

anything by mouth to an unconscious person

1

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: None.

Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable.

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires

involving this material.

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear. Protective Equipment:

NFPA Ratings:

NFPA Health: NFPA Flammability: 1 NFPA Reactivity: 0

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use

proper personal protective equipment as listed in Section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Methods for containment: Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by

covering, diking or other means. Provide ventilation.

Methods for cleanup: Clean up spills immediately observing precautions in the protective equipment section. Place into a

suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water

to remove trace residue.

SECTION 7: HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Storage: Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general **Engineering Controls:**

ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance

of the personal protective equipment.

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166. Eye/Face Protection:

Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be Skin Protection Description:

used to prevent contact with eyes, skin or clothing.

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be Respiratory Protection:

permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety

PPE Pictograms:



EXPOSURE GUIDELINES

Titanium dioxide:

Guideline ACGIH: TLV-TWA: 10 mg/m3

Ethylene glycol:

Guideline ACGIH: TLV-STEL: C 100 mg/m3 (H)

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State: Liquid. Color: White Odor: Slight.

Odor Threshold: Not applicable. **Boiling Point:** >99°F (>37°C) Melting Point: Not applicable. 11.68 Lbs/gal Density: Solubility: Not applicable. Vapor Density: Not applicable. Vapor Pressure: Not applicable. **Evaporation Rate:** Not applicable. 7 - 10 pH:

Viscosity: 50-140

Coefficient of Water/Oil

Distribution

Not applicable.

Flammability: Not applicable.

Flash Point: None.

Material VOC: 23 gm/L(Includes Water) Coating VOC::48 gm/L(Excludes Water) VOC Content:

SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Hazardous Polymerization: Not reported.

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

SECTION 11: TOXICOLOGICAL INFORMATION

Amorphous silica:

Eye: Administration into the eye - Rabbit Standard Draize test: 25 mg/24H [Mild] (RTECS)

Ethylene glycol:

Administration into the eye - Rat Standard Draize test: 0.012 %/3D [Not reported.] Eve: Administration into the eye - Rabbit Standard Draize test: 500 mg/24H [Mild]

Administration into the eye - Rabbit Standard Draize test: 100 mg/1H [Mild] Administration into the eye - Rabbit Standard Draize test: 0.012 ppm/3D [Not reported.]

Administration into the eye - Rabbit Standard Draize test: 1440 mg/6H [Moderate] (RTECS)

 $Administration\ onto\ the\ skin\ -\ Rabbit\ LD50\ -\ Lethal\ dose,\ 50\ percent\ kill:\ 9530\ uL/kg\ [Details\ of\ toxic\ effects\ not\ reported\ other\ than\ lethal\ dose\ value]\ (RTECS)$ Skin:

Oral - Rat LD50 - Lethal dose, 50 percent kill: 4700 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS) Ingestion:

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not restricted as a hazardous material.

DOT UN Number: Not restricted as a hazardous material.

IATA Shipping Name: Not restricted as a dangerous good.

IATA UN Number: Not restricted as a dangerous good.

Canadian Shipping Name: Not restricted as a dangerous good.

Canadian UN Number: Not restricted as a dangerous good.

IMDG UN Number: Not restricted as a dangerous good.

IMDG Shipping Name: Not restricted as a dangerous good.

ADR UN Number: Not restricted as a dangerous good.

ADR Shipping Name: Not restricted as a dangerous good.

SECTION 15: REGULATORY INFORMATION

<u>Titanium dioxide</u>:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 236-675-5

Nepheline Syenite:

Canada DSL: Listed

<u>Anhydrous aluminum silicate</u>:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 266-340-9

Amorphous silica:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 231-545-4

Aluminum hydroxide:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 244-492-7

Ethylene glycol:

TSCA Inventory Status: Listed

Section 313: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

Canada DSL: Listed
EC Number: 203-473-3

SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 1
HMIS Fire Hazard: 1
HMIS Reactivity: 0
HMIS Personal Protection: X

SDS Creation Date: February 05, 2014

SDS Revision Date: October 20, 2017
SDS Author: Actio Corporation

Copyright© 1996-2018 Enviance. All Rights Reserved.