





K4 & K5 Series Temporary High Bays

Bergen's construction grade Temporary High Bays are designed for the job site but offer portability that make it easy to use for do-it-yourself and FarmAg applications. The K4 is available in 100 watts with a **35ft 18/3 SJTW daisy chain power cord**; and the K5's are available in 30W, 60W, 100W, and 150W with 10ft 18/3 SJTW daisy chain power cables; all include stainless steel reinforced cages, heavy-duty carabiner hook, and 1ft power cables. Bergen Temporary High Bays are an energy saving and long life solution to replace traditional HID & CFL work lights.




**AVAILABLE IN 30W,
60W, 100W & 150W**

- Heavy duty, durable design
- Easy portability, light weight
- All-Weather Applications, IP65
- UL & OSHA Compliant
- 5 Year Warranty



K4 & K5 Series Temporary High Bays



Additional LEDs on the bottom



Easy to hang and remove - Stainless Steel Carabiner Hook

35'
DAISY-CHAIN
POWER CABLE



MODEL	NEW - K4100	K530	K560	K5100	K5150
Watts	100	30	60	100	150
Voltage	100-277V	100-277V	100-277V	100-277V	100-277V
Lumens	12,000	4,050	7,800	13,000	19,500
Color Rendering Index (CRI)	80	80	80	80	80
Surge Protection	Up to 12,000V	Up to 6,000V	Up to 6,000V	Up to 12,000V	Up to 12,000V
Light Beam Angle	360°	360°	360°	360°	360°
Color Rating	5000K	5000K	5000K	5000K	5000K
Daisy Chain - Length	✓ - 35FT.	✓ - 10FT.	✓ - 10FT.	✓ - 10FT.	✓ - 10FT.
Power Cord	1FT.	1FT.	1FT.	1FT.	1FT.
Drive and Cage Material	Plastic & Steel	Plastic & Steel	Aluminum Die Cast & Steel	Aluminum Die Cast & Steel	Aluminum Die Cast & Steel
IP Rating	IP65	IP65	IP65	IP65	IP65
Indoor and Outdoor	✓	✓	✓	✓	✓
UL / OSHA Compliant	✓	✓	✓	✓	✓
Operating Temperature	-4F° to 122F° (-20°C to 50°C)	-4F° to 122F° (-20°C to 50°C)	-4F° to 122F° (-20°C to 50°C)	-4F° to 122F° (-20°C to 50°C)	-4F° to 122F° (-20°C to 50°C)
Heavy Duty Carabiner Hook	✓	✓	✓	✓	✓
Warranty	5 year	5 year	5 year	5 year	5 year
Rated Hours	50,000	50,000	50,000	50,000	50,000
Dimensions (out of box)	11.4" x 6"	9.6" x 4.1"	12" x 6"	12" x 6"	12.6" x 6.5"