

DryPlus® Masonry Waterproofer

- Smooth, Decorative Interior/Exterior Flat Finish
- 10 Year Guarantee*
- Withstands 12 PSI of Water Pressure
- Mildew Resistant Film
- 100% Styrene Acrylic
- Sprayable! Saves Application Time

No. 875 White
No. 876 Basement Gray

2 Coats Required for Optimal Durability

Spread Rate:
Rough 75-100 Sq. Ft.
Smooth 100-125 Sq. Ft.

Dry Time:
1 Hr. Dry to Touch
4 Hr. Recoat

Soap & Water Clean-Up

READY TO USE OR ADD TINTING COLORANTS

WHERE TO USE

Walls subject to hydrostatic pressure. Ideal for above or below grade Basement Walls, Retaining Walls, Garage Walls, Masonry Walls, Cinder Blocks, Stucco, Brick, Foundations and Landscape Walls. Apply to dry or slightly damp surfaces. ***Not for use on floors or walls with active water leaks.***

PREPARATION

(Proper surface preparation is required.) New or Unpainted Surfaces: New concrete must cure for a minimum of 30 days. Test for loose, flaking concrete by pressing a piece of masking or cellophane tape at various places, then pull it off with an abrupt action. If the tape does not pull the concrete from the surface, it can be painted. If the existing concrete is removed, the loose concrete should be removed down to a sound substrate. ***For below grade application:*** All holes or cracks must be properly patched with a fast setting hydraulic cement. ***For above grade application:*** Remove mildew stains with a mildew stain removing product. All surfaces must be clean and free of dirt, dust, efflorescence and oil. Follow all label instructions. **Previously Painted Surfaces:** BEHR PREMIUM DryPlus® No. 875 provides best results when applied to bare or untreated surfaces. PREVIOUSLY PAINTED SURFACES IN GOOD, REPAINTABLE CONDITION MAY BE PAINTED WITH BEHR PREMIUM DryPlus NO. 875, HOWEVER, BEHR WILL NOT GUARANTEE THE RESULTS. Test for loose, flaking paint by pressing a piece of masking or cellophane tape at various places, then pull it off with an abrupt action. If the tape does not pull the paint from the surface, it can be painted. If the existing paint is removed, the loose paint should be removed down to a sound substrate by wire brushing or sanding. For Interior or Exterior application; remove deteriorated coating prior to application. Follow all preparation instructions under "New or Unpainted Surfaces" above.

APPLICATION

Stir well before use. Do not thin product. Use with adequate ventilation. Use product when air and surface temperature are 50-90˚ F (10-32˚ C). Apply to dry or slightly damp masonry walls. Wipe off any visible moisture with a dry cloth before painting. Apply using a high quality 1/2"-3/4" nap roller, 4" nylon/polyester brush or an airless sprayer capable of delivering 0.5 GPM or greater using a .023"-.025" spray tip. ***Two coats minimum are required:*** ***First Coat:*** Using a brush or roller, work the waterproofer onto the surface until all pores or voids are covered ***Second Coat:*** Using a brush or roller, cover the entire surface. Properly fill any voids left after the first coat. Additional spot application may be needed depending on the porosity of the surface. **Important: If leaking is still present after two coats, it indicates that voids or pinholes are still open. Re-apply product to these areas. DO NOT thin product or apply at a greater spread rate.**

DRY TIME

Low temperatures or high humidity conditions will affect drying time. Full cure should be reached in 7-14 days.

DISPOSAL

Properly dispose of all soiled rags and **protect unused product from freezing.** For disposal of empty containers and unused product contact your household refuse collection service.

WARNING If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

***LIMITED WARRANTY**

Behr Process LLC warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for 10 years from the date of purchase. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED, VERTICAL SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified on the label during the warranty period, Behr Process LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey:** The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. To obtain warranty service, call 1-800-854-0133. Behr Process LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2024 Behr Process LLC
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. <100 g/L • REV. 2/24

⚠**WARNING:** This product can expose you to chemicals including ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

WARNING! IRRITANT CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CONTAIN: DIURON, ETHYLHEXYL BENZOATE, GROUND CALCIUM CARBONATE, CRYSTALLINE SILICA, AND TITANIUM DIOXIDE. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.