



Quality Products Since 1932 • DRYLOK® • ZAR® • UGL®

Spray Specifications D-88

DRYLOK® Original Masonry Waterproofer

1 to 15 gallons

Equipment: Graco® Fast Finish Pressurized Hopper Gun (Part # 25D496) compressor needed, Fast Finish System (Part # 25D492) includes both Hopper gun and compressor

16+ gallons

Electric Equipment: Graco® TexSpray RTX 5000PI (Part # 17H575), RTX 5000PX (17H579) or RTX 5500PX (17H581)

Mixing Instructions: Agitate only

Tips and Nozzles: 6mm nozzle with #6 WideTex Spray tip

Fluid Pressure Setting: Mid point

Gun Air Setting: Full

Recommended Hose Diameter: 1¼" for hose run and 1" x 10' Whip to gun

Max Hose Length: 50 feet

Spraying Directions: Spray approximately 24" to 36" from surface. Spray in two crossing directions (north/south then east/west) while overlapping spray pattern by 50%. Apply to desired film thickness specification. Back roll for best coverage.

Air/Pneumatic Equipment: Graco® GTX 2000EX

Mixing Instructions: Agitate only

Tips and Nozzles: 6mm nozzle with #6 WideTex Spray tip (WideTex Kit #24S143 required)

Fluid Pressure Setting: Mid point

Gun Air Setting: Full

Recommended Hose Diameter: 1¼" for hose run and 1" x 10' Whip to gun

Max Hose Length: 50 feet

Spraying Directions: Spray approximately 24" to 36" from surface. Spray in two crossing directions (north/south then east/west) while overlapping spray pattern by 50%. Apply to desired film thickness specification. Back roll for best coverage.

Revised April 3, 2019

570-344-1202 • 1-800-845-5227 • Fax 570-969-7634 • www.UGL.com

Corporate Office: 1396 Jefferson Avenue, Dunmore, PA 18509 • Mail to: P.O. Box 70, Scranton, PA 18501-0070
Plant Locations: Jacksonville, IL • Jackson, MS