halolighting.com

February 18, 2020

HALO® Recessed RA 4" & 6" Direct Mount Adjustable Gimbal

HALO is pleased to announce the 4-inch and 6-inch RA Direct Mount Adjustable Gimbal. The smooth lens provides visual comfort and the WFL distribution patterns are ideal for accent illumination. Requiring only 3-1½" of plenum depth, the RA-DM can be installed virtually anywhere and reduces installation time and expense. This solution is excellent for Mixed-Use dwellings as well as traditional residential.

The low-profile driver / junction box can be installed through the ceiling cutout and positioned remotely providing clearance from potential obstructions making it ideal for both new construction and renovation work. The RA-DM is also compatible with the HL4RSMF / HL6RSMF new construction mounting frames.

Field selectable color temperature provides SKU consolidation opportunities at distribution and flexibility during installation. Applications include living and dining areas, bedrooms, kitchens, home offices and mixed-use spaces – anywhere where task or accent lighting is desired.

Features at a Glance

- 4" & 6" semi-regressed gimbal, rotates 360°, tilts up to 35°
- 2700K, 3000K, 3500K, 4000K and 5000K field selectable CCT
- No housing required, reduces installation time and expense
- Up to 750 lumens delivered
- 90 CRI (min), R9 > 50 and color accuracy within 4 SDCM
- Remote driver / junction box, 120V, 5% LE/TE phase cut dimming
- Held securely in 0.5" 1.25" thick ceilings with (2) retention springs
- Airtight and suitable for direct contact with insulation
- Wet location listed, suitable for shower applications
- Requires only 3-1/2" of plenum depth, installs virtually anywhere

- Smooth lens provides visual comfort, can be used to meet Well Building UGR
- Airtight per ASTM-E283-04
- Meets FCC Title 47 CFR Part 15, Subpart B
- ENERGY STAR® qualified, refer to qualified product list for applicable models
- Meets state of California Title 24 high efficacy LED compliance under JA8
- cULus certified, suitable for direct contact with air permeable insulation
- Five-year limited warranty

Catalog Number	Material Number	Description	UPC	Case Quantity
RA4069S1EWHDMR	13342358	4" RA, 600lm, Field Select CCT, 90 CRI, direct mount, matte white	080083911325	4
RA6069S1EWHDMR	13342359	6" RA, 600lm, Field Select CCT, 90 CRI, direct mount, matte white	080083911349	4

Selling Tools

Specification sheets, installation instructions, dimming guide and IES files are available now, refer to the HALO Recessed website. The fixture fittings and accessories ship from stock, consult FLASH for pricing and availability. Take advantage of this exciting new product introduction and grow your HALO Recessed sales now.

See HALO in a whole new light!

Glenn Siegel Bryant Bilal
Marketing & Product Product & Marketing Manager

Management Director HALO Recessed

Joseph Dimperio

Product & Marketing Manager HALO Recessed



Cooper Lighting Solutions is a registered trademark.

All other trademarks are property of their respective owners.

Product availability, specifications, and compliances are subject to

