

CERTIFICATE OF COMPLIANCE

Certificate Number E61542
Report Reference E61542-19751211
Issue Date 2020-APRIL-3

Issued to: DURHAM CO
722 DURHAM RD
PO BOX 908
LEBANON MO 65536-0908

This certificate confirms that METER SOCKETS
representative samples of See Addendum Page for models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 414, Meter Sockets
Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE


Certificate Number E61542
Report Reference E61542-19751211
Issue Date 2020-APRIL-3

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models:

Cat. Nos. 1004341, 1005302, and 1005076.

Cat. No. U; followed by one or more of the following A, B, F, TT, G, I, J, M, T, D, or E; followed by one of the following base designations C42Y3Y, C42Y3Y (M Series), C52Y3Y, C52Y3Y (M Series with 250 MCM), C72Y3Y, C72Y3Y (M Series), H42Y3Y, H52Y3Y, H72Y3Y, H43YYY, H433YY, H434YY, H53YYY, H73YYY, H432YYA, H42YYY, H52YYY, or H72YYY; may be followed by an alpha-numeric characters in quotations "-"; and followed by A, B, C, L, K, M, N, P, Q, R, S, T, U, V, W, or Z. Cat. Nos. with "H" prefix can be replaced by "L" as alternate prefix for all assemblies except for those rated 320 A 3 phase. Cat. Nos. with "H" prefix can be replaced by "E" as alternate prefix for all 200 A assemblies. Note: Y = 0 through 9, Last "Y" is optional in base designation.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

