

6-INCH 14 HP 429 CC KINETIC CYCLONIC ELECTRIC START DRUM CHIPPER SHREDDER

ITEM NUMBER

OPC566E

13

UPC

827518006757

DESCRIPTION

The OPC566E is a 6-inch kinetic cyclonic chipper powered by an electric start, direct drive KOHLER® Command PRO® CH440 14 HP 429 cc engine with 22.7 ft/lb gross torque to demolish trees up to 6.25 inches in diameter. Equipped with double edge reversible 12-inch cutting blades that auto-adjust to pulverize trees and brush, dual tool-free swing-open chutes that quickly open for easy drum access, D.O.T. approved tires and a 48-inch extended axle for uneven ground and towing stability with front articulated ground wheels for easy equipment moving, a 2-inch hitch receiver and tow bar, and a rotational expulsion chute pickup truck height for bed loading.

SPECIFICATION

ENGINE KOHLER® Command PRO® CH440 14 HP 429 cc

GEARBOX 22.7 ft/lb (30.7 Nm) gross torque

REAR WHEELS & TIRES D.O.T. approved 4.80-8 Ø15" (Ø41.9 cm) OD x 4.25" (10.8 cm) on 9" (22.9 cm) rims

FRONT WHEELS & TIRES Off-road 4.10-4 Ø10" (Ø25.4 cm) OD on Ø5" (Ø12.7 cm) rims

WHEELBASE 48" (121.9 cm)

CHIPPING CAPACITY Ø6.25" (Ø15.9 cm)

CUTTERS 12" (30.5 cm) double edge reversible chipper blades

CHIPPER SHREDDER Auto-adjusting from Ø1/8" (Ø0.32 cm) up to Ø6.25" (Ø15.9 cm) trees and brush

EXPULSION CHUTE 59" (149.9 cm) truck bed height with 180° adjustable spout

COUPLER 2" (5.08 cm)

DIMENSIONS 102" (L) x 47" (W) x 59" (H)
259.1 cm (L) x 119.4 cm (W) x 149.9 cm (H)

WEIGHT 594 lb (269.4 kg)

SHIPPING DIMENSIONS 45" (L) x 31" (W) x 48" (H)
114.3 cm (L) x 78.7 cm (W) x 121.9 cm (H)

SHIPPING WEIGHT 726 lb (329.3 kg)

WARRANTY 3-year KOHLER® engine
1-year DK2 chassis



FEATURES

- Powered by a KOHLER® Command PRO® CH440 14 HP 429 cc engine **1**
- Dual-belt drive drum transmission with 12" (30.5 cm) double edge reversible cutting blades **2**
- Auto adjust cutters for trees and brush up to 6.25" (15.9 cm) in diameter
- 48" (121.9 cm) axle with D.O.T. approved 4.80-8 Ø15" (Ø41.9 cm) OD rear tires on Ø9" (Ø22.9 cm) rims and off-road 4.10-4 Ø10" (Ø25.4 cm) OD front tires on Ø5" (Ø12.7 cm) rims **3**
- Includes safety kit
- Electric start (battery included) **4**
- CE safety approved shutoff
- Dual tool free swing open chutes
- Tool-free 180° rotational spout on 59" (149.9 cm) truck bed height expulsion chute
- Extra-large feed chute with integrated equipment moving handles
- Includes 3-year KOHLER® engine and 1-year DK2 chassis warranty
- NOT HIGHWAY TOWABLE AND MAX SPEED 25MPH (40KM/H)**

