

SPECIFICATIONS*

| | |
|---|-----------------------------------|
| Engine Type | Air-Cooled, 2-Cycle |
| Displacement | 42 cc (2.56 cu. in.) |
| Spark Plug Gap | 0.025 in. (0.635 mm) |
| Spark Plug | Torch® CMR7H or equivalent plug |
| Lubrication | Bar and Chain Oil |
| Fuel/Oil Ratio | 40:1 |
| Fuel Tank Capacity | 9 oz. (270 mL) |
| Chain Oil Reservoir Capacity | 6.5 oz. (200 mL) |
| Approximate Unit Weight (without fuel or chain oil) | 11.75 - 12.75 lbs. (5.3 - 5.8 kg) |
| Guide Bar Length (TB4214C XP) | 14 in. (35.6 cm) |
| Guide Bar Length (TB4216C XP) | 16 in. (40.6 cm) |
| Guide Bar Length (TB4218C XP) | 18 in. (45.7 cm) |
| Saw Chain Pitch | 3/8 in. (9.5 mm) |
| Saw Chain Gauge | 0.050 in. (1.3 mm) |

* All specifications are based on the latest product information available at the time of printing. We reserve the right to make changes at any time without notice.

REPLACEMENT PARTS

Please contact the Customer Support Department to order replacement parts.

| Part # | Description |
|------------------|------------------------------|
| 713-05277 | Saw Chain (14 in. / 35.6 cm) |
| 713-05276 | Saw Chain (16 in. / 40.6 cm) |
| 713-05042 | Saw Chain (18 in. / 45.7 cm) |
| 795-01022A | Guide Bar (14 in. / 35.6 cm) |
| 795-01023A | Guide Bar (16 in. / 40.6 cm) |
| 795-01024A | Guide Bar (18 in. / 45.7 cm) |
| 753-08105 | Bar-Retaining Nuts |