SAFETY DATA SHEET

Issuing Date 10-Nov-2020

Revision Date 27-Jul-2020

Revision Number 1

NGHS / English

(U_L)

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Vulkem 116 Polyurethane Sealant Gray

Other means of identification

Product Code(s) 1595783_HD

Recommended use of the chemical and restrictions on use

Recommended Use Sealant - Architectural

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification DAP Products Inc.

Address 2400 Boston Street

Suite 200 Baltimore Maryland 21224 US

Telephone Phone:410-675-2100

Fax:410-779-2064

E-mail alisonebel@verizon.net

Emergency telephone number

Company Emergency Phone

Number

410-779-2253

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Vapors)	Category 3
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Category 1



Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

Appearance Black grey Physical state Paste Liquid Odor Unpleasant

GHS Label elements, including precautionary statements

Danger

Hazard statements

Toxic if inhaled

Causes serious eye irritation

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

May cause genetic defects

May cause cancer

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

In case of inadequate ventilation wear respiratory protection

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of water and soap

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER or doctor

Precautionary Statements - Storage

Store locked up



Page 2/13

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Causes mild skin irritation. Toxic to aquatic life with long lasting effects.

Unknown acute toxicity

99 % of the mixture consists of ingredient(s) of unknown toxicity

72 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

99 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

95.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

95.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

94.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Limestone	1317-65-3	20	-	-
Diisodecyl phthalate	26761-40-0	10	-	-
Titanium dioxide	13463-67-7	7	-	-
Naphtha (petroleum), heavy aromatic	64742-94-5	5	-	-
Pseudocumene	95-63-6	1.5	-	-
Aromatic solvent	64742-95-6	1.5	-	-
Quartz	14808-60-7	1	-	-
Polymethylene polyphenylene isocyanate	9016-87-9	1	-	-
Methylene bisphenyl isocyanate (MDI)	101-68-8	1	-	-
Aluminum oxide	1344-28-1	1		
1,3,5-Trimethylbenzene	108-67-8	1	-	-

4. FIRST AID MEASURES

Description of first aid measures

General advice

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.

Inhalation

May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical advice/attention. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Immediate medical attention is required. Do not breathe dust.



Page 3 / 13

Revision Date 27-Jul-2020

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation

or allergic reactions see a physician.

Ingestion May produce an allergic reaction. Do NOT induce vomiting. Clean mouth with water and

drink afterwards plenty of water. Never give anything by mouth to an unconscious person.

Get immediate medical advice/attention.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See section 8 for more

information. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or

other proper respiratory medical device. Do not breathe vapor or mist.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ or

wheezing. Itching. Rashes. Hives. Burning sensation. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Product is or contains a sensitizer. May cause sensitization by inhalation and skin contact.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Do not breathe vapor or mist. Avoid generation of dust. Do



Page 4/13

Revision Date 27-Jul-2020

not breathe dust.

Other Information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled

containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. Do not breathe vapor or mist. Handle product only in

closed system or provide appropriate exhaust ventilation.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Limestone	-	TWA: 15 mg/m ³	TWA: 5 mg/m³ respirable dust
1317-65-3		TWA: 5 mg/m ³	TWA: 10 mg/m³ total dust
		(vacated) TWA: 15 mg/m ³	
		(vacated) TWA: 5 mg/m ³	
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m ³
13463-67-7		(vacated) TWA: 10 mg/m³ total	
		dust	
Pseudocumene	-	-	TWA: 25 ppm
95-63-6			TWA: 125 mg/m ³
Quartz	TWA: 0.025 mg/m³ respirable	TWA: 0.1 mg/m³ (vacated)	IDLH: 50 mg/m³ respirable dust
14808-60-7	fraction		TWA: 0.05 mg/m³ respirable
			dust
Methylene bisphenyl isocyanate	TWA: 0.005 ppm	Ceiling: 0.02 ppm	IDLH: 75 mg/m ³
(MDI)		Ceiling: 0.2 mg/m ³	Ceiling: 0.020 ppm 10 min
101-68-8			Ceiling: 0.2 mg/m ³ 10 min
			TWA: 0.005 ppm
			TWA: 0.05 mg/m ³
Aluminum oxide	TWA: 1 mg/m³ respirable	TWA: 15 mg/m³ total dust	
1344-28-1	particulate matter	TWA: 5 mg/m³ respirable	



1,3,5-Trimethylbenzer 108-67-8	ne	-			fraction WA: 10 mg/r dust I) TWA: 5 m rable fractio	ıg/m³		25 ppm 25 mg/m³
Chemical name	Albert	a	British C	olumbia	Ontar	io TWAEV		Quebec
Limestone 1317-65-3	TWA: 10 r	ng/m³	TWA: 3	0 mg/m³ 3 mg/m³ 0 mg/m³			TW	A: 10 mg/m ³
Diisodecyl phthalate 26761-40-0					TWA	: 5 mg/m ³		
Titanium dioxide 13463-67-7	TWA: 10 r	ng/m³		0 mg/m³ 3 mg/m³	TWA:	10 mg/m ³	TW	A: 10 mg/m ³
Quartz 14808-60-7	TWA: 0.025	mg/m³	TWA: 0.0	25 mg/m ³	TWA:	0.10 mg/m ²	TW.	A: 0.1 mg/m ³
Polymethylene polyphenylene isocyanate 9016-87-9	TWA: 0.00 TWA: 0.07							
Methylene bisphenyl isocyanate (MDI) 101-68-8	TWA: 0.00 TWA: 0.05			005 ppm 0.01 ppm		0.005 ppm 0.02 ppm		A: 0.005 ppm : 0.051 mg/m ³
Aluminum oxide 1344-28-1	TWA: 10 r	ng/m³	TWA: 1.	0 mg/m³	TWA	: 1 mg/m³	TW	A: 10 mg/m ³

Other Exposure Guidelines Vacated

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves.

Skin and body protectionWear suitable protective clothing.

exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and immediately after handling the product. Do not breathe vapor or mist. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is

recommended. Take off contaminated clothing and wash before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES



Page 6/13

Information on basic physical and chemical properties

Paste; Liquid **Physical state Appearance** Black grey Odor Unpleasant

Color No information available **Odor Threshold** No data available

Property **Values** Remarks Method

<u>UNKNOWN</u> pН

No data available Melting / freezing point None known No data available Boiling point / boiling range None known

99 C / 210 F **Flash Point**

Evaporation Rate No data available None known Flammability (solid, gas) No data available None known None known

Flammability Limit in Air

Upper flammability limit No data available Lower flammability limit No data available

Vapor pressure No data available None known Vapor density No data available None known

Relative density 1.16

Water Solubility No data available

Solubility(ies) No data available None known

Partition coefficient: n-octanol/waterN/A

Autoignition temperature No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known Dynamic viscosity No data available None known

Other Information

No information available **Explosive properties** Oxidizing properties No information available **Softening Point** No information available No information available **Molecular Weight** No information available **VOC Content (%) Liquid Density** No information available **Bulk Density** No information available **Particle Size** No information available No information available Particle Size Distribution

10. STABILITY AND REACTIVITY

No information available. Reactivity

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur. Hazardous polymerization may occur.

Conditions to avoid Excessive heat.

Incompatible materials None known based on information supplied.

Hazardous Decomposition Products Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Hydrogen

cyanide. Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION



Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause sensitization in

susceptible persons. (based on components). May cause irritation of respiratory tract. Toxic

by inhalation.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitization by

skin contact. (based on components). Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause irritation. Prolonged contact may

cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. May cause additional affects

as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting

and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling

of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the

eyes. Difficulty in breathing.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 33,167.80 mg/kg
ATEmix (inhalation-gas) 426.40 ppm
ATEmix (inhalation-dust/mist) 1.47 mg/L
ATEmix (inhalation-vapor) 2.02 mg/L

Unknown acute toxicity

99 % of the mixture consists of ingredient(s) of unknown toxicity

72 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

99 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

95.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

95.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

94.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diisodecyl phthalate	= 64 g/kg (Rat)	> 3160 mg/kg (Rabbit)	> 12.54 mg/L (Rat) 4 h
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
Naphtha (petroleum), heavy	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m³ (Rat) 4 h
aromatic			
Pseudocumene	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Aromatic solvent	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Polymethylene polyphenylene	= 49 g/kg (Rat)	> 9.4 g/kg (Rabbit)	= 490 mg/m ³ (Rat) 4 h
isocyanate			
Methylene bisphenyl isocyanate	= 31600 mg/kg (Rat)	-	= 369 mg/m ³ (Rat) 4 h
(MDI)			
Aluminum oxide	> 5000 mg/kg (Rat)	-	-
1,3,5-Trimethylbenzene	<u>-</u>	-	= 24 g/m³ (Rat) 4 h



Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause sensitization by inhalation. May cause sensitization by skin contact.

Germ cell mutagenicity Contains a known or suspected mutagen. Classification based on data available for

ingredients. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	Х
Quartz 14808-60-7	A2	Group 1	Known	Х
Polymethylene polyphenylene isocyanate 9016-87-9	-	Group 3	-	-
Methylene bisphenyl isocyanate (MDI) 101-68-8	-	Group 3	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Diisodecyl phthalate	96h EC50: > 0.8 mg/L	96h LC50: > 0.55 mg/L	No data available	48h EC50: > 0.02 mg/L



	(Pseudokirchneriella subcapitata) 72h EC50: > 500 mg/L (Desmodesmus subspicatus)	(Lepomis macrochirus) 96h LC50: > 1 mg/L (Pimephales promelas)		(Daphnia magna)
Naphtha (petroleum), heavy aromatic	No data available	96h LC50: = 1740 mg/L (Lepomis macrochirus) 96h LC50: = 19 mg/L (Pimephales promelas) 96h LC50: = 2.34 mg/L (Oncorhynchus mykiss) 96h LC50: = 41 mg/L (Pimephales promelas) 96h LC50: = 45 mg/L (Pimephales promelas)	No data available	48h EC50: = 0.95 mg/L (Daphnia magna)
Pseudocumene	No data available	96h LC50: 7.19 - 8.28 mg/L (Pimephales promelas)	No data available	48h EC50: = 6.14 mg/L (Daphnia magna)
Aromatic solvent	No data available	96h LC50: = 9.22 mg/L (Oncorhynchus mykiss)	No data available	48h EC50: = 6.14 mg/L (Daphnia magna)
1,3,5-Trimethylbenzene	No data available	96h LC50: = 3.48 mg/L (Pimephales promelas)	No data available	No data available

Persistence and Degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Naphtha (petroleum), heavy aromatic	6.1
Pseudocumene	3.63

MobilityNo information available.Other adverse effectsNo information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Pseudocumene 95-63-6	Toxic

14. TRANSPORT INFORMATION	



DOTNOT REGULATEDProper Shipping NameNON-REGULATED

Hazard Class N/A

TDG Not applicable

MEX Not applicable

ICAO Not applicable

IATA Not applicable
Proper Shipping Name NON REGULATED

Proper Shipping Name NON F Hazard Class N/A

IMDG/IMO Not applicable

Hazard Class N/A

RID Not applicable

ADR Not applicable

ADN Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.

DSL/NDSL Contact supplier for inventory compliance status.

EINECS/ELINCS Contact supplier for inventory compliance status.

ENCS Contact supplier for inventory compliance status.

KECL Contact supplier for inventory compliance status.

PICCS Contact supplier for inventory compliance status.

Leaend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372



Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Pseudocumene - 95-63-6	95-63-6	1.5	1.0
Polymethylene polyphenylene isocyanate - 9016-87-9	9016-87-9	1	1.0
Methylene bisphenyl isocyanate (MDI) - 101-68-8	101-68-8	1	1.0
Aluminum oxide - 1344-28-1	1344-28-1	1	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Diisodecyl phthalate 26761-40-0		X		

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Methylene bisphenyl isocyanate (MDI)	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
101-68-8			

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65		
Diisodecyl phthalate - 26761-40-0	Developmental		
Titanium dioxide - 13463-67-7	Carcinogen		
Quartz - 14808-60-7	carcinogen, 10/1/1988 (airborne particles of respirable size)		

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Limestone 1317-65-3	Х	X	Х		
Diisodecyl phthalate 26761-40-0			Х		
Titanium dioxide 13463-67-7	Х	Х	Х		
Pseudocumene 95-63-6	Х	Х	Х	Х	Х
Quartz 14808-60-7	Х	Х	Х		Х
Polymethylene	X			X	



polyphenylene isocyanate 9016-87-9					
Methylene bisphenyl isocyanate (MDI) 101-68-8	Х	Х	Х	X	Х
Aluminum oxide 1344-28-1	Χ	Х	X	Х	
1,3,5-Trimethylbenzene 108-67-8		Х			

16. OTHER INFORMATION

NFPA Health hazards 3 Flammability 1 Instability 0 Physical and Chemical

Properties HMIS Health hazards 2 * Flammability 1 Physical hazards 0 Personal Protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date 10-Nov-2020

Revision Date 27-Jul-2020

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

