

KILZ® ODORLESS® INTERIOR OIL-BASE PRIMER AEROSOL



- Oil based primer/sealer/stainblocker in convenient aerosol spray
- Interior use
- Ideal for spot priming in areas sensitive to solvent odors
- Fast-dissipating odor technology for no lingering odors
- Blocks heavy stains including tannin bleed
- Seals persistent smoke, pet and food odors
- Lower solvent odor than typical oil based primers
- Ideal for priming drywall, brick, masonry, metal, plaster, siding and wood
- Fast drying - recoat in 1 hour



Mineral Spirits
Clean-Up



20 - 25 Sq. Ft. (1.9 - 2.3 m²)
per container*



To Touch: 15 - 30 Minutes**
To Recoat / Topcoat: 1 Hour**



Protect from
Freezing

WHERE TO USE

KILZ ODORLESS® Oil-base is a powerful interior stain blocker with no lingering odor. Ideal for use in offices, schools, dining areas, apartments and other areas sensitive to strong solvent odors. Use KILZ ODORLESS to block stains including water, tannin and smoke from tobacco and fire. Not recommended for floors.

SURFACE PREPARATION (The following steps are recommended for product performance)

- The surface must be clean, free of dust, grease, wax, peeling paint, mold, mildew, wallpaper paste. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.
- Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.

WARNING If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

- Glossy Surfaces: For maximum adhesion, scuff sand the surface thoroughly before priming.

APPLICATION

- Eye protection is recommended.
- For best results, use at room temperature. Cover adjacent areas to protect from overspray.
- Shake can vigorously for 1 minute after mixing ball begins to rattle and often during use. Hold can upright, moving from side-to-side while spraying lightly and evenly about 12" from area being painted. Two to three thin coats produce best results.
- Topcoat with latex or oil-based paint after 60 minutes. NOTE: On some surfaces, spot priming may cause a non-uniform appearance in the final coat. To avoid this, prime the entire surface.

CLEAN-UP & DISPOSAL

- Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released. If spray nozzle becomes clogged, remove and clean.
- Do not stick pins or wire into can opening.
- Replace nozzle with valve opening pointed away from you. Clean fresh overspray with mineral spirits or acetone. Remove dried paint with paint remover, but test small area first to ensure paint remover does not damage substrate.
- Please consider donating any unused product. For recycling or disposal information contact your local household refuse collection service.

VENTILATION REQUIRED: To avoid inhalation and combustion hazards (see below), **DO NOT** use this product unless you can achieve cross-ventilation by opening windows and doors during application and drying. **CONTAINS PETROLEUM DISTILLATES AND ACETONE. VAPOR HARMFUL.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC-23C or equivalent) or leave the area. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **VAPORS MAY IGNITE EXPLOSIVELY.** Do not spray near sparks, heat or open flame. Do not smoke. Vapors are heavier than air, and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. **WARNING-CONTENTS UNDER PRESSURE:** Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Prolonged exposure to sun may cause bursting. **FIRST AID:** If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY



WARNING

Cancer and Reproductive Harm
www.P65Warnings.ca.gov

LIMITED WARRANTY: For warranty service, call: 1-866-774-6371, or email: techservice@masterchem.com. Masterchem Industries LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

* Depending on the surface texture, porosity and application method.

**At 77°F (25°C), 50% RH. Longer dry time may be required in cooler temperatures and in higher humidity.



Max VOC: 60% By Weight
Max Product Weighted MIR: 0.7
©2018 Masterchem Industries LLC
1-866-774-6371 • www.kilz.com
REV. 07/18 • 10444