

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

SECTION 1: Identification

1.1 Product identifier

Trade name **DRYLOK® Powdered Masonry Waterproofer**
Alternative number(s) 00542; UFI: 993U-W4VN-K00G-QWUW

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Waterproofing sealers
Concrete masonry

1.3 Details of the supplier of the safety data sheet

United Gilsonite Laboratories, Inc.
1396 Jefferson Avenue
Dunmore PA 18509
United States

Telephone: +1 (570) 344-1202
Telefax: (570) 969-7634
e-mail: sales@ugl.com
Website: <http://www.ugl.com/>

e-mail (competent person) mark.fortese@ugl.com (Mark Fortese)

1.4 Emergency telephone number

Emergency information service 1-800-424-9300 Chemtrec (NORTH AMERICA)
Emergency telephone number: Outside office hours

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.6	carcinogenicity	1A	Carc. 1A	H350

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS05, GHS08



- Hazard statements

H318 Causes serious eye damage.
H350 May cause cancer.

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

- Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P280	Wear eye protection/face protection.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling Quartz (SiO₂), Calcium dihydroxide, Cristobalite

2.3 Other hazards

of no significance

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Quartz (SiO ₂)	CAS No 14808-60-7	25 - < 50	Carc. 1A / H350
Titanium dioxide	CAS No 13463-67-7	5 - < 10	Carc. 2 / H351
Calcium dihydroxide	CAS No 1305-62-0	5 - < 10	Skin Irrit. 2 / H315 Eye Dam. 1 / H318 STOT SE 3 / H335
Cristobalite	CAS No 14464-46-1	0.05 - < 1	Carc. 1A / H350
Aluminium oxide	CAS No 1344-28-1	0.05 - < 1	Acute Tox. 3 / H331

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water, Foam, ABC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Deposited combustible dust has considerable explosion potential.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains, Take up mechanically

Advice on how to clean up a spill

Take up mechanically.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment.

- Specific notes/details

Dust deposits may accumulate on all deposition surfaces in a technical room. The product in the delivered form is not dust explosion capable; the enrichment of fine dust however leads to the danger of dust explosion.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Removal of dust deposits.

- Ventilation requirements

Use local and general ventilation.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	particulates not otherwise classified		REL							appx-D	NIOSH REL
US	particulates not otherwise classified (PNOC)		PEL	1,766	15					i, dust	29 CFR 1910.1000
US	particulates not otherwise classified (PNOC)		PEL	529.5	5					partml, r, dust	29 CFR 1910.1000
US	Particulates not otherwise regulated		PEL (CA)		10					dust	Cal/OSHA PEL
US	Particulates not otherwise regulated		PEL (CA)		5					r	Cal/OSHA PEL
US	calcium hydroxide	1305-62-0	PEL (CA)		5						Cal/OSHA PEL

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	calcium hydroxide	1305-62-0	REL		5 (10 h)						NIOSH REL
US	calcium hydroxide	1305-62-0	TLV®		5						ACGIH® 2019
US	calcium hydroxide	1305-62-0	PEL		15					i, dust	29 CFR 1910.1000
US	calcium hydroxide	1305-62-0	PEL		5					r, dust	29 CFR 1910.1000
US	alpha-Alumina	1344-28-1	REL							appx-D	NIOSH REL
US	alpha-alumina	1344-28-1	PEL		15					i, dust	29 CFR 1910.1000
US	alpha-alumina	1344-28-1	PEL		5					r, dust	29 CFR 1910.1000
US	aluminium, insoluble compounds	1344-28-1	TLV®		1					r	ACGIH® 2019
US	aluminium oxide	1344-28-1	PEL (CA)		10					dust	Cal/ OSHA PEL
US	aluminium oxide	1344-28-1	PEL (CA)		5					r	Cal/ OSHA PEL
US	titanium dioxide	13463-67-7	TLV®		10						ACGIH® 2019
US	titanium dioxide	13463-67-7	PEL		15					i, dust	29 CFR 1910.1000
US	titanium dioxide	13463-67-7	REL							lowest, appx-A	NIOSH REL
US	cristobalite	14464-46-1	PEL (CA)		0.05					r	Cal/ OSHA PEL
US	silica, crystalline - cristobalite	14464-46-1	PEL		0.05					r	29 CFR 1910.1000
US	quartz	14808-60-7	PEL (CA)		0.05					r	Cal/ OSHA PEL
US	silica, crystalline - quartz	14808-60-7	PEL		0.05					r	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	REL		0.05 (10 h)					r, appx-A	NIOSH REL

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	portland cement	65997-15-1	REL		10 (10 h)					i	NIOSH REL
US	portland cement	65997-15-1	PEL		15					i, dust	29 CFR 1910.1000
US	portland cement	65997-15-1	REL		5 (10 h)					r	NIOSH REL
US	portland cement	65997-15-1	PEL		5					r, dust	29 CFR 1910.1000
US	portland cement	65997-15-1	TLV®		1					r, noAsb_less1Sil	ACGIH® 2019

Notation

appx-A	NIOSH Potential Occupational Carcinogen (Appendix A)
appx-D	see Appendix D - Substances with No Established RELs
Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
i	inhalable fraction
lowest	exposure by all routes should be carefully controlled to levels as low as possible
noAsb_less1	contains no asbestos and less than 1% free crystalline silica
Sil	
partml	particles/ml
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

Particulate filter device (EN 143).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	solid (powder)
Color	white
Odor	odorless

Other safety parameters

pH (value)	not applicable
Melting point/freezing point	not determined
Initial boiling point and boiling range	3,000 °C at 101.3 kPa
Flash point	not applicable
Evaporation rate	Not determined
Flammability (solid, gas)	this material is combustible, but will not ignite readily
Explosion limits of dust clouds	not determined
Vapor pressure	not determined
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	>400 °C
Viscosity	not relevant (solid matter)
Explosive properties	none
Oxidizing properties	none

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

Hints to prevent fire or explosion

The product in the delivered form is not dust explosion capable; the enrichment of fine dust however leads to the danger of dust explosion.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Aluminium oxide	1344-28-1	inhalation: vapor	3 mg/l/4h
Aluminium oxide	1344-28-1	inhalation: dust/mist	0.888 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
Quartz (SiO ₂)	14808-60-7	1	
Titanium dioxide	13463-67-7	2B	
Cristobalite	14808-60-7	1	

Legend

1 Carcinogenic to humans
2B Possibly carcinogenic to humans

National Toxicology Program (United States): Report on Carcinogens			
Name of substance	CAS No	Classification	Number
Cristobalite		Known to be a human carcinogen	6th Report on Carcinogens

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- | | |
|--|---|
| 14.1 UN number | not subject to transport regulations |
| 14.2 UN proper shipping name | not assigned |
| 14.3 Transport hazard class(es) | not assigned |
| 14.4 Packing group | not assigned |
| 14.5 Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 Special precautions for user | There is no additional information. |
| 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code | The cargo is not intended to be carried in bulk. |

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
Aluminium oxide	1344-28-1	fibrous forms	1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)
none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Quartz (SiO ₂)	14808-60-7		IARC Carcinogens - 1
Titanium dioxide	13463-67-7		IARC Carcinogens - 2B Prop 65
Cristobalite	14464-46-1		NTP 13th RoC - known OEHA RELs Prop 65

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Quartz (SiO ₂)		1095			1.0 %
Cristobalite		1095			1.0 %
Aluminium oxide	1344-28-1				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Quartz (SiO ₂)		A, *	
Titanium dioxide	13463-67-7	A	
Calcium dihydroxide	1305-62-0	A	
Cristobalite		A, *	

Legend

- * Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).
- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Quartz (SiO ₂)	14808-60-7		CA
Titanium dioxide	13463-67-7		
Calcium dihydroxide	1305-62-0		
Cristobalite	14464-46-1		CA
Aluminium oxide	1344-28-1		

Legend

CA Carcinogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
QUARTZ (SIO ₂)	14808-60-7	
TITANIUM OXIDE (TIO ₂)	13463-67-7	
CALCIUM HYDROXIDE (CA(OH) ₂)	1305-62-0	
ALUMINUM OXIDE (AL ₂ O ₃)	1344-28-1	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Quartz (SiO ₂)	14808-60-7	T
Titanium dioxide	13463-67-7	T
Calcium dihydroxide	1305-62-0	T
Aluminium oxide	1344-28-1	T

Legend

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
silica, crystalline		airborne particles of respirable size	cancer
titanium dioxide	13463-67-7	airborne, unbound particles of respirable size	cancer

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed
US	TSCA	not all ingredients are listed
AU	AICS	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed

Legend

AICS Australian Inventory of Chemical Substances
CICR Chemical Inventory and Control Regulation
CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)
DSL Domestic Substances List (DSL)

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

Legend

ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.4	Emergency information service: 1-800-424-9300 Chemtrec (NORTH AMERICA) This number is only available during the following office hours: Mon-Fri 08:00 AM - 05:00 PM	Emergency information service: 1-800-424-9300 Chemtrec (NORTH AMERICA) Emergency telephone number: Outside office hours	yes
2.1		Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200): change in the listing (table)	yes
2.2		- Pictograms: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.2	- Hazardous ingredients for labelling: Quartz (SiO ₂), Cristobalite	- Hazardous ingredients for labelling: Quartz (SiO ₂), Calcium dihydroxide, Cristobalite	yes
2.3	Other hazards	Other hazards: of no significance	yes
2.3	Hazards not otherwise classified		yes
2.3		Hazards not otherwise classified: change in the listing (table)	yes
2.3	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		yes
3.2		Description of the mixture: change in the listing (table)	yes
4.1	Following skin contact: Brush off loose particles from skin. Rinse skin with water/shower.	Following skin contact: Rinse skin with water/shower.	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
9.1	Auto-ignition temperature: not determined	Auto-ignition temperature: >400 °C	yes

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
11.1	Serious eye damage/eye irritation: Shall not be classified as seriously damaging to the eye or eye irritant.	Serious eye damage/eye irritation: Causes serious eye damage.	yes
12.7	Other adverse effects	Other adverse effects: Data are not available.	yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes
15.1		Hazardous Substances List (MN-ERTK): change in the listing (table)	yes
15.1		Hazardous Substance List (NJ-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (Chapter 323) (PA-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (RI-RTK): change in the listing (table)	yes
15.1		Proposition 65 List of chemicals: change in the listing (table)	yes
15.1		NPCA-HMIS® III: change in the listing (table)	yes
15.1		NFPA® 704: change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes
16	Abbreviations and acronyms		yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16		List of relevant phrases (code and full text as stated in chapter 2 and 3): change in the listing (table)	yes

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

DRYLOK® Powdered Masonry Waterproofer

Version number: REV 3.0
Replaces version of: 2020-07-28 (REV 2)

Revision: 2021-03-31

Code	Text
H350	May cause cancer.
H351	Suspected of causing cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

End of safety data sheet