

## Seaming Instructions

**NAME:** Next Level **STYLE NO.** H4117 **DATE.** 11/26/2018

**Pattern repeat:** 3/4"W x 1 7/8"L

Block pattern

### **SIDE SEAMS**

Best seam quality is achieved by cutting from face of carpet.

Using a row finder, find and separate a row that will leave on the whole block of loop yarns.

On other edge, find a row which will leave on all of the cut yarns.

Pull both pieces together and move carpet back and forth to bring on pattern match, then seam seal both cut edges.

Using a premium quality seaming tape, seam edges together, move iron in direction of the pile lay of the carpet.

Set thermostat on iron at 3 to 3 1/2 and follow with a round wheel tractor, rolling it up and down over seam.

Use a seam weight to hold seam flat, weighing no heavier than 10 lbs. allow seam to cool completely before stretching.

### **Cross Seams**

Using a row finder, find a row which will leave on the whole loop block, then using a cushion back cutter cut along the separated row, the piece of carpet with pile laying towards seam is best cut on a slight angle under cutting the face fibers.

On other piece, find and separate a row leaving on the whole cut pile block, using the cushion back cutter, cut straight up and down.

Pull both pieces together and shift slightly to align on pattern match, then seam seal both cut edges.

Using a premium quality seaming tape, seam pieces together [set thermostat on 3 to 3 1/2 setting, follow seaming

Using a round wheel tractor, tractor up and down seam, follow with a seam weight, no heavier than 10 lbs. to hold seam flat while cooling down, allow seam to completely cool before stretching.