SAFETY DATA SHEET



1. Identification

Product identifier BEHR® Solid Color House & Fence Wood Stain - Tintable White

Other means of identification

Product number 011

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process Corp.

1801 E. St. Andrew Place Santa Ana. CA 92705

 Telephone
 714-545-7101

 Emergency telephone
 +1 760 476 3962

+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 2

Specific target organ toxicity, repeated Category 2 (kidney)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer. May cause damage to organs (kidney) through prolonged or

repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe mist/vapors. Wear protective gloves/protective clothing/eye

protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	7 - 13
Diatomaceous earth	61790-53-2	3 - 7
Ethylene glycol	107-21-1	1 - 5

BEHR® Solid Color House & Fence Wood Stain - Tintable White 953218 Version #: 01 Revision date: - Issue date: 18-March-2020 Diuron 330-54-1 0.1 - 1

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion Most important Edema. Prolonged exposure may cause chronic effects. symptoms/effects, acute and

delaved Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

BEHR® Solid Color House & Fence Wood Stain - Tintable White 953218 Version #: 01 Revision date: - Issue date: 18-March-2020

8. Exposure controls/personal protection

Occupational exposure limits

Components	for Air Contaminants (29 CFR 1910.10 Type	Value	Form	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 CF	R 1910.1000)			
Components	Type	Value	Form	
Diatomaceous earth (CAS 61790-53-2)	TWA	0.8 mg/m3		
		20 mppcf		
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.	
		15 mg/m3	Total dust.	
		50 mppcf	Total dust.	
		15 mppcf	Respirable fraction.	
US. ACGIH Threshold Limit	t Values			
Components	Туре	Value	Form	
Diuron (CAS 330-54-1)	TWA	10 mg/m3		
Ethylene glycol (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.	
		50 ppm	Vapor fraction	
	TWA	25 ppm	Vapor fraction	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	vapor nacuon	
US. NIOSH: Pocket Guide t	o Chemical Hazards			
Components	Туре	Value		
Diatomaceous earth (CAS 61790-53-2)	TWA	6 mg/m3		
Diuron (CAS 330-54-1)	TWA	10 mg/m3		
logical limit values	No biological exposure limits noted for	r the ingredient(s).		
propriate engineering atrols	Good general ventilation should be us applicable, use process enclosures, lo maintain airborne levels below recommendation established, maintain airborne levels to	ocal exhaust ventilation, or oth mended exposure limits. If ex	ner engineering controls to	
ividual protection measures Eye/face protection	, such as personal protective equipme Wear safety glasses with side shields			
Skin protection Hand protection	Wear appropriate chemical resistant g	gloves.		
Skin protection Other	Use of an impervious apron is recomm	nended.		
Respiratory protection	If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.			
Thermal hazards	Wear appropriate thermal protective of	lothing, when necessary.		
i ile i ila ilazal us				

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.
Color Opaque.
Odor Slight.

Odor threshold Not available.

pH 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling > 99 °F (> 37.2 °C)

range

Flash point Not applicable
Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Vapor pressureNot available.Vapor densityNot available.

Relative density 1.28

Solubility(ies)

Solubility (water) Soluble.

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 50 - 140 KU at 25°C

Other information

Density 10.66 lbs/gal
Explosive properties Not explosive.
Oxidizing properties Not oxidizing.

VOC 41 g/l (including water) (Material)

97 g/l (excluding water) (Coating)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. **Eye contact** Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Edema. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity

Components Species Test Results

Ethylene glycol (CAS 107-21-1)

Acute Dermal

LD50 Rabbit 9530 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute Inhalation

LC50 Rat 3.43 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Description of the second of

Respiratory sensitization

Respiratory or skin sensitization

Skin sensitization This product is not expected to cause skin sensitization.

Not a respiratory sensitizer.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Diatomaceous earth (CAS 61790-53-2) 3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (kidney) through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Diuron (CAS 330-54-1) Ethylene glycol (CAS 107-21-1)

Listed.

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Carcinogenicity

categories

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Ethylene glycol	107-21-1	1 - 5	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylene glycol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Diatomaceous earth (CAS 61790-53-2)

Diuron (CAS 330-54-1)

Ethylene glycol (CAS 107-21-1)

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Diatomaceous earth (CAS 61790-53-2)

Diuron (CAS 330-54-1)

Ethylene glycol (CAS 107-21-1)

Titanium dioxide (CAS 13463-67-7)

BEHR® Solid Color House & Fence Wood Stain - Tintable White

953218 Version #: 01 Revision date: - Issue date: 18-March-2020

US. Pennsylvania Worker and Community Right-to-Know Law

Diatomaceous earth (CAS 61790-53-2)

Diuron (CAS 330-54-1)

Ethylene glycol (CAS 107-21-1)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Diatomaceous earth (CAS 61790-53-2)

Diuron (CAS 330-54-1)

Ethylene glycol (CAS 107-21-1)

Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

Issue date 18-March-2020

Revision date - 01

List of abbreviations DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

LD50: Lethal Dose, 50%.

LC50: Lethal Concentration, 50%.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PEL: Permissible Exposure Limit. STEL: Short-Term Exposure Limit. TWA: Time Weighted Average Value.

References HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer Behr Process Corp cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

BEHR® Solid Color House & Fence Wood Stain - Tintable White

953218 Version #: 01 Revision date: - Issue date: 18-March-2020