



TECHNICAL DATA SHEET
Latex•ite® OIL SPOT PRIMER
Manufacturer Product#: 1OSPC
UPC#: 090932413160



PHYSICAL PROPERTIES & PERFORMANCE

Appearance: White liquid	Maximum VOC: Less than 10 g/L
Application Temperature: 55° F and rising.	Specific Gravity: 1.2
Viscosity: N/A	Weight Per Quart: 2 lbs.
Color: White in liquid state	Consistency: Watery liquid.
Boiling Point: >212° F	Cure Time (50% relative humidity, 70° F): 2-4 hours
Freeze ability: Do not allow to freeze.	Container Size & Weight: 1 quart, approx. 2 lbs.

FEATURES

Latex•ite® OIL SPOT PRIMER is an important first step in preparing your driveway. Once you've thoroughly cleaned the driveway it's time to prepare the oil and gas spots. If you don't treat them properly, the spots will bleed through your newly sealed driveway and the stains will be back! Latex•ite® OIL SPOT PRIMER will seal over the oil and gas spots and will provide a strong bond between the driveway and the new sealer.

- **Prime oil and gas spots to ensure strong bond to new sealer.**
- **Apply with paint brush and allow to dry thoroughly prior to sealing.**

SURFACE PREPARATION

Sweep and clean off entire driveway using Latex•ite® CLEANER/DEGREASER. Scrub oil, gas spots, stains and rinse with water. Apply Latex•ite® OIL SPOT PRIMER to any oil spots/stains using a paint brush.

APPLICATION

Latex•ite® OIL SPOT PRIMER works best when applied with a paintbrush. Shake the product first. Next, simply pour a thin coat of primer over the affected area and use a brush to apply. Allow to dry thoroughly prior to using other Latex•ite products (patch / repair or sealer).

PRECAUTIONS

Avoid applying when rainfall is likely within 24-48 hours of application time. Avoid applying when temperatures drop below 55° F. When transporting this product, ensure that the container is secured and the lid is secure. Do not allow the container to tumble as this may loosen the lid and allow leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Protective clothing and eyewear should be used during application.

CLEAN UP & STORAGE

Clean up with soap and water. Containers are recyclable. Do not heat or store container in temperatures above 110° F. KEEP FROM FREEZING! Product is Non-Hazardous.

!!!CAUTION!!!

Latex•ite® OIL SPOT PRIMER is for exterior use only. Keep out of reach of children. Keep container capped when not in use. Non-flammable.

Emergency & First Aid Procedures:

Eyes: Immediately flush with clean water for 15 minutes while holding eyelids open; consult a physician.

Inhalation: If overcome by mist or vapor, remove from exposure immediately; call a physician. If breathing is stopped or irregular, start resuscitation, administer oxygen.

Skin: Remove any contaminated clothing and wash skin with soap and warm water. Vegetable or mineral oil can remove dry material.

Ingestion: DO NOT INDUCE VOMITING even though vomiting may occur. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Get immediate medical attention.