



12" SLIDING DUAL BEVEL COMPOUND MITER SAW

707212

The new JET® dual bevel sliding compound miter saw is one the most versatile saws in your shop. Efficiently cut miters, bevels, straights, and compounds with precision and accuracy over a hand saw. A workhorse in your shop that is also portable enough to take with you when you need a great saw on the job.



FEATURES

- Dual bevel capability with up front controls to maximize cutting of compound angles
- Change miter angles quickly with the single motion thumb lever
- Enclosed linear bearings allows for smooth and controlled slide operation
- Durable compact die cast aluminum construction
- Heavy duty 15 amp motor easily powers through wood
- Ergonomic, D-shaped, ambidextrous, rubber grip handle for maximum control
- Razor thin high visibility red laser provides precise cut line reference
- LED light provides additional visibility in low light areas
- Miter detent override provides fine adjustment for infinite miter angles
- Adjustable left and right fence and extension tables provide greater versatility and support
- Dust port with dust bag and 2-1/2" adaptor to maximize dust collection
- 5 second motor brake

JET RED ASSURANCE 3-YEAR WARRANTY

JET warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Service Centers located throughout the United States can give you quick service. In most cases, any of these JPW Industries Authorized Service Centers can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET tools. For the name of an Authorized Service Center in your area call 1-800-274-6848.

STAND BEHIND YOUR WORK

550+ SERVICE CENTERS NATIONWIDE | INDUSTRY-LEADING WARRANTIES | EXPERT TECHNICAL SERVICE



12" SLIDING DUAL BEVEL COMPOUND MITER SAW

707212

SPECIFICATIONS

Blade Size (In.)	12
Blade Speed (RPM)	4200
Arbor Size (In.)	5/8
Laser Guide	Red
Bevel Type	Dual
Bevel Stops	0°, 33.9°, and 45° (L/R)
Miter Stops	0°, 15°, 22.5°, 31.6°, 45° (L/R)
Miter Capacity (Deg.)	52 L, 60 R
Cut Capacity at 90° (In.)	14 x 4
Cut Capacity at 45° Miter (In.)	14 x 2 (L), 14 x 1-3/8 (R)
Cut Capacity at 45° Bevel (In.)	10 x 4
Cut Capacity at 45° Compound (In.)	10 x 2 (L), 10 x 1-3/8 (R)
Dust Bag	Included
Motor Phase (PH)	1
Motor Voltage (V.)	115
Prewired Voltage (V.)	115
Motor Amps	15



STAND BEHIND YOUR WORK

550+ SERVICE CENTERS NATIONWIDE | INDUSTRY-LEADING WARRANTIES | EXPERT TECHNICAL SERVICE