

Cupola Assembly Instructions



*Watch our Assembly Video at
www.gooddirections.com/installationinstructions or scan*





Cupola Assembly Instructions


Your Package Includes:

3 Cupola Components: Base, Mid-Section & Roof
25 - 1 5/8" Stainless Steel Screws

View our Easy to Follow Installation
Video at GoodDirections.com


1. Determine your Roof Pitch

Nail two boards together so they pivot. Straddle the roof with each board as shown. Make sure that each side is flat against the roof, and the center is at the center of the peak. Mark the boards with a pencil. This becomes your cutting template.



2. Mark the Cupola Base

Draw a center line on two opposite sides of the cupola base. Using your board template, make a line from each lower corner to make the center line. This will be your cutting line. Start cuts at corners and end at center.




3. Position

Place caulked (as shown at right) pieces of 2 x 4 to be snug against the inside walls of the cupola base. Screw them into the roof

After base is installed, caulk where base and roof meet on angle sides.


4. Mounting & Assembly

Attach the base to the 2 x 4's. Once the base is secured to the roof, attach the mid section to the base using the screws (provided) in the pre-drilled holes. Install the roof in the same manner.



Drill holes to secure cupola to 2 x 4 pieces screwed to roof (step 3).

Before screwing to roof, apply a generous bead of caulking to 2 x 4's. Then place them in position, caulk side down.



Add a Good Directions Weathervane to your Cupola for the perfect finishing touch.