



TECHNICAL DATA SHEET

PHYSICAL PROPERTIES & PACKAGING (FLOATING RESILIENT GRIPSTRIP FLOORING)

Product	Allure GripStrip 6" x 36" Plank	Allure GripStrip 12" x 24" Tile	Allure GripStrip 12" x 36" Tile
Size	6" x 36" (152.4mm x 914.4mm)	12" x 24" (304.8mm x 609.6mm)	12" x 36" (304.8mm x 914.4mm)
Construction	Solid Vinyl Tile/LVT	Solid Vinyl Tile/LVT	Solid Vinyl Tile/LVT
Use	Residential	Residential	Residential
Wear Layer	4mil (0.1mm)	4mil (0.1mm)	4mil (0.1mm)
Edge Detail	Square Edge	Square Edge	Square Edge
Embossing(s)	Barnside, In-Register	Mountainside	In-Register, Leather, Mountainside
Gauge	0.150" (3.8mm)	0.150" (3.8mm)	0.150" (3.8mm)
Pieces/Carton	16	12	8
Coverage/Piece	1.5 Sq.Ft. (0.1394 Sq.M.)	2 Sq.Ft. (0.1858 Sq.M.)	3 Sq.Ft. (0.2787 Sq.M.)
Coverage/Carton	24 Sq.Ft. (2.23 Sq.M.)	24 Sq.Ft. (2.23 Sq.M.)	24 Sq.Ft. (2.23 Sq.M.)
Limited Warranty	25-Year Residential	25-Year Residential	25-Year Residential

NORTH AMERICAN STANDARDS – MANUFACTURING & USAGE (ASTM F1700)

Standard	Description	Requirements	Results
ASTM F1700	Classification	Refer to Standard	Class III, Type B
ASTM F386	Thickness	±0.005"	Passes Requirements
ASTM F1914	Residual Indentation	Average <8%; Maximum - Any Sample ≤10%	Surpasses Requirements
ASTM F137	Flexibility	No cracks/breaks (1"/25.4mm Mandrel)	Surpasses Requirements
ASTM F2199	Dimensional Stability	≤0.020"/Linear Foot	Surpasses Requirements
ASTM F925	Chemical Resistance	No more than "Slight Change"	Passes Requirements
ASTM F1514	Resistance to Heat	Average & Max ΔE < 8.0	Surpasses Requirements
ASTM F1515	Resistance to Light	Average & Max ΔE < 8.0	Surpasses Requirements

NORTH AMERICAN STANDARDS – SAFETY & PERFORMANCE

Standard	Description	Requirements	Results
ASTM E648	Radiant Panel (Critical Radiant Flux)	Class I: ≥ 0.45 W/cm ²	Passes Requirements
ASTM E662	Smoke Density	Flaming & Non-Flaming ≤ 450	Passes Requirements
ASTM F963	Heavy Metals	Refer to Standard	Passes Requirements
ASTM D7823	Phthalates	Refer to Standard	Meets CPSIA Guidelines
ASTM D2047	Coefficient of Friction / Slip Resistance	N/A	≥0.55 (Dry)
ASTM F970	Static Load	±0.005", 250-Lbs. Load	Passes Requirements
SIM Test	Static Load Limit	Test to Limit	≥750 lbs.

NORTH AMERICAN CERTIFICATIONS

Standard	Description
FloorScore® CHPS 01350	This product is FloorScore® Certified (SCS-FS-02874) and has thus been found to comply with the volatile organic compound emissions criteria of the California Section 01350 standard.
NSF/ANSI 332	This product is NSF/ANSI 332 Gold Certified (SCS-RF-04050) and thus meets benchmark standards for social, environmental and economic sustainability as defined by the NSF/ANSI 332 standard. The assessment evaluated product design, product manufacturing, long-term value, end-of-life management, corporate governance, and innovation.