



Glass Holder installation instructions

1. Scope of application:

This instruction applies to glass hangers installed under cabinets, suitable for hanging high-heeled glasses such as red wine glasses, champagne glasses, and water glasses.

2. Required tools and accessories:

Screwdriver or electric drill

Tape measure

Pencil or marker

Installation screws (usually included with the product)

Level (optional)

3. Preparation before installation:

Confirm the position:

Choose a suitable position under the cabinet to ensure that the cup does not collide with the countertop or other objects after sagging.

Measurement and marking:

Use a tape measure to measure the spacing of the hanger mounting holes, and use a pencil to mark the installation holes at the bottom of the cabinet.

Check the cabinet material:

Make sure the bottom of the cabinet is solid wood or has enough strength to bear the weight of the hanger and glasses.

4. Installation steps:

Method 1: Standard screw fixing (the most common method)

Align the holes:

Fit the hanger to the bottom of the cabinet and adjust the position to align with the previously marked installation point.

Pre-drilling (optional):

Use a small drill bit to pre-drill shallow holes at the marked positions to help screw in the screws more smoothly.

Fix the hanger:

Use a screwdriver or electric drill to fix the hanger to the bottom of the cabinet to ensure that it is firm and not loose.

Sinber

Check after installation:

Gently shake the hanger to confirm its stability, and test whether the glass can slide in and out smoothly.

5. Precautions:

Do not overload the hanger to avoid damage or falling off caused by too many glasses.

It is recommended to hang glasses with a diameter of more than 4cm and a handle length of more than 8cm.

Clean the hanger regularly to prevent dust accumulation from affecting use.

If the cabinet bottom plate is too thin, it is recommended to use a gasket or back plate to increase the load-bearing capacity.