



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® All Purpose Spackling Paste

PRODUCT DESCRIPTION

DAP® All Purpose Spackling Paste is a ready mixed, easy-to-use patching material used to fill holes and cracks and treat surfaces prior to painting. The product has a smooth working consistency, dries quickly, is non-shrinking and sands easily. Recommended for interior use only.



| PACKAGING | COLOR | UPC |
|-----------|-------|------------|
| ½ Pint | White | 7079810222 |
| Quart | White | 7079810224 |
| Gallon | White | 7079876859 |

KEY FEATURES & BENEFITS

- **Ready-to-use**

SUGGESTED USES

Ideal for filling and concealing small cracks, nail holes and blemishes in drywall.

APPLICATION

1. Surface must be clean, dry and free of dust and particles.
2. Use sandpaper to dull glossy surface before repairing.
3. Stir thoroughly before use.
4. Apply with a clean putty knife.
5. For a smoother finish, dip putty knife in water and lightly smooth spackling.
6. For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
7. Spackling Paste can be sanded or painted in 1 to 5 hours after application, depending on temperature, humidity and depth of fill.
Wet sanding is recommended to avoid generation of dust.
8. Clean tools immediately with water.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

| | |
|--------------------------|---|
| Consistency: | Paste |
| Vehicle: | Latex Polymer |
| Volatile: | Water |
| Filler: | Inert Fillers |
| Odor: | Mild |
| Weight/Gallon: | 14.8 lbs./gal |
| Solids: | 71% by weight |
| Application Temperature: | 50°F to 100°F |
| Service Temperature: | 0°F to 150°F |
| Shelf Life: | 12 months |
| Freezing: | Freeze/thaw stable 5 cycles at 0°F |
| Drying Time | Approximately 2-5 hours depending on temperature, humidity and depth of fill) |

CLEAN UP & STORAGE

Wash tools immediately after use with water. Be sure container is closed and tightly sealed. Store in a cool, dry place.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com