



Safety Data Sheet

Issue Date 28-Aug-2013

Revision Date: 01-Oct-2017

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Onetime Lightweight Lighten Up Spackling Compound

Other means of identification

SDS # RD-0041

Product Code 0574 Series

Recommended use of the chemical and restrictions on use

Recommended Use For filling small holes in wallboard & wood. Lightweight color change spackling that goes on pink & dries white when it's time to paint.

Details of the supplier of the safety data sheet

Supplier Address

Red Devil, Inc.
4175 Webb Street
Pryor, Oklahoma 74361
www.reddevil.com

Emergency Telephone Number

Company Phone Number 918-825-5744
Fax: 918-825-5761
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Light pink – dries similar to wallboard color **Physical State** Paste **Odor** Mild Acrylic/slight ammoniacal

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | Weight-% |
|------------------------------|-------------|----------|
| Acrylic / Vinyl Acrylic | MIXTURE | <50 |
| Non-hazardous Ingredients* | Proprietary | <15 |
| Soda lime borosilicate glass | 65997-17-3 | <15 |
| Mica | 12001-26-2 | <10 |
| Calcium Carbonate | 1317-65-3 | <10 |
| Titanium Dioxide | 13463-67-7 | <1 |
| Phenolphthalein | 77-09-8 | <0.15 |

* Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). (Calcium Carbonate, Titanium Dioxide, Mica, Phenolphthalein and Soda lime borosilicate glass) Inhalation of particulates unlikely due to product's physical state.

4. FIRST-AID MEASURES

First Aid Measures

| | |
|-----------------------|---|
| General Advice | Provide this SDS to medical personnel for treatment. |
| Eye Contact | Immediately flush with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention. |
| Skin Contact | Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing. |
| Inhalation | Remove to fresh air. If breathing is difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention. |
| Ingestion | Do not induce vomiting unless directed by medical personnel. If vomiting occurs, lean patient forward to maintain an open airway & prevent aspiration. Get immediate medical attention. |

Most important symptoms and effects

| | |
|-----------------|--|
| Symptoms | Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and sneezing. |
|-----------------|--|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|---|
| Notes to Physician | Medical Conditions Aggravated by Exposure: Asthma & asthma-like conditions may worsen from prolonged or repeated exposure to dust, should sanding be performed. |
|---------------------------|---|

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Dry chemical. Water spray (fog). Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product may ignite and burn at temperatures exceeding the flash point.

Hazardous Combustion Products Carbon oxides. Nitrogen oxides (NOx).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

| | |
|----------------------------------|--|
| Personal Precautions | Wear protective clothing as described in Section 8 of this safety data sheet. |
| Other Information | Small Spills: 1 drum or less – Level D Equipment (gloves, chemical resistant apron, boots & eye protection). Large Spills: Rubber gloves, rubber boots, face shield & Tyvek suit as a minimum. Minimum level of PPE for releases in which the oxygen level is < 19.5% or is unknown, should be Level B: triple gloves (rubber gloves & nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing & boots, hard hat & self-contained breathing apparatus. |
| For Emergency Responders | Restrict access to spill area. |
| Environmental Precautions | Minimize use of water to prevent environmental contamination. Prevent spill or rinse from contaminating storm drains, sewers, soil or groundwater. Do not allow discharge containing this material to enter streams, ponds, estuaries, oceans or other waters unless in accordance w/ requirements of National Pollutant Discharge Elimination System (NPDES) permit & permitting authority has been notified in writing prior to discharge. Do not allow discharge containing this material to enter sewer systems w/o previously notifying local sewage treatment plant authority. For information, contact State Water Board or EPA Regional Office Other: U.S. regulations may require reporting of spills of this material reaching surface waters if sheen is formed. |

Methods and material for containment and cleaning up

| | |
|--------------------------------|--|
| Methods for Containment | Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill. |
| Methods for Clean-Up | Sweep up absorbed material and shovel into suitable containers for disposal. Wash area with soap and water. For waste disposal, see section 13 of the SDS. |

7. HANDLING AND STORAGE

Precautions for safe handling

| | |
|--------------------------------|--|
| Advice on Safe Handling | Keep out of reach of children & pets. Do not take internally. Do not breathe vapors or dust. If dry sanding use NIOSH-approved dust mask. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing. Do not eat or drink while handling this material. In event of spill – see Section 6. |
|--------------------------------|--|

Conditions for safe storage, including any incompatibilities

| | |
|---------------------------|---|
| Storage Conditions | Stable under normal conditions of handling, use & storage. Store containers in a cool, dry location, away from direct sunlight & high temperatures. Protect from freezing. Store away from incompatible materials (caustics & oxidizers). Close container after each use & keep tightly closed when not in use. To maximize shelf life, store @ temperatures below 26C (80F). |
|---------------------------|---|

Incompatible Materials

Strong bases. Oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Exposure guidelines / protective equipment are for routine handling and accidental spills

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--|--|--|--|
| Soda lime borosilicate glass 65997-17-3 | TWA: 1 fiber/cm ³ respirable fibers: length >5 μm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m ³ inhalable fraction | - | - |
| Mica 12001-26-2 | TWA: 3 mg/m ³ respirable fraction | (vacated) TWA: 3 mg/m ³ respirable dust <1% Crystalline silica TWA: 20 mppcf <1% Crystalline silica | IDLH: 1500 mg/m ³ TWA: 3 mg/m ³ containing <1% Quartz respirable dust |
| Calcium Carbonate 1317-65-3 | - | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction | TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |
| Titanium Dioxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust | IDLH: 5000 mg/m ³ |

Appropriate engineering controls**Engineering Controls**

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Provide appropriate local exhaust ventilation if material is to be sanded.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Use approved safety goggles or safety glasses. If necessary, refer to appropriate regulations & standards.

Skin and Body ProtectionSkin: Wear chemical resistant rubber gloves for repeated or prolonged use.
Body: Not required w/ normal use.**Respiratory Protection**

Avoid breathing of dust. Avoid breathing of vapors, mists or spray. If concentrations exceed exposure limits specified, use a NIOSH-approved supplied air respirator. If protection factor exceeded, use self contained breathing apparatus (SCBA). A respiratory protection program that exceeds OSHA 1910.134 & ANSI Z88.2 requirements should be followed when conditions warrant respirator use. If dry sanding preferred, use approved NIOSH/OSHA respirator.

General Hygiene Considerations

Wash hands w/ soap & water before breaks & @ end of workday. Remove & wash contaminated clothing prior to re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------|---|-----------------------|--------------------------------|
| Physical State | Paste | Odor | Mild Acrylic/slight ammoniacal |
| Appearance | Light pink – dries similar to wallboard color | Odor Threshold | Not determined |
| Color | Light pink – dries similar to wallboard color | | |

| | | |
|------------------------|---|--------------------------------|
| <u>Property</u> | <u>Note: The information below is not intended for use in preparing product specifications</u> | <u>Remarks • Method</u> |
|------------------------|---|--------------------------------|

| | | |
|-------------------------------------|-----------------------------|-----------------|
| pH | 7.0-10.0 | |
| Melting Point/Freezing Point | ~ 0 °C / ~32 °F | |
| Boiling Point/Boiling Range | Not established | |
| Flash Point | > 93.33 °C / > 200 °F | Ceta Closed Cup |
| Evaporation Rate | Slower than n-Butyl Acetate | |
| Flammability (Solid, Gas) | Not determined | |
| Upper Flammability Limits | Unknown | |
| Lower Flammability Limit | Unknown | |
| Vapor Pressure | Not established | |
| Vapor Density | Heavier than air | |
| Specific Gravity | ~0.30-0.40 | @ 25 °C (77 °F) |
| Water Solubility | Soluble in water | |
| Solubility in other solvents | Not determined | |
| Partition Coefficient | Not determined | |
| Autoignition Temperature | Not determined | |
| Decomposition Temperature | Not determined | |
| Kinematic Viscosity | Not determined | |
| Dynamic Viscosity | Not determined | |
| Explosive Properties | Not determined | |
| Oxidizing Properties | Not determined | |
| VOC Content (%) | 0.5% | |
| VOC Content | < 10 g/L | |

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

| | |
|---------------------------------|--|
| Hazardous Polymerization | Hazardous polymerization does not occur. |
|---------------------------------|--|

Conditions to Avoid

Incompatible Materials. Excessive heat or cold.

Incompatible Materials

Strong bases. Oxidizing agents.

Hazardous Decomposition Products

Carbon oxides. Nitrogen oxides (NOx).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

| | |
|---------------------|---|
| Eye Contact | Eye contact may result in tearing, redness & pain. |
| Skin Contact | Prolonged and frequent contact may cause redness and irritation. Repeated skin contact may cause dermatitis. |
| Inhalation | Overexposure to vapors during application & curing may mildly irritate respiratory tract & result in coughing & sneezing. |
| Ingestion | May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. |

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--------------------------------|-----------------------|-------------|-----------------|
| Titanium Dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |

Information on physical, chemical and toxicological effects

| | |
|-----------------|--|
| Symptoms | Please see section 4 of this SDS for symptoms. |
|-----------------|--|

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|------------------------|--|
| Sensitization | Not known to be human skin or respiratory sensitizers. |
| Carcinogenicity | Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Product contains trace amounts of residual Formaldehyde. OSHA & NTP identify Formaldehyde as a potential carcinogen. IARC identifies Formaldehyde as a human carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, w/ human significance unknown. Rats have shown carcinogenic effects in respiratory system. Risk should be minimal when used w/ adequate ventilation. Maintain adequate ventilation to prevent exposure above OSHA exposure limits. Phenolphthalein is a possible carcinogen when it appears as a respirable dust. |

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|--|-------|----------|------------------------|------|
| Soda lime borosilicate glass 65997-17-3 | | Group 3 | | |
| Titanium Dioxide 13463-67-7 | | Group 2B | | X |
| Phenolphthalein 77-09-8 | | Group 2B | Reasonably Anticipated | X |

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

| | |
|-----------------------------|------------------------------------|
| Target organ effects | Acute: Eyes & Skin. Chronic: Skin. |
|-----------------------------|------------------------------------|

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

PRACTICES SHOULD BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

not tested for aquatic or animal toxicity. Release of product to terrestrial, atmospheric & aquatic environments should be avoided.

Persistence/Degradability

Not tested for persistence & biodegradability

Bioaccumulation

Not tested for bio-accumulation potential

Mobility

Not tested for mobility in soil

Other Adverse Effects

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

Ozone

Not expected to produce any ozone depletion

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Not Applicable

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

Not regulated

IATA

Not regulated

IMDG

Not regulated

15. REGULATORY INFORMATION

International Inventories

| | |
|-------------|--------|
| TSCA | Listed |
| DSL | Listed |
| NDSL | Listed |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

SARA 311/312 Hazard Categories

| | |
|--|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | No |
| Fire Hazard | No |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

SARA 313

| Chemical Name | CAS No | Weight-% | SARA 313 - Threshold Values % |
|---------------------------|---------|----------|-------------------------------|
| Phenolphthalein - 77-09-8 | 77-09-8 | <0.15 | 0.1 |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

| Chemical Name | California Proposition 65 |
|-------------------------------|---------------------------|
| Titanium Dioxide - 13463-67-7 | Carcinogen |
| Phenolphthalein - 77-09-8 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|--------------------------------|------------|---------------|--------------|
| Mica 12001-26-2 | X | X | X |
| Calcium Carbonate 1317-65-3 | X | X | X |
| Titanium Dioxide 13463-67-7 | X | X | X |
| Phenolphthalein 77-09-8 | X | | |

16. OTHER INFORMATION

| | | | | |
|--------------------|-----------------------|---------------------|-------------------------|----------------------------|
| <u>NFPA</u> | Health Hazards | Flammability | Instability | Special Hazards |
| | 1 | 0 | 0 | Not determined |
| <u>HMIS</u> | Health Hazards | Flammability | Physical Hazards | Personal Protection |
| | 1 | 0 | 0 | X |

Issue Date 28-Aug-2013
Revision Date: 25-Sep-2013
Revision Note New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet