

Features:

- Long-fiber aspen pads for superior cooling
- Cabinets made from 24-Gauge, G60 grade galvanized steel
- One piece drawn water pan for rust protection and durability
- Polymer bonded coating in wet section to prevent corrosion
- Rugged welded construction
- Heavy duty constructed blower wheel
- Solid steel drive shaft
- ETL safety rated



Performance Specifications

Model	Mount	Drive	Nominal CFM	Motor Electrical Specifications					Pump	Belt
				HP	Speeds	Volts	Hz	Amps		
W28	Window	Direct	2800	1/8	2	115	60	3.2	220	N/A
W38	Window	Belt	3800	1/3	2	115	60	5.5	220	A-43 (4L-450)
W48	Window	Belt	4800	1/2	2	115	60	7.5	380	A-57 (4L-590)

Specifications shown with recommended Hessaire Fanpac motors

Dimensions / Weights Specifications

Model	Cabinet (In.)			Duct Location (In.)					Drain (In.)		Pan (In.)	Unit Weight (lbs)		Media Pad Dims (In.)		Blower Wheel Dims (In.)			Blower Pulley (In.)	
	Height	Width	Depth	Opening		Position			Position			Ship	Operating	# Per Unit	Height	Width	Dia.	Width		Shaft Dia.
	H	W	D	A	B	C	E	L	F	G	J									
W28	27	22	22	9 5/8	18 11/16	14 1/2	1 3/4	9	11	6 5/16	3	56	96	3	23	17 1/2	9	8	1/2	N/A
W38	28 1/4	28	28	10 3/4	22 1/3	13 3/16	3	10	14 1/8	5 1/4	3 1/2	80	181	3	22 7/16	22 3/4	12	12	5/8	7
W48	35 1/4	34	34	12 1/4	23 1/8	17 1/4	5 1/4	10	17 5/8	5 1/4	3 1/2	123	262	3	29 1/4	28 1/2	16	16	1	11

