

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: 876 B'ment W/proofer silver gray

Product Code: 876 MSDS Manufacturer 876

Number:

Manufacturer Name: BEHR Process Corporation
Address: 3400 W. Segerstrom Avenue

Santa Ana, CA 92704

 General Phone Number:
 (714) 545-7101

 General Fax Number:
 (714) 241-1002


 Customer Service Phone
 (800) 854-0133 ext. 2

Number:

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300
Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)

MSDS Creation Date: June 26, 2006
MSDS Revision Date: June 30, 2011

MSDS Format: According to ANSI Z400.1-2004



HMIS	
Health Hazard	1
Fire Hazard	1
Reactivity	0
Personal Protection	

Chronic Health Effects

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Nepheline Syenite	37244-96-5	10 - 30 by weight
Titanium dioxide	13463-67-7	5 - 10 by weight
Undisclosed/Proprietary	No data	1 - 5 by weight
Non hazardous ingredient(s)	Not applicable	30 - 60 by weight
Ethylene glycol	107-21-1	1 - 5 by weight
Dipropylene glycol butoxy ether	29911-28-2	1 - 5 by weight
Styrene/Acrylate copolymer	Propritary	30 - 60 by weight

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: Irritant.

Potential Health Effects:

Eye: May cause irritation.

Skin: May cause irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation.

Signs/Symptoms: Overexposure may cause headaches and dizziness.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing

Conditions:

None generally recognized.

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical

attention, if irritation or symptoms of overexposure persists.

Skin Contact: Immediately wash skin with soap and plenty of water.

Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give

oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center

immediately. Never give anything by mouth to an unconscious person.

Other First Aid: Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested.

Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: No Data

Lower Flammable/Explosive Limit: Not applicable.

Upper Flammable/Explosive Limit: Not applicable.

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray

when fighting fires involving this material.

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH

(approved or equivalent) and full protective gear.

NFPA Ratings:

NFPA Health: 1

NFPA Flammability: 1

NFPA Reactivity: 0

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Use proper personal protective equipment as listed in section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Spill Cleanup Measures: Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical

waste container. Provide ventilation. Clean up spills immediately observing

precautions in the protective equipment section.

SECTION 7 - HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes,

skin and clothing.

Storage: Store in a cool, dry, well ventilated area away from sources of heat, combustible

materials, and incompatible substances. Keep container tightly closed when not

in use.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling

vapor or mist.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust

ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR

1910.133, OSHA eye and face protection regulation, or the European standard

EN 166.

Skin Protection Description: Chemical-resistant gloves and chemical goggles, face-shield and synthetic

apron or coveralls should be used to prevent contact with eyes, skin or clothing.

Respiratory Protection:

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne

concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may

not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash

facility and a safety shower.

EXPOSURE GUIDELINES

<u>Titanium dioxide</u>:

Guideline ACGIH: TLV-TWA: 10 mg/m3
Guideline OSHA: OSHA-TWA: 15 mg/m3

Ethylene glycol:

Guideline ACGIH: TLV-STEL: C 100 mg/m3 (Aerosol only)

876 B'ment W/proofer silver gray

Revison: 6/30/2011, Version: 0

BEHR Process Corporation

Page: 2 of 5

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liauid. **Boiling Point:** No Data Melting Point: No Data

Density: 10 - 12 Lbs./gal.

Vapor Density: Greater than 1 (Air = 1).

No Data Molecular Formula: Mixture Molecular Weight: Mixture Flash Point: No Data

VOC Content: Material VOC: 70 gm/l (Includes Water)

Coating VOC.: 137 gm/l (Excludes Water)

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Hazardous Polymerization: Not reported.

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below $32\,$

deg. F.

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

SECTION 11 - TOXICOLOGICAL INFORMATION

Nepheline Syenite:

RTECS Number: OP9365000

Titanium dioxide:

RTECS Number: XR2275000

Skin: Administration onto the skin - Human Standard Draize test.: 300 ug/3D

(Intermittent) (RTECS)

Ethylene glycol:

RTECS Number: KW2975000

Eye - Rabbit TDLo: 10 pph [Sense Organs and Special Senses (Eye) -Eve:

Conjunctive irritation1

Eve - Rat Standard Draize test.: 0.012 %/3D Eve - Rabbit Standard Draize test.: 500 mg/24H Eye - Rabbit Standard Draize test.: 100 mg/1H Eye - Rabbit Standard Draize test.: 0.012 ppm/3D Eye - Rabbit Standard Draize test.: 1440 mg/6H (RTECS)

Skin: Administration onto the skin - Rabbit LD50: 9530 uL/kg [Details of toxic effects

not reported other than lethal dose value]

Administration onto the skin - Rabbit Open irritation test: 555 mg (RTECS)

 $\mbox{O}\,\mbox{ral}$ - Rat LD50: 4700 mg/kg [Details of toxic effects not reported other than Ingestion:

lethal dose value1

Oral - Guinea pig LD50: 6600 mg/kg [Details of toxic effects not reported other

than lethal dose value]

Oral - LD50: 2000 mg/kg [Details of toxic effects not reported other than lethal

dose value]

Oral - Mouse LD50: 5500 mg/kg [Details of toxic effects not reported other

than lethal dose value]

Oral - LD50: 5500 mg/kg [Kidney/Ureter/Bladder - Other changes] Oral - LD50: 1650 mg/kg [Kidney/Ureter/Bladder - Other changes] Oral - Guinea pig LD50: 6610 mg/kg [Behavioral - Somnolence (general depressed activity) Gastrointestinal - Other changes Kidney/Ureter/Bladder -

Other changes] (RTECS)

Dipropylene glycol butoxy ether:

RTECS Number: UA8200000

Eye - Rabbit Standard Draize test.: 100 mg (RTECS) Eye:

Skin: Administration onto the skin - Rabbit LD50: 5860 uL/kg [Behavioral -

> Somnolence (general depressed activity) Gastrointestinal - Hypermotility, $diarrhea\ Lungs, Thorax, or\ Respiration\ -\ Other\ changes]\ (RTECS)$

Indestion: Oral - Rat LD50: 1620 uL/kg [Behavioral - Somnolence (general depressed

activity) Behavioral - Ataxia Skin and Appendages - Hair] (RTECS)

BEHR Process Corporation

Page:3 of 5

876 B'ment W/proofer silver gray Revison:6/30/2011. Version:0

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the

classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

SECTION 14 - TRANSPORT INFORMATION

DOT UN Number: No Data

DOT Hazard Class: No Data

SECTION 15 - REGULATORY INFORMATION

California PROP 65: WARNING: This product contains a chemical known to the state of California to

cause cancer and birth defects or other reproductive harm.

Nepheline Syenite:

TSCA Inventory Status: Not listed

Canada DSL: Listed

Titanium dioxide:

TSCA Inventory Status: Listed

State Regulations: Listed in the New Jersey State Right to Know List.

Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL: Listed

Ethylene glycol:

TSCA Inventory Status: Listed

State Regulations: Listed in the New Jersey State Right to Know List.

Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL: Listed

 $\underline{\mbox{Dipropylene glycol butoxy ether}}:$

TSCA Inventory Status: Listed
Canada DSL: Listed

SECTION 16 - ADDITIONAL INFORMATION

HMIS Health Hazard: 1
HMIS Fire Hazard: 1
HMIS Reactivity: 0
HMIS Other: x

MSDS Creation Date: June 26, 2006
MSDS Revision Date: June 30, 2011

MSDS Revision Notes: Quarterly formula update

MSDS Author: Actio Corporation

Disclaimer: This Health and Safety Information is correct to the best of our knowledge and

belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.

Trademark: The trademarks, service marks, graphics and logos used on this MSDS are

registered or unregistered trademarks of BEHR Process Corporation. All Rights

Reserved.

Copyright© 1996-2011 Actio Corporation. All Rights Reserved.

876 B'ment W/proof er silv er gray Revison:6/30/2011, Version:0