

PRODUCT SPECIFICATION


Item name	Nate 18W Square Pouf	
Item code	AXCPF18-11-DNM	Patterned Denim Mélange
	AXCPF18-11-G	Patterned Grey Mélange
Item dimension	W18" x D18" x H14"	Factory Name - Shyam

I. GENERAL INFORMATION**1.1. Product picture of All Color Variations**

AXCPF18-11-DNM



AXCPF18-11-G


**1.2. General Dimension****I.3. Main materials:**

Component	Material	Requirements
Main material	100% Cotton	
Inter Liner	Cotton	
Filler	100 % polystyrene EPS Ball	

I.4. Exploded View of item:

II. CONSTRUCTION

II.1. Technical drawings



II.2. Construction requirements

- Before mass production, product needs to pass all related tests – conform to US Consumer Product Safety Commission - at Simpli Home approved test labs.
- All wood must be kiln dry before production and maintained at a humidity level between 8-12% during the manufacturing process.
- The variance of moisture between 2 lamellas cannot be over 2%.
- Width of lamination: should be between 40-80mm. The lamination should have the same width on a board.
- All wood must be free from insect or fungal contamination.
- Wood with sign of previous contamination must not be used (woodworm holes, signs of mold...).
- All products must be free from physical defects such as poor finish, patchy areas, contamination, pin holes or pitting.
- The surface finish must not discolor, come loose, peel, chip or flake during normal handling or use.
- Finished wood must be smooth and evenly finished, free from cracks, splinters, rough edges and uneven coatings. Hair cracking is considered as critical point.
- Dent, chipped mark, nick... are not allowed.
- Dead knots must not be present on finished wood.
- Filler must not be visible on visual surface (always in view by customer) and must be no bigger than 5mm x 5mm on other surfaces.
- All load bearing pieces must be free of knots.
- There must not be knots at joints.
- Live knots must be less than 2cm and not exceed 1/3 width of lamella. And only 3 live knots are allowed on each surface, spacing between live knots need to be minimum 10 centimeters.
- Sap wood: can not be visible. It's allowed for max length 10cm + width 1cm on hidden surface.
- Discolor / Black grain: must not acceptable in visible surface.

III. FINISHING

III.1. Color

AXCPF18-11-DNM



AXCPF18-11-G



III.2. Finishing requirements

Property	Test Code	Limit
Chemical requirements		
- Total lead in surface coating	16 CFR 1303	90ppm
- Phthalates Content	US CPSIA 2008 Sec. 108	1000ppm
Physical requirements		
- Adhesion Test	ASTM D3359 (Mod)	Class 3
- Hardness Test	ASTM D3363 - 05(2011) e2 Mod.	
Color fastness to light 60h	AATCC 16.3 – 2014, Xenon-Arc-Lamp, 60 AFU	Grade 4

- Color swatch should be approved by Simpli Home before production starts.
- Any treatment use on wood (stain, preservatives, varnishes) must not release color or other staining during use.
- Lacquer / coating should be tested at Approved Labs according to CPSC before mass production.
- All surfaces have to be sanded properly with appropriated sanding papers (No. 120 – 150 – 180 – 220 – 320 – due to each stage of process) before painting applied.
- All parts must be stained properly on all surfaces and all edges including the surfaces that might end up hidden.
- The bottom of the legs and the bottom edge of side panels should be painted or sealed with lacquer.
- All pre-fixed structures have to be pre-stained correctly prior to assembling. This will avoid exposed unfinished lines once these parts shrunk.
- Pre-stains should be applied with darker color than color of products.
- Especially on edges of furniture: all edges should be WELL finished: on the exposed edges of the drawers, edges of top panels, tops of frame, side of frame, inside the cabinet.
- The NC coating should be evenly spread on the surface of the wood, and due to there are different absorption rates on the wood surface, factory has to apply more coating to the edges, in order to make these edges appear to have better finish.
- Finishing steps and lacquer used should follow the steps mentioned on the color swatch signed by Simpli Home. Any change needs to be approved prior to applying.
- Color must be consistent from product to product, from order to order.

IV. HARDWARE

IV.1. Key hardware requirements

Ref.	Code	Hardware Description	Unit	Qty	ASSM
1		N/A	pc		NO
2		N/A	pc		NO

IV.2. Extra hardware requirement for product assembled by end users.

Packaging of products must include a specific extra hardware as replacement for broken / missing hardware. Hardware items and quantity will be specified for each item level.

For packing of hardware, see VI.

IV.3. Hardware/ Fitting requirements

Property	Test Code	Limit
Chemical requirements		
- Total lead in surface coating	16 CFR 1303	90ppm
- Phthalates in surface coating	US CPSIA 2008 section 108	1000ppm
Physical requirements		
- Resistance to corrosion	ASTM B117-19 (Mod)	Shall withstand 24 hours in 1% salt spray (fog) with no noticeable oxidation / corrosion / visual changes.

V. PACKAGING

V.1. Packaging Instruction

Product to be packed according Simpli Home approved Packaging Instruction.

V.2. Packaging requirements

- Product should be dried completely before packaging.
- Product should be cleaned completely before packaging. Any dust, stains... are not allowed on any surface.


Property	Requirement	Document
Carton full packed	ISTAA (N/A)	
Carton type	RSC Carton	
Carton cardboard	Double-wall (5 Ply) Corrugated, 6.5mm thickness. Burst strength: Minimum of 275psi	
Carton layout	Must be approved by Simpli Home	
Marking	Exactly the same as Simply Home marking, includes color(s)	
All sides inside carton	Wrap with Non-Woven Fabric	
All edges inside carton		
All parts	Wrapped by paper protect sheet. Protect sheets must cover all surfaces to avoid damage of parts during transit.	
Simpli Home leaflet	Must be included inside carton	
Two short open edges of carton	Use reinforcing tape (fiberglass tape) 70mm	
Four open edges of carton	Use clear tape 80mm (cover the reinforce tape where overlap). Do not apply the scotch tape across the open edge. Tape should not cover the barcode number	

Hardware red strings identifier	Visible from outside of carton	
Torn, scratches, dirty... boxes	Not accepted	

V. 3. Hardware package

Property	Requirement
Each type of hardware	Packed separately in a zip-bag, with a label that shows the hardware number according to Assembly Instruction
Handles/Knob	Packed in individual bag for surface protection before putting into zip-bag
Extra hardware	Packed in separate bag with "EXTRA HARDWARE" label. Each type of hardware inside also packed in separate bag with label
Anti-tipping kit	Packed in individual bag. Outside of bag having guide line and information of manufacture
Hardware bag	Must be clear of all wood parts and must be completely covered by protection sheet, then wrapped by 2 ply cardboard sheet. Hardware bags must be placed firmly in a preserved room to avoid damage or scratch the wood parts.

V.4. Warning label

Description	Example	Position	Required
Warning		Bottom of the product	Yes
Zipper Warning		Bottom of the product	No
Law Label US		Bottom of the product	Yes
Law Label CANADA		Bottom of the product	Yes