1_P	RODUCT AND COMPANY	Supersedes Revision: 03/11/2020	
Product Name:	Klean Strip Premium Stripper Aero		
Company Name:	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	<b>Phone Number:</b> (901)775-0100	
Web site address: Emergency Contact: Information:	www.wmbarr.com 3E 24 Hour Emergency Contact W.M. Barr Customer Service	(800)451-8346 (800)398-3892	
Intended Use: Product Code:	Paint/Varnish Remover EKPS302		
	2. HAZARDS IDENTI	FICATION	
Gas Under Pressure, Liquefie Simple Asphyxiant Skin Corrosion/Irritation, Cato Serious Eye Damage/Eye Irrit Germ Cell Mutagenicity, Cate Carcinogenicity, Category 1B Specific Target Organ Toxicit	egory 2 ation, Category 2 gory 1B		
GHS Signal Word: GHS Hazard Phrases:	Danger Flammable aerosol. Containers gas under pressure; may Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. May cause damage to organs through HUS1: May displace oxygen and caus	h prolonged or repeated exposure.	
GHS Precautionary Phrases:	<ul> <li>HUS1: May displace oxygen and cause rapid suffocation.</li> <li>Cobtain special instructions before use.</li> <li>Do not handle until all safety precautions have been read and understood.</li> <li>Keep away from heat/sparks/open flames/hot surfaces No smoking.</li> <li>Do not spray on an open flame or any other ignition source.</li> <li>Pressurized container: Do not pierce or burn, even after use.</li> <li>Do not breathe gas/mist/vapors/spray.</li> <li>Wash hands thoroughly after handling.</li> <li>Wear protective gloves/protective clothing/eye protection/face protection.</li> <li>Use personal protective equipment as required.</li> </ul>		
GHS Response Phrases:	IF ON SKIN: Wash with plenty of soa	p and water. Iter for several minutes. Remove contact lenses, if sing. al attention/advice. el unwell. dvice/attention.	
Licensed to W.M. Barr and Company		GHS form	

			Supersedes Revision: 03/11/2020		
GHS Storage and Disposal Phrases: Potential Health Effects (Acute and Chronic):		Store locked up. Protect from sunlight and store in well-ventilated place. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container according to local, state and federal regulations.			
		See above.			
-	3. CO	MPOSITION/INFOR	MATION ON INGREDIENTS		
CAS #	Hazardous Com	oonents (Chemical Name)	Concentration		
616-38-6	Dimethyl carbona		30.0 -60.0 %		
67-68-5	Methyl sulfoxide	{Dimethyl sulfoxide; DMSO}	10.0 -30.0 %		
1330-20-7	Xylene (mixed iso	mers) {Benzene, dimethyl-}	10.0 -30.0 %		
68476-86-8	Liquified petroleur isobutane, n-buta	m gas, sweetened   {propane, ne}	7.0 -13.0 %		
100-41-4	Ethylbenzene {Et	hylbenzol; Phenylethane}	1.0 -5.0 %		
68439-46-3	Alcohol ethoxylate	e (Alcohols, C9-11, Ethoxylated)	0.1 -1.0 %		
98-82-8	Cumene {Benzer Isopropylbenzene	ne, 1-Methylethyl-; ;}	0.1 -1.0 %		
1095-66-5	Oleic acid, compo	ound with morpholine (1:1)	0.1 -1.0 %		
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}		0.1 -1.0 %		
110-91-8	8 Morpholine {Diethylene imidoxide} 0.1 -1.0 %		0.1 -1.0 %		
66455-14-9	Alcohols, C12-13, ethoxylated		0.1 -1.0 %		
Additional Ch	nemical		position is being withheld as a trade secret.		
		4. FIRST All	D MEASURES		
Emergency a Procedures:	and First Aid		the skin thoroughly with large amounts of water and mild oving contaminated clothing. Seek medical attention if		
			eyes with water, remove any contact lens. Continue to flush utes, then seek immediate medical attention.		
		Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.			
		Ingestion: If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.			
Signs and Sy Exposure:	-	See Section 2.			
Note to Phys	ician:				
Licensed to W.N	I. Barr and Company		GHS form		

	5. FIRE FIGHTING MEASURES
	Level 2 Aerosol
Flash Pt:	61.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: N.D. UEL: N.D.
Autoignition Pt:	N.D.
	: Use carbon dioxide, dry powder, or alcohol resistant foam.
Unsuitable Extinguishing Media:	Do not use straight streams of water. If water is used, use a water spray or fog.
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
Flammable Properties and	Danger! Flammable. Keep away from heat, sparks, flame, and all other sources of
Hazards:	ignition. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves,
	heaters, electric motors and all other sources of ignition during use and until all vapors
	are gone. Beware of static electricity that may be generated by synthetic clothing and other sources.
Hazardous Combustion	Carbon monoxide, carbon dioxide. sulfur oxides, hydrogen sulfide
Products:	Carbon monoxide, carbon dioxide. Sundi oxides, nydrogen sunde
	6. ACCIDENTAL RELEASE MEASURES
Steps To Be Taken In Case Material Is Released Or	Vapors may cause flash fire or ignite explosively.
Spilled:	Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. U proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.
	Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.
	7. HANDLING AND STORAGE
Precautions To Be Taken in Handling:	Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispos of empty container according to all regulations. Do not reuse this container.
	Do not use this product near any source of heat or open flame, furnace areas, pilot lights stoves, etc.
	Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.
	Do not spread this product over large surface areas because fire and health safety risks
	will increase dramatically.

#### Precautions To Be Taken in Storing:

Store in a cool place in original container and protect from sunlight. Exposure to high temperatures or prolonged exposure to sun may cause can to leak or swell. Do not store near flames or at elevated temperatures.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS # Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
616-38-6 Dimethyl carbonate	ACGIH TLV	TLV: 500 ppm STEL: 750 ppm	
	OSHA PELs	PEL: 1000 ppm	
1330-20-7 Xylene (mixed isome {Benzene, dimethyl-}	ers) ACGIH TLV	TLV: 100 ppm STEL: 150 ppm	
	OSHA PELs	PEL: 100 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	
100-41-4 Ethylbenzene {Ethylbenzol; Phenylethane}	ACGIH TLV	TLV: 20 ppm STEL: 125 ppm	
	OSHA PELs	PEL: 100 ppm	
98-82-8 Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene	ACGIH TLV }	TLV: 50 ppm	
	OSHA PELs	PEL: 50 ppm	
67-56-1 Methanol {Methyl alco Carbinol; Wood alcohol}	hol; ACGIH TLV	TLV: 200 ppm STEL: 250 ppm	
	OSHA PELs	PEL: 200 ppm	
110-91-8 Morpholine {Diethyler imidoxide}	e ACGIH TLV	TLV: 20 ppm	
	OSHA PELs	PEL: 20 ppm	
Respiratory Equipment (Specify Type):		n inadequate ventilation or fresh air, wear a pi H approved self-contained breathing apparatu tting hood.	
		d work places and other regular users - Use o gineered air control systems designed to prev	•
	A dust mask does n	ot provide protection against vapors.	
Eye Protection:	Chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical contact to the face and eyes.		
Protective Gloves:	Wear gloves with as much resistance to the chemical ingredients as possible. Laminate film gloves offer the best protection. Consult your glove supplier for additional information Gloves contaminated with product should be discarded and not reused.		
Other Protective Clothing:	such as impermeabl any clothing or prote any clothing or other	methods can dictate use of additional protecti le aprons, etc., to minimize exposure. Before active equipment that has been contaminated protective equipment that cannot be deconta	reuse, thoroughly clea by prior use. Discard
	gloves or shoes.		

Engineering Controls       Use process enclosures, local exhaust ventilation, or other engineering controls to airborne levels below recommended exposure limits.         Use only with adequate ventilation to prevent buildup of vapors. If the work area is well ventilated, DO NOT use this product. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed ar         Whenever possible, use outdoors in an open air area. If using indoors open all wir and doors and maintain a cross ventilation of moving fresh air across the work are strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering STOP ventilation is inadequate. Leave area immediately and mo fresh air.	not eas. ndows a. If
Use only with adequate ventilation to prevent buildup of vapors. If the work area is well ventilated, DO NOT use this product. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed ar Whenever possible, use outdoors in an open air area. If using indoors open all wir and doors and maintain a cross ventilation of moving fresh air across the work are strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering STOP ventilation is inadequate. Leave area immediately and mo	eas. ndows a. If
well ventilated, DO NOT use this product. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed ar Whenever possible, use outdoors in an open air area. If using indoors open all wir and doors and maintain a cross ventilation of moving fresh air across the work are strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering STOP ventilation is inadequate. Leave area immediately and mo	eas. ndows a. If
well ventilated, DO NOT use this product. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed ar Whenever possible, use outdoors in an open air area. If using indoors open all wir and doors and maintain a cross ventilation of moving fresh air across the work are strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering STOP ventilation is inadequate. Leave area immediately and mo	eas. ndows a. If
accumulate and concentrate, such as basements, bathrooms or small enclosed ar Whenever possible, use outdoors in an open air area. If using indoors open all wir and doors and maintain a cross ventilation of moving fresh air across the work are strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering STOP ventilation is inadequate. Leave area immediately and mo	ndows a. If
and doors and maintain a cross ventilation of moving fresh air across the work are strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering STOP ventilation is inadequate. Leave area immediately and mo	a. If
and doors and maintain a cross ventilation of moving fresh air across the work are strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering STOP ventilation is inadequate. Leave area immediately and mo	a. If
strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering STOP ventilation is inadequate. Leave area immediately and mo	
	ve to
fresh air.	
Work/Hygienic/Maintenance Wash hands thoroughly after use and before eating, drinking, or smoking.	
Practices:	
Do not eat, drink, or smoke in the work area.	
Facilities storing or handling this material should be equipped with an emergency	
eyewash and safety shower.	
9. PHYSICAL AND CHEMICAL PROPERTIES	
Physical States: [X]Gas []Liquid []Solid	
Appearance and Odor: Opaque viscous, Aromatic Odor	
Odor threshold not determned.	
pH: N.D.	
Melting Point: No data N.D.	
Boiling Point: > 99.90 F	
Flash Pt: 61.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)	
Evaporation Rate: < 1 (BuAC=1)	
Flammability (solid, gas): No data available.	
Explosive Limits: LEL: N.D. UEL: N.D.	
Vapor Pressure (vs. Air or N.D.	
mm Hg):	
Vapor Density (vs. Air = 1): N.D.	
Specific Gravity (Water = 1): 1.018 - 1.042	
Density: 8.47 - 8.67 LB/GL	
Solubility in Water: Appreciable	
Solubility Notes:	
Octanol/Water Partition ND Coefficient:	
Percent Volatile: 95.59 % by weight.	
VOC / Volume: 43.4300 % WT	
Autoignition Pt: N.D.	
Decomposition Temperature: No data N.D.	
Viscosity: 1000 - 3000 cSt	
Corrosion Rate: N.D.	
Additional Physical Flash point is for liquid contents	
Information	
ND = Not Determined	
Licensed to W.M. Barr and Company GH	

	10. STABILITY AND REACTIVITY
Stability:	Unstable [ ] Stable [ X ]
Conditions To Avoid - Instability:	Stable
Incompatibility - Materials To Avoid:	Bases, oxygen, sodium, potassium, strong oxidizers, reactive metals, strong acids
Hazardous Decomposition or Byproducts:	Carbon monoxide, carbon dioxide
Possibility of Hazardous Reactions:	Will occur [ ] Will not occur [ X ]
Conditions To Avoid - Hazardous Reactions:	Will not occur.
	11. TOXICOLOGICAL INFORMATION
Toxicological Information:	This product has not been tested as a whole. Refer to section 2 for acute and chronic effects. CAS# 1330-20-7: Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H. Result: Behavioral: Muscle contraction or spasticity. Lungs, Thorax, or Respiration:Other changes. - Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974 Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe. Result: Behavioral: General anesthetic. Behavioral: Somnolence (general depressed activity). Behavioral: Irritability. - "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972
	CAS# 100-41-4: Tumorigenic Effects:, TCLo, Inhalation, Rat, 750.0 ppm. Result: Tumorigenic: Carcinogenic by RTECS criteria. Kidney, Ureter, Bladder: Tumors. Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe. Result: Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants). Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth). Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

				S	upersedes Revis	ion: 03/11/2020
		CAS# 68439-46-3:				
		Acute toxicity, LD50, Oral, Rat, 1378.	MG/KG.			
		Result:				
		Behavioral: Somnolence (general dep	pressed activ	rity).		
		Behavioral: Ataxia. Gastrointestinal:Hypermotility, diarrhe	2			
		- Journal of the American College of		Mary Ann I	iebert Inc N	ew York NY
		Vol/p/yr: 10(4),427, 1991			100 or (, 110., 11	
Chronic Toxicological Effects:		This product has not been tested as a	a whole.			
Carcinogenicity/Other		IARC 2B - Possibly Carcinogenic to H				
nformation:		IARC 3: Not Classifiable as to Carcin				
		ACGIH A3 - Confirmed Animal Carcir	-	nknown Re	levance to Hi	imans ACGIF
		A4 - Not Classifiable as a Human Car	cinogen.			
CAS #	Hazardous Co	mponents (Chemical Name)	NTP	IARC	ACGIH	OSHA
616-38-6	Dimethyl carbor	nate	n.a.	n.a.	n.a.	n.a.
67-68-5	Methyl sulfoxide	e {Dimethyl sulfoxide; DMSO}	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed i	somers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.
68476-86-8	Liquified petrole n-butane}	eum gas, sweetened {propane, isobutane,	n.a.	n.a.	n.a.	n.a.
100-41-4	Ethylbenzene {	n.a.	2B	A3	n.a.	
68439-46-3	Alcohol ethoxyla	n.a.	n.a.	n.a.	n.a.	
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}		Possible	2B	n.a.	n.a.
1095-66-5	Oleic acid, compound with morpholine (1:1)		n.a.	n.a.	n.a.	n.a.
67-56-1	Methanol {Meth	nyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
110-91-8	Morpholine (Die	ethvlene imidoxide}	n.a.	3	A4	n.a.
66455-14-9	Morpholine {Diethylene imidoxide} Alcohols, C12-13, ethoxylated		n.a.	n.a.	n.a.	n.a.
		12. ECOLOGICAL INFO	ORMATIO	ON		
General Ecol	ogical	This product has not been tested as a	a whole.			
nformation:						
		13. DISPOSAL CONSID				
Vaste Dispos	sal Method:	Dispose in accordance with all applica			leral regulatio	ons.
	SPORT (US DO	14. TRANSPORT INFO		JN		
	er Shipping Na					
DOT Haza	•••	2.1 FLAMMABLE G/	AS			
UN/NA Nu		UN1950				
		FLIMMIBLE GIS				
		2				
		•				
icensed to W.M.	. Barr and Company	1				GHS forn

Additional T Information:	ransport The shipper / supplier may a Consumer Commodity, Limit or others, as allowed under 4 Subchapter C to ensure that	ed Quantity, Visc 19CFR Hazmat R	cous Liquid, Does N Regulations. Please	lot Sustain Combustion, consult 49CFR	
	15. REGULATOR			·	
EPA SARA (S	uperfund Amendments and Reauthorization Act of	of 1986) Lists			
<b>CAS #</b> 616-38-6	Hazardous Components (Chemical Name) Dimethyl carbonate	<b>S. 302 (EHS)</b> No	<b>S. 304 RQ</b> No	<b>S. 313 (TRI)</b> No	
67-68-5	Methyl sulfoxide {Dimethyl sulfoxide; DMSO}	No	No	No	
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	No	Yes 100 LB	Yes	
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No	No	No	
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	No	Yes 1000 LB	Yes	
68439-46-3	Alcohol ethoxylate (Alcohols, C9-11, Ethoxylated)	No	No	No	
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	No	Yes 5000 LB	Yes	
1095-66-5	Oleic acid, compound with morpholine (1:1)	No	No	No	
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes 5000 LB	Yes	
110-91-8	Morpholine {Diethylene imidoxide}	No	No	No	
66455-14-9	Alcohols, C12-13, ethoxylated	No	No	No	
CAS #	Hazardous Components (Chemical Name)	Other US EPA o	r State Lists		
616-38-6	Dimethyl carbonate	TSCA: Inventory	,		
67-68-5	Methyl sulfoxide {Dimethyl sulfoxide; DMSO}	TSCA: Inventory			
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory			
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	TSCA: Inventory			
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory CA PROP.65: Yes: Canc.			
68439-46-3 98-82-8	Alcohol ethoxylate (Alcohols, C9-11, Ethoxylated) Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}				
1095-66-5 67-56-1	Oleic acid, compound with morpholine (1:1) Methanol {Methyl alcohol; Carbinol; Wood alcohol}	TSCA: Inventory CAA HAP,ODC: HAP: VHAP TSCA: Inventory CA PROP.65: Yes: RDTox.			
110-91-8 66455-14-9	Morpholine {Diethylene imidoxide} Alcohols, C12-13, ethoxylated	TSCA: Inventory TSCA: Inventory			

Additional Regulatory Information	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.		
	16. OTHER INFORMATION		
Revision Date:	03/19/2020		
Preparer Name:	W.M. Barr EHS Dept (901)775-0100		
Additional Information Abo This Product:	out No data available.		
Company Policy or Disclaimer:	The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.		