



JDI-6EV

6 20 FLUID EVACUATORS

Designed to remove used oil and other fluids from any vehicle when conventional draining methods are not practical. Fluid evacuators remove used oil and other "non-flammable" fluids from almost any vehicle using compressed air and an on-board venturi vacuum system.



- 6- and 20-gallon capacities
- Heavy-duty steel construction
- Powerful venturi vacuum system
- Easy-to-read vacuum gauge
- 7' suction hose
- Six suction probes for most applications
- Three "OE Style" evacuator adapters
- Convenient storage tube for suction probes
- Wheels and casters are oil and chemical resistant for longer life
- Self-evacuating with 10' quick disconnect evacuation hose
- Sight tube for quick indication of fluid level

FLUID HANDLING

| SPECIFICATIONS: | 6EV | 20EV | 20EV-B |
|-------------------------|-------------|--------------|--------------|
| GALLONS | 6-GALLON | 20-GALLON | 20-GALLON |
| SUCTION CAPACITY | 4-GALLONS | 14-GALLONS | 14-GALLONS |
| AIR PRESSURE FOR VACUUM | 110-115 PSI | 110-115 PSI | 110-115 PSI |
| DEPRESSURIZATION TIME | 60-90 SEC. | 120-150 SEC. | 120-150 SEC. |
| SUCTION SPEED | .04-.05 GPM | .04-.05 GPM | .04-.05 GPM |
| MATERIAL | STEEL | STEEL | STEEL |
| WHEEL SIZE - FRONT | N/A | 4" SWIVEL | 4" SWIVEL |
| WHEEL SIZE - REAR | 7" FIXED | 7" FIXED | 7" FIXED |
| WEIGHT | 45 LBS. | 55 LBS. | 65 LBS. |

FLUID



Applications include:

- Traditional automotive repair - Including oil, coolant, transmission fluid, brake fluid, differential oil and power steering fluid.
- Auto Dealers - Essential for European manufactured vehicles that do not include a factory drain plug (Audi/ VW, BMW, Mercedes, Land Rover/ Jaguar).
- Quick Lubes - Avoid stripped drain plugs. Makes it easy to correct overfills.
- Motorcycle/ATV Service - Perfect for oil changes.
- Marine Applications - Boats, Jet Skis and other PWC.
- Farm & Industrial - Tractors, generators, off-road equipment.

JDI-20EV-B

20-Gallon Fluid Evacuator with Transparent Bowl

The JDI-210EV-B is equipped with a 2-gallon transparent bowl which gives the operator the option to check quantity and quality of oil prior to discharging it into the tank below. The bowl is heat-resistant to a maximum of 212° F



Probes & Adapters

Evacuators come with six suction probes and three "OE Style" adapters. See page 33 for part numbers and specifications.

HANDLING
FLUID