



## CALCI-FREE™ TANKLESS WATER HEATER FLUSH

### DESCRIPTION:

---

Calci-Free™ Tankless Water Heater Flush is an efficient chemical cleaner designed for tankless water heater found in commercial and residential application. It contains a unique combination of organic and inorganic cleaners, as well as patented corrosion inhibitors.

### CHARACTERISTICS:

---

- Thorough Cleaning
- Fast Acting
- Easy to Use
- Biodegradable
- Cleans Circulation Coils
- Restores Water Flow & Pressure
- No Strong Odor

### APPLICATIONS:

---

Any type of tankless water heater. Do not use on aluminum.

### PACKAGING:

---

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
68708	1.2 lbs (544.3 g)	12	xx	xx

# CALCI-FREE™

## INSTRUCTIONS

---

**READ MSDS, ALL DIRECTIONS AND WARNINGS ON LABEL BEFORE USING  
WEAR SAFETY GOGGLES AND RUBBER OR PLASTIC GLOVES**

1. Add full contents of package to 2 gallons of water into plastic bucket.
2. Mix the powder in water until completely dissolved.
3. Shut off water supply to the water heater from the inlet and outlet valve and relieve pressure.
4. Disconnect the water heater at the energy source. Disconnect inlet and outlet water valves.
5. Use a recirculation pump to feed the cleaning solution into the water heater. Recirculate for 20 minutes or until the unit is clean. Clean the heat exchanger only.

**Follow your service manual for specific cleaning instructions.**

6. After cleaning, dispose used cleaning chemicals in accordance with local regulations.
7. With the energy source turned off, flush the water heater thoroughly for 10 minutes with cold water.
8. Reconnect the water heater to the energy source.

For additional technical information, call Toll Free 1-800-231-3345

## PRECAUTIONS

---

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

### **DANGER!**

**CAUSES SEVERE IRRITATION AND BURNS TO EVERY AREA OF CONTACT  
MAY BE FATAL IF SWALLOWED, HARMFUL IF INHALED  
KEEP OUT OF REACH OF CHILDREN  
READ BACK PANEL CAREFULLY.**

**CONTAINS: Inorganic Acid.** Do not get in eyes, on skin, or on clothing. Wear goggles or face shield, protective clothing and rubber gloves. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. **FIRST AID:** In case of exposure, contact physician immediately. **Eyes** - Hold eyes open and rinse gently with water for 15 minutes. **Skin** - Remove contaminated clothing immediately. Rinse skin with plenty of water for 15 minutes. **Ingestion** - DO NOT INDUCE VOMITING. Only if conscious, give large amounts of water. **Inhalation** - Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. **Use With Adequate Ventilation. KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Material Safety Data Sheet.

## SPECIFICATIONS

---

Color	Solid Mixture
Shelf Life	2 years minimum, subject to inspection.

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



Certified to NSF/ANSI 61

## LIMITED WARRANTY

---

RectorSeal makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal shall not be liable for incidental or consequential damages.

MANUFACTURED BY

RectorSeal • 2601 Spenwick Drive • Houston, Texas 77055-1035, USA  
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051

www.rectorseal.com