Issuing Date 31-Dec-2015

Revision Date 31-Dec-2015

Revision Number 5

SAFETY DATA SHEET

4

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name	PUR Replacement Filter Faucet RF9999		
Other means of identification			
Synonyms	None		
Recommended use of the chemical and restrictions on use			
Recommended Use	Filter		
Uses advised against	No information available		
Details of the supplier of the safety data sheet			
Supplier Name	Kaz USA, Inc.		
Supplier Address	One Vapor Trail Hudson NY 12534 US		
Supplier Phone Number	Phone:(479) 271-8078 Contact Phone(479) 271-8078		
Supplier Email	kbender@kaz.com		
Emergency telephone number			

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Serious eye damage/eye irritation	Category 2



GHS Label elements, including precautionary statements

	Emer	rgency Ov	erview		
Signal word	Warning				
Hazard Statements Harmful if inhaled Causes serious eye irritation					
Appearance Solid	Physi	ical state	Solid	Odor	None

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Wear eye/face protection Wash hands and face thoroughly after handling

Precautionary Statements - Response

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Storage None

Precautionary Statements - Disposal None

Hazards not otherwise classified (HNOC)

Not applicable

<u>Unknown Toxicity</u> 7.1 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

No information available



Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Supplier Trade Secret	Trade Secret	7 - 13	*
Supplier Trade Secret	Trade Secret	5 - 10	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice	Show this safety data sheet to the doctor in attendance.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. If symptoms persist, call a physician.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.
Ingestion	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
Most important symptoms and effe	cts, both acute and delayed
Most Important Symptoms and Effects	Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.
Indication of any immediate medica	al attention and special treatment needed

Notes to Physician Treat symptomatically.



5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, soda ash, lime or sand. DRY sand, dry chemical, soda ash or lime or withdraw from area and let fire burn. Move containers from fire area if you can do it without risk.

Unsuitable extinguishing media

DO NOT USE WATER OR FOAM.

Specific hazards arising from the chemical

Produce flammable gases on contact with water. May ignite on contact with water or moist air. Some react vigorously or explosively on contact with water. May be ignited by heat, sparks or flames. Some are transported in highly flammable liquid. Runoff may create fire or explosion hazard.

Uniform Fire Code Irritant: Solid

Hazardous Combustion Products Carbon oxides.

Carbon Uxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do it without risk. DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.
Other Information	DO NOT GET WATER on spilled substance or inside containers.
Environmental precautions	
Environmental precautions	Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
Methods and material for containm	ent and cleaning up
Methods for containment	Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Dike for later disposal; do not apply water unless directed to do so. Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry.
Methods for cleaning up	Pick up and transfer to properly labeled containers.



7. HANDLING AND STORAGE

Precautions for safe handling

Handling	In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.
Conditions for safe storage, includ	ing any incompatibilities
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children.
Incompatible Products	None known based on information supplied.
8. EXPOSURE CONTROLS/PERSONAL PROTECTION	

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Supplier Trade Secret	-	TWA: 15 mg/m ³	TWA: 5 mg/m ³ respirable dust
		TWA: 5 mg/m ³	TWA: 10 mg/m ³ total dust
		(vacated) TWA: 15 mg/m ³	
		(vacated) TWA: 5 mg/m ³	
Supplier Trade Secret	TWA: 1 mg/m ³ respirable	-	
	fraction		

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure GuidelinesVacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d
962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures	Showers
	Eyewash stations
	Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	None required for consumer use. If there is a risk of contact:. Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Do not breathe dust.



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

	_		
Physical state	Solid		
Appearance	Solid	Odor	None
Color	No information available	Odor Threshold	No information available
Property	<u>Values</u>	Remarks Method	_
рН	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Insoluble in water	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/w	vaterNo data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		
Other Information			
Softening Point	No data available		
VOC Content (%)	No data available		
Particle Size	No data available		

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Particle Size Distribution

<u>Chemical stability</u> Stable under recommended storage conditions. <u>Possibility of Hazardous Reactions</u> None under normal processing. <u>Hazardous Polymerization</u> Hazardous polymerization does not occur.

Conditions to avoid Excessive heat. Incompatible materials None known based on information supplied. Hazardous Decomposition Products Carbon oxides.



11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information.
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. May cause redness, itching, and pain. May cause temporary eye irritation.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Supplier Trade Secret	= 6450 mg/kg (Rat)	-	-
Supplier Trade Secret	= 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 18.3 mg/L (Rat)1 h

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic Toxicity	No known effect based on information supplied. Carcinogenic potential is unknown.
Target Organ Effects	Eyes. Respiratory system. Central Vascular System (CVS). Skin.
Aspiration Hazard	No information available.



Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 5,819.00 mg/kg ATEmix (inhalation-dust/mist) 4.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to	Daphnia Magna (Water	
			Microorganisms	Flea)	
Supplier Trade Secret	96h EC50: = 18 mg/L	96h LC50: = 1800 mg/L	EC50 3200 - 5600 mg/L 8 h	48h EC50: 1000 - 1800	
	(Desmodesmus subspicatus)	(Brachydanio rerio) 96h	EC50 = 1550 mg/L 16 h	mg/L	
		LC50: 3200 - 5600 mg/L			
		(Oryzias latipes) 96h LC50:			
		1800 - 3200 mg/L (Poecilia			
		reticulata)			

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION



Note:	The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"
DOT	NOT REGULATED
Proper Shipping Name Hazard Class	NON REGULATED N/A
Emergency Response Guide Number	138
TDG	Not regulated
<u>MEX</u>	Not regulated
ICAO	Not regulated
	Not regulated
Proper Shipping Name Hazard Class	NON REGULATED N/A
IMDG/IMO	Not regulated
Proper Shipping Name Hazard Class	NON-REGULATED PER SP 188 N/A
EmS-No.	F-A, S-I
RID	Not regulated
ADR	Not regulated
ADN_	Not regulated
International Inventories	15. REGULATORY INFORMATION

TSCA DSL

Complies All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313 Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372



SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Supplier Trade Secret	Х	Х			

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Supplier Trade Secret		Mexico: TWA 10 mg/m ³
(7-13)		Mexico: STEL 20 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada WHMIS Hazard Class

Not determined

16. OTHER INFORMATION

NFPA HMIS	Health Hazards Health Hazards		bility 0 I cal Hazard 0	Physical and Chemical Hazards Personal Protection X
Prepared By	23 Brit Lathar	ct Stewardship tish American Blvd. n, NY 12110 572-6501		
Issuing Date	31-De	c-2015		



Revision Date Revision Note

31-Dec-2015 No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet



Product Information Sheet

Panasonic Batteries

Panasonic Industrial Company A Division Panasonic Corporation of North America 5201 Tollview Drive, 1F-3 Rolling Meadows, IL 60008 Toll Free: 877-726-2228 Fax: 847-637-4660 Internet: www.panasonic.com/industrial/batteries-oem e-mail: <u>oembatteries@panasonic.com</u> Product: Manganese Dioxide (CR Type) Lithium Batteries Applicable models/sizes: All CR type coin batteries

Revision: January 1, 2020

The batteries referenced herein are exempt articles and are <u>not</u> subject to the OSHA Hazard Communication Standard requirement. This sheet is provided as a service to our customers.

<u>SDS</u>

Safety Data Sheets (SDS) are a sub-requirement of the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200. This Hazard Communication Standard does not apply to various subcategories including anything defined by OSHA as an "article". OSHA has defined "article" as a manufactured item other than a fluid or particle; (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g. minute or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees.

Because all of our batteries are defined as "articles", they are exempt from the requirements of the Hazard Communication Standard; hence a SDS is not required.

Coin Cell Components	Material	Formula	
Positive Electrode	Manganese Dioxide	MnO ₂	1313-13-9
Negative Electrode	Lithium	Li	7439-93-2
Electrolyte	Propylene Carbonate-Solvent	$C_4H_6O_3$	108-32-7
	1,2 Dimethoxyethane-Solvent	$C_4H_{10}O_2$	110-71-4
	Lithium Perchlorate-Salt	LiClO ₄	7791-03-9

The following components are found in a Panasonic Manganese Dioxide (CR) Lithium battery:

DISPOSAL

Lithium batteries are neither specifically listed nor exempted from the Federal Environmental Protection Agency (EPA) hazardous waste regulations as promulgated by the Resource Conservation and Recovery Act (RCRA). The only metal of possible concern in a lithium battery is lithium that is not a listed or characteristic toxic hazardous waste. Waste lithium batteries can be considered a reactive hazardous waste if there is a significant amount of unreacted, or unconsumed lithium remaining in the spent battery. The key to disposing of a lithium battery as a non-hazardous waste is to guarantee that it is fully or mostly discharged. Once it is discharged it can be disposed of as non-hazardous waste. You can dispose of a fully charged or partially discharged lithium battery as a hazardous waste after they are first neutralized through an approved secondary treatment. The need for a secondary treatment prior to disposal is a requirement of the U.S. Land Ban Restrictions of the Hazardous and Solid Waste Amendments of 1984. A secondary treatment center can only receive these batteries as manifested hazardous waste. The waste code for charged lithium

batteries is D003, reactive. In either case, button cell batteries contain so little lithium that they never qualify as a reactive hazardous waste. These batteries are safe for disposal in the normal municipal waste stream. Disposal of large quantities of undischarged lithium batteries should be performed by permitted, professional disposal firms knowledgeable in Federal, State and local hazardous materials and hazardous waste transportation and disposal requirements. As always, households are exempt from the RCRA hazardous waste guidelines.

<u>Notice</u>: The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation. Panasonic Industrial Company makes no warranty expressed or implied. In California, packages that contain CR lithium coin cells and the Owners/Operating Instructions of products that contain CR lithium coin cells must include the following statement: "Perchlorate Material – special handling may apply, See <u>www.dtsc.ca.gov/hazardouswaste/perchlorate/</u>".

TRANSPORTATION

All Panasonic lithium batteries are not subject to the requirements of the Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.

Effective January 1, 2019 all Panasonic lithium batteries can be shipped by air in accordance with International Civil Aviation Organization (ICAO), 2019-2020 edition, Section II or Section 1B or International Air Transport Association (IATA) 61th edition, Section II or Section 1B Packing Instructions (PI) 968 (Batteries), PI 969 (Batteries, packed with equipment) and PI 970 (Batteries, contained in equipment) as appropriate

All Panasonic lithium batteries are regulated by the International Maritime Organization (IMO), 2018, 39th amendment, under Special Provisions 188 and 230.

All Panasonic lithium batteries are regulated by the ADR, 2019-2020 Edition under SP 188 and the TDG under SP 34

All Panasonic lithium cells are tested and comply with the UN Model Regulations, Manual of Test and Criteria, Part III, subsection 38.3.

If you build any of our lithium cells into a battery pack, you must also assure that they are tested in accordance with the UN Model Regulations, Manual of Test and Criteria. Part III, subsection 38.3, 6th Revised Edition, Amendment 1.

If you plan on transporting any untested prototype battery packs contact your Panasonic Sales Representative for regulatory information. Check with your air carrier before shipping. Many air carriers have additional requirements.

First Aid

If you get electrolyte in your eyes, flush with water for 15 minutes without rubbing and immediately contact a physician. If you get electrolyte on your skin wash the area immediately with soap and water. If irritation continues, contact a physician. If a battery is ingested, call the Rocky Mountain Poison and Drug Center at 800-498-8666 for the US and Canada and 303-389-1300 internationally or your local poison center immediately. Lithium coin batteries lodged in the esophagus should be removed immediately. Leakage, chemical burns and perforation can occur within hours of ingestion.

General Recommendations

CAUTION: Risk of fire, explosion and burns. Do not recharge, crush, heat above 212°F (100°C) or incinerate.

Fire Safety

In case of fire, you can use a Class "D" fire extinguisher or other smothering agent such as Lith-X, copper powder or dry sand. If you use water, use enough to smother the fire. Cooling the exterior of the batteries will help prevent rupturing. Fire fighters should use self-contained breathing apparatus. Detailed information on fighting a lithium metal battery fire can be found in Guide 138 (Substances – Water – Reactive) of the US DOT Emergency Response Guide.

Notice: The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation. Panasonic Industrial Company makes no warranty expressed or implied.