		Cleaner Revision: 05/20/2019
		Supersedes Revision: 04/25/2019
1.	PRODUCT AND COMPANY I	DENTIFICATION
Product Name: Company Name:	Klean Strip Brush Cleaner W. M. Barr 2105 Channel Avenue Memphis, TN 38113	Phone Number: (901)775-0100
Web site address: Emergency Contact: Information:	www.wmbarr.com 3E 24 Hour Emergency Contact W.M. Barr Customer Service	(800)451-8346 (800)398-3892
Intended Use:	Clean up of natural and synthetic paint b	prushes.
Product Code:	QKBC121, GKBC120	
	2. HAZARDS IDENTIFI	CATION
	xicity (single exposure), Category 1 xicity (repeated exposure), Category 2 gory 1	
\checkmark \checkmark		
GHS Signal Word:	Danger	
GHS Signal Word: GHS Hazard Phrases:	 Danger Highly flammable liquid and vapor. Harmfull if swallowed, in contact with sk May be fatal if swallowed and enters air Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. Suspected of damaging fertility or the un Causes damage to organs. May cause damage to organs through p 	ways. nborn child.

Do not breathe gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

GHS Response Phrases:

Licensed to W.M. Barr and Company

	•
	Call a POISON CENTER or doctor/physician if you feel unwell.
	IF ON SKIN: Wash with plenty of soap and water.
	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin
	with water/shower.
	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	5
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	IF exposed: Call a POISON CENTER or doctor/physician.
	IF exposed or concerned: Get medical attention/advice.
	Get medical attention/advice if you feel unwell.
	Specific treatment see label.
	Specific measures see label.
	Rinse mouth.
	Do NOT induce vomiting.
	If skin irritation occurs, get medical advice/attention.
	If eye irritation persists, get medical advice/attention.
	Take off contaminated clothing and wash before re-use.
	Wash contaminated clothing before reuse.
	In case of fire, use dry chemical powder to extinguish.
GHS Storage and Disposal	Store in cool/well-ventilated place.
Phrases:	Store locked up.
	Dispose of contents/container according to local, state and federal regulations.
OSHA Regulatory Status:	This material is classified as hazardous under OSHA regulations.
Potential Health Effects (Acute and Chronic):	**See above.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	10.0 -30.0 %
108-88-3	Toluene {Benzene, Methyl-; Toluol}	10.0 -30.0 %
64741-85-1	Raffinates (petroleum), sorption process	10.0 -30.0 %
67-64-1	Acetone {2-Propanone}	10.0 -30.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	5.0 -10.0 %
141-43-5	Ethanol, 2-Amino- {Ethanolamine; Monoethanolamine; beta-Aminoethyl alcohol}	0.1 -1.0 %

Revision: 05/20/2019 Supersedes Revision: 04/25/2019

	4. FIRST AID MEASURES
Emergency and First Aid Procedures:	
In Case of Inhalation:	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.
In Case of Skin Contact:	Immediately flush skin with plenty of water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Wash clothing before reuse.
In Case of Eye Contact:	Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.
In Case of Ingestion:	Do not induce vomiting unless directed to do so by medical personnel.
Signs and Symptoms Of Exposure:	**Refer to section 2.
Note to Physician:	**None known.
	5. FIRE FIGHTING MEASURES
	NFPA Class IB
Flash Pt:	4.00 F Method Used: TAG Closed Cup
Explosive Limits:	LEL: N.D. UEL: N.D.
Autoignition Pt:	N.D.
Suitable Extinguishing Media	a:Use carbon dioxide, dry powder, or alcohol restistant foam.
Unsuitable Extinguishing Media:	Water stream may be ineffective and spread the fire.
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spay to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
Flammable Properties and Hazards:	Vapors may travel to source of ignition and flash back.
Hazardous Combustion Products:	Oxides of carbon.
	6. ACCIDENTAL RELEASE MEASURES
Steps To Be Taken In Case Material Is Released Or	Vapors may cause flash fire or ignite explosively.
Spilled:	Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.
	7. HANDLING AND STORAGE
Precautions To Be Taken in Handling:	Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.
	Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.
Licensed to W.M. Barr and Company	GHS forma

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

Precautions To Be Taken in Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS # Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
67-56-1 Methanol {Methyl alcoh Carbinol; Wood alcohol}	nol; ACGIH TLV	TLV: 200 ppm STEL: 250 ppm	
	OSHA PELs	PEL: 200 ppm	
108-88-3 Toluene {Benzene, Methyl-; Toluol}	ACGIH TLV	TLV: 50 ppm	
	OSHA PELs	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	
67-64-1 Acetone {2-Propanone	} ACGIH TLV	TLV: 500 ppm STEL: 750 ppm	
	OSHA PELs	PEL: 1000 ppm	
111-76-2 Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	ACGIH TLV	TLV: 20 ppm	
	OSHA PELs	PEL: 50 ppm	
141-43-5 Ethanol, 2-Amino- {Ethanolamine; Monoethanolamine beta-Aminoethyl alcohol}	ACGIH TLV e;	TLV: 3 ppm STEL: 6 ppm	
	OSHA PELs	PEL: 3 ppm	
Respiratory Equipment (Specify Type):	ventilation under engine appropriate TLV. For c properly maintained an	vork place and other regular usersUse o eered air control systems designed to pre occasional use, where engineered air cont of properly fitted NIOSH approved respira- loes not provided protection against vapor	vent exceeding trol is not feasible, use tor for organic solvent
Eye Protection:		cal goggles or face shields are recommend rritation, or injury. Contact lenses should s.	
Protective Gloves:	materials such as nitrile on chemicals being use	uch resistance to the chemical ingredients e rubber may provide protection. Glove se ed and conditions of use. Consult your glo Gloves contaminated with product should	election should be based ove supplier for
Other Protective Clothing:		thods can dictate the use of additional propermeable aprons, etc., to minimize expos	•
Engineering Controls (Ventilation etc.):	Use only with adequat where vapors can accu enclosed areas. When open all windows and c	e ventilation to prevent buildup of vapors. Imulate and concentrate such as basement never possible, use outdoors in an open and doors and maintain a cross ventilation of r g odor is noticed or you experience slight	Do not use in areas nts, bathrooms, or small rea. If using indoors, noving fresh air across
Licensed to W.M. Barr and Company			GHS forma

	Supersedes Revision: 04/25/2019
	nausea or eye-watering Stop ventilation is inadequate. Leave area immediately. If
	the work area is not well ventilated, then do not use this product. A dust mask does not
	provide protection against vapors.
Work/Hygienic/Maintenance	Wash hands thoroughly after use and before eating, drinking, or smoking.
Practices:	
	Do not eat, drink, or smoke in the work area.
	Discard any clothing or other protective equipment that cannot be decontaminated.
	Facilities storing or handling this material should be equipped with an emergency
	eyewash and safety shower.
9.	PHYSICAL AND CHEMICAL PROPERTIES
Physical States:	[]Gas [X]Liquid []Solid
Appearance and Odor:	Clear to slightly turbid.
	Odor threshold not determined.
pH:	10.5
Melting Point:	N.D.
Boiling Point:	> 133.00 F
Bolling Point: Flash Pt:	
	4.00 F Method Used: TAG Closed Cup
Evaporation Rate:	N.D.
Flammability (solid, gas):	Flammable; may be ignited by heat, sparks or flames.
Explosive Limits:	LEL: N.D. UEL: N.D.
Vapor Pressure (vs. Air or	N.D.
mm Hg):	
Vapor Density (vs. Air = 1):	N.D.
Specific Gravity (Water = 1):	0.7649 - 0.9032
Density:	N.D.
Solubility in Water:	N.D.
Octanol/Water Partition	N.D.
Coefficient:	
Percent Volatile:	100.0 % by weight.
VOC / Volume:	70.0000 % WT
Autoignition Pt:	N.D.
Decomposition Temperature	: N.D.
Viscosity:	N.D.
	10. STABILITY AND REACTIVITY
Stability:	Unstable [] Stable [X]
Conditions To Avoid -	**None known.
Instability:	
-	Incompatible with strong oxidizing agents, strong caustics, acids, alkali, amines, reducin
Avoid:	agents, aldehydes, ammonia, nitrogen peroxides and reactive metals.
Hazardous Decomposition o	
Byproducts:	
Possibility of Hazardous	Will occur [] Will not occur [X]
Reactions:	
Conditions To Avoid -	**None known.
Hazardous Reactions:	
Licensed to W.M. Barr and Company	GHS forma

	11. TOXICOLOGICAL INFORMATION
Toxicological Information:	This product has not been tested as a whole. Refer to section 2 for acute and chronic effects. CAS# 108-88-3: Reproductive Effects:, TCLo, Inhalation, Rat, 800.0 MG/M3, 6 H, female 14-20 day(s) after conception. Result: Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). Effects on Newborn: Behavioral. - Brazilian Journal of Medical and Biological Research., Vol/p/yr: 23,533, 1990 Standard Draize Test, Eyes, Species: Rabbit, 2.000 MG, 24 H, Severe.
	Result: Effects on Embryo or Fetus: Other effects to embryo. Specific Developmental Abnormalities: Eye, ear. - Prehled Prumyslove Toxikologie, Marhold, J., Organicke Latky, Prague Czechoslovakia, Vol/p/yr: -,29, 1986
	CAS# 67-64-1: Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe. Result: Behavioral: Change in motor activity (specific assay). Behavioral: Alteration of classical conditioning. - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946
	CAS# 111-76-2: Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H. Result: Behavioral: Ataxia. Nutritional and Gross Metabolic:Weight loss or decreased weight gain. - Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983
	Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG. Result: Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord). Effects on Embryo or Fetus: Other effects to embryo. Specific Developmental Abnormalities: Musculoskeletal system. - Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,
	Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg. Result: Lungs, Thorax, or Respiration:Changes in pulmonary vascular resistance.
	Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe. Result: Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects.

		Effects on Newborn: Drug de	pendency	/.			
		- American Journal of Ophtha	lmology.,	Ophthalm	nic Pub. Co.,	435 N. Michi	gan Ave.,
		Suite 1415, Chicago, IL 6061	1, Vol/p/y	r: 29,1363	, 1946		
		CAS# 141-43-5:					
		Acute toxicity, LD50, Oral, Ra	it, 1720. I	MG/KG.			
		Result:					
		Brain and Coverings: Other d	•	•			
		Autonomic Nervous System:	•	<i>,</i> .	ympathomin	netic.	
		Autonomic Nervous System:					
		- Toxicology and Applied Pha 55802, Vol/p/yr: 42,417, 1977	-	ly, Acaden	nic Press, ind	C., 1 E. FIRST 3	St., Duiuth, Min
		Open irritation test., Skin, Spe Result:	ecies: Ra	bbit, 505.0	MG, Modera	ate.	
		Peripheral Nerve and Sensati	ion: Sens	orv chang	e involvina s	egmental dis	tribution
		Behavioral: Alteration of class			e involving 5	oginental alo	
		- Union Carbide Data Sheet,		-	., 39 Old Ric	lgebury Rd.,	Danbury, CT
		06817, Vol/p/yr: 1/13, 1972					
		Standard Draize Test, Eyes, S Result:	Species:	Rabbit, 25	0.0 UG, Sev	ere.	
		Peripheral Nerve and Sensati	ion: Sens	ory chang	e involving s	egmental dis	tribution.
		Behavioral: Change in motor	•	•	say).		
		Behavioral: Alteration of class		-			
		- American Journal of Ophtha	•••	•		435 N. Michi	gan Ave.,
		Suite 1415, Chicago, IL 6061	i, voi/p/y	1. 29,1303	, 1940		
Carcinogenic	itv/Other	IARC 3: Not Classifiable as to	o Carcino	aenicity in	Humans.		
Information:		ACGIH A3 - Confirmed Anima ACGIH A4 - Not classifiable a	al Carcino	ogen with l	Jnknown Re	levance to H	umans
CAS #	Hazardous Com	ponents (Chemical Name)		NTP	IARC	ACGIH	OSHA
67-56-1	Methanol {Methy	/l alcohol; Carbinol; Wood alcoho	l}	n.a.	n.a.	n.a.	n.a.
108-88-3	Toluene {Benzer	ne, Methyl-; Toluol}		n.a.	3	A4	n.a.
64741-85-1	Raffinates (petrol	leum), sorption process		n.a.	n.a.	n.a.	n.a.
67-64-1	Acetone {2-Prop	anone}		n.a.	n.a.	A4	n.a.
111-76-2	Ethanol, 2-Butoxy ether)}	y- {Ethylene glycol n-butyl ether,	(a glycol	n.a.	3	A3	n.a.
141-43-5	Ethanol, 2-Amino beta-Aminoethyl	 {Ethanolamine; Monoethanolam alcohol} 	nine;	n.a.	n.a.	n.a.	n.a.

Revision: 05/20/2019 Supersedes Revision: 04/25/2019

	12. ECOLOGICAI		TION	
General Ecol Information:	ogical This product has not been te	sted as a whole.		
	13. DISPOSAL CO	DNSIDERAT	IONS	
Waste Dispo	sal Method: Dispose in accordance with a	applicable local, s	tate, and federal re	egulations.
	14. TRANSPORT		ΓΙΟΝ	
LAND TRAN	SPORT (US DOT):			
	ber Shipping Name: Paint Related Material			
UN/NA N	umber: UN1263	Packing G	roup:	II
Additional T Information:	ransport The shipper / supplier may a Consumer Commodity, Limit or others, as allowed under 4 Subchapter C to ensure that	ed Quantity, Visc 19CFR Hazmat R	ous Liquid, Does Negulations. Please	Not Sustain Combustion e consult 49CFR
	15. REGULATOR	Y INFORMA	TION	
EPA SARA (S	uperfund Amendments and Reauthorization Act o	of 1986) Lists		
CAS # 67-56-1	Hazardous Components (Chemical Name) Methanol {Methyl alcohol; Carbinol; Wood alcohol}	S. 302 (EHS) No	S. 304 RQ Yes 5000 LB	S. 313 (TRI) Yes
108-88-3	Toluene {Benzene, Methyl-; Toluol}	No	Yes 1000 LB	Yes
64741-85-1	Raffinates (petroleum), sorption process	No	No	No
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	No	No	Yes-Cat. N230
141-43-5	Ethanol, 2-Amino- {Ethanolamine; Monoethanolamine; beta-Aminoethyl alcohol}	No	No	No
				
CAS#	Hazardous Components (Chemical Name)	Other US EPA or	r State Lists	
67-56-1	Hazardous Components (Chemical Name) Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: TSCA: Inventory	HAP: VHAP	
	Methanol {Methyl alcohol; Carbinol; Wood	CAA HAP,ODC:	HAP: VHAP es: RDTox. HAP: VHAP , 8A CAIR	
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: TSCA: Inventory CA PROP.65: Ye CAA HAP,ODC: CWA NPDES TSCA: Inventory	HAP: VHAP es: RDTox. HAP: VHAP , 8A CAIR es: RDTox(F)	
67-56-1 108-88-3	Methanol {Methyl alcohol; Carbinol; Wood alcohol} Toluene {Benzene, Methyl-; Toluol}	CAA HAP,ODC: TSCA: Inventory CA PROP.65: Ye CAA HAP,ODC: CWA NPDES TSCA: Inventory CA PROP.65: Ye	HAP: VHAP es: RDTox. HAP: VHAP , 8A CAIR es: RDTox(F)	
67-56-1 108-88-3 64741-85-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol} Toluene {Benzene, Methyl-; Toluol} Raffinates (petroleum), sorption process Acetone {2-Propanone} Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether,	CAA HAP,ODC: TSCA: Inventory CA PROP.65: Ye CAA HAP,ODC: CWA NPDES TSCA: Inventory CA PROP.65: Ye TSCA: Inventory TSCA: Inventory CAA HAP,ODC:	HAP: VHAP es: RDTox. HAP: VHAP , 8A CAIR es: RDTox(F) Yes - Cat.	
108-88-3 64741-85-1 67-64-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol} Toluene {Benzene, Methyl-; Toluol} Raffinates (petroleum), sorption process Acetone {2-Propanone}	CAA HAP,ODC: TSCA: Inventory CA PROP.65: Ye CAA HAP,ODC: CWA NPDES TSCA: Inventory CA PROP.65: Ye TSCA: Inventory TSCA: Inventory	HAP: VHAP es: RDTox. HAP: VHAP , 8A CAIR es: RDTox(F) Yes - Cat.	

Additional Regulatory Information	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.
	16. OTHER INFORMATION
Revision Date:	05/20/2019
Preparer Name:	W.M. Barr EHS Dept (901)775-0100
Additional Information Ab This Product:	out N.D.: Not determined.
Company Policy or Disclaimer:	The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.