LFADZM

Instruction Sheet

■INFLATABLE BOUNCER

KEEP THE INSTALLATION INSTRUCTION FOR FURTHER REFERENCE
PLEASE READ ALL OF THE SAFETY RULES BEFORE SETTING UP
We BELIEVE IN SAFETY FIRST.PLEASE FOLLOW ALL OF THERULES FOR YOUR CHILDREN'S SAFETY

WARNING! ELECTRICALLY OPERATED PRODUCT

ADULT SUPERVISION REQUIRED.OPERATING BLOWER (AIR PUMP) NOT RECOMMENDED FOR CHILDREN UNDER 16 YEARS OF AGE. AS WITH ALL ELECTRIC PRODUCTS, PRECAUTIONS SHOULD B E OBSERVED DURING HANDLING AND USE TO PREVENT ELECTRIC SHOCK.

CAUTION:

NOT SUITABLE FOR ADULTS
NOT SUITABLE FOR HIRING ORCOMMERCIAL USE
ADULT SET-UP REQUIRED
ADULT SUPERVISION REQUIRED
WAR NING!
ONLY FOR DOMESTIC USE.OUTDOOR USE
TO BE WSED ON SOFT GROUND ONLY



WARNING! Not suitable for children under 3 years Small parts may be swallowed.

SET-UP


- Check the ground where the product will be set up for any sharp objects or debris. Do not install the product over concrete or any hard surface.
- Place the product on a soft level surface at least 2 meters from any structure or obstruction such as a fence, garage, and house, overhanging branches, laundry lines or electrical wires.
- Ensure the play area is free from hazards such as furniture, walls, sharp objects, other hard surfaces, etc.
- Set up the product away from water and any potential fire hazards.
- Keep the blower (air pump) and power cord away from areas of water and moisture. If water contacts the blower(air pump), unplug the blower(air pump) power cord. Do not operate until the blower is completely dry.
- Remove the product from the carry bag. If any, ensure the slide cover coming with the product streches well from top to end. Be sure to place the product as close to the power source as possible.
- Streth the inflation tube and attach it to the end of the blower(air pump). Ensure the inflation tube is securely attached and in good condition. The inflation tube should be straight and untwisted. Reposition the blower(air pump)if necessary.
- If the product comes with water bags, please follow the undermentioned instruction, otherwise, overleap this point. Spread out the product, place and fasten the empty water bags at the two sides of the product. Open the stopple and fill water in the water bags until 80% full(about 22kg), push and close the stopple. Make sure water bags are firmly attached on the product and no water leakage before the product is fully infkated, and never allow children to play on the slide without installing water bags. (refer to picture A)
- Push ground stakes through blower base holes. You may need to use a hammer for proper placement.
- Make sure the blower(air pump)power switch is in the OFF position. Ensure the power connections are safely sited and tripping hazard is minimized.
- The blower(air pump)should be srcurely sited and affixed to the ground before use.Plug the blower(air pump)into an approved ground outlet.
- Ensure the blower(air pump)is free from debris and securely sited to avoid tripping.
- Turn the blower (air pump)power switch to ON.The continual air-flow blower(air pump)must be left ON at all time while the product is being used.(refer to picture B)
- The product should be fully inflated.
- Ground support stakes are used for lawn ground surfaces. Hook and fit each provided ground stake through
 each loop in the bouncer. To prevent overturn or lift during playing, push stakes firmly into the soil. Make
 sure the hooked end of the stake is over the loop at all time during use. The stakes should be placed level
 with or under the ground in order to reduce trippinghazards. (refer to picture C)
- Please check the age recommendation and user weights(printed on the product). You must not
 exceed the total weight for the product.
- Put the included play accessories if any for playing into the product.(refer to picture D,E)
- If the product comes with support cushions at the sides,do not stand or sit on the cushions.

 Hint: Air leak from the seams is necessary because the product is inflated by constant air flow and this leakage is required to stop the product becoming over-inflated.


Hint: It is drawn user's attention to the orientation of inflatable equipment installation in relation to the sun. The sliding surface of the proudct shall not face to the sun as sun shine can glare the children's eyes when they are sliding down along the slide.











TAKE DOWN

- Make sure all children exit the product.
- Makes sure the product is free from foreign objects.
- If the product comes with water bags, please follow the undermentioned instruction, otherwise, overleap this point. Detach the water bags from the product. Remove the product and blower before opening the stopple for draining.Empty water in the water bags and dry them in cool place for next time's use.
- Turn the blower(air pump) power switch to OFF.
- Unplug the blower(air pump) power cord.
- Loosen the Velcro and detach the inflation tube from the blower. The product should deflate on its own within 5 minutes.Make sure the product is entirely deflated,(refer to picture F)
- Remove ground support stakes.
- Fold the product in half from both ends, and then fold it in half 2 more times from both sides, vertically to the first fold. (refer to picture G,H,I)
- Roll it up tightly from the end opposite the inflationtube. (refer to picture J.K)
- Slip the carry bag over the folded product and stakes (plastic balls or water bags). Zip the bag (refer to picture L)













MAINTENANCE

- ► Checks and maintenance of the main parts of the toys should be carried out of regular intervals, if these checks are not carried out the toys chould overturn or otherwise become a hazard. Whenever practical, the instuctions shall also be affixed to the toy.
- The seasonal inspection and maintenance should be conducted for any damage or leakage of product.
- ► The product can be wiped clean with a mild detergent. Keep water away from the blower(air pump) at all times.
- ▶ Do not store the product when wet. Store the product and the blower indoors in dry conditions when not in use.

REPAIR

In case of any breakage of product, please patch up through hand sewing. Each type of product is provided with a repair kit which includes six pieces of cloth(in three colors; each color has two pieces) and three 20-meter long threads of different colors. Sewing needles are not provided and you should purchase by yourself (3# sewing needle is suggested).

- Turn off air blower and deflate the product.
- Thread a needle with a spare thread and tie a knot at its end.
- Close up the broken cloth and sew along the gap. Tie a knot after sewing to avoid loose thread. In case of cloth breakage(as shown in picture M). please cover thebreakage with a piece of patching cloth of proper size. Then sew up thepatching cloth along its sides. While repairing, you should take notice that the sewing should only occur on the surface layer of the original cloth rather than reaching its underlayer.
- * In case of breakage in the seam position (as shown in picture N), the sewing should only occur between the two split cloth rather than reaching the underlayer or any other cloth.
- * In case of large-size breakage or internal structural damage, please change product or have professionals do the repairing. Air leakage is normal in the repaired position and air pressure of the repaired product maybe lower than the original. But it will not affect the normal use of the product.
- Patching in one position for more than twice is not suggested.
- Needles should be taken good care of and not be left on the product after sewing.
- It is suggested that persons with sewing technique should do the repairing work.





MADE IN CHINA 4