6200 Series Fiberglass Single Sided Step Ladders



The Werner 6200 Series Step Ladders are design for professional contractors and industrial users. With a duty rating of 300 pounds, this series features a HolsterTop with the Lock-In System to secure tools from falling while keeping them right at hand. These ladders offer a full set of rear horizontals and heavy duty internal spreaders. All steps are knee braced and the foot pads are riveted to the EDGE® structure. The EDGE bracing system helps protect the rail from damage. Each TRACTION-TRED® step is slip resistant and double riveted. Fiberglass rails are non-conductive for working near electricity.

Features

- Back-up plates to reinforce top connectors
- Designed for one person jobs
- Every rivet backed up by metal plate or washer to protect fiberglass
- Full set of rear horizontals
- Internal Spreaders
- Molded braces
- Shoulder bolt and nut on top hinge
- Slip-resistant Traction-Tred steps all knee braced

Dimensions

Top Dimension	Front Rails	Front Flange	Rear Rails	Rear Flange	Steps
	Dimension	Dimension	Dimension	Dimension	Dimension
5-5/8 in x 12-3/8 in — 5-3/4 in x 13 in	3-1/8 in	1-3/16 in — 1-4/16 in	1-3/8 in — 1-7/8 in	1-3/16 in — 2-1/16 in	3 in – 4.5 in

Specifications

Model No.	Size	Style	Reach Height	Max. Standing Height	Approx. Width	Approx. Spread
6202	2 ft	Step Stools and Step Stands	8 ft	11 in	17-1/4 in	19-1/2 in
6203	3 ft	Single-Sided	7 ft	1 ft 11 in	18-1/8 in	23-1/8 in
6204	4 ft	Single-Sided	8 ft	1 ft 11 in	19-7/8 in	29 in
6205	5 ft	Single-Sided	9 ft	2 ft 10 in	21-5/8 in	35-1/8 in
6206	6 ft	Single-Sided	10 ft	3 ft 10 in	23-3/8 in	41-1/4 in
6206S	6 ft	Single-Sided	10 ft	3 ft 10 in	23-3/8 in	41-1/4 in
6207	7 ft	Single-Sided	11 ft	4 ft 9 in	25-1/8 in	47-1/2 in
6208	8 ft	Single-Sided	12 ft	5 ft 9 in	26-7/8 in	53-5/8 in
6210	10 ft	Single-Sided	14 ft	7 ft 8 in	30-3/8 in	65-7/8 in
6212	12 ft	Single-Sided	16 ft	9 ft 7 in	33-7/8 in	78-1/4 in

Dimensions

Feature	Size		
Top Dimension	5-3/4 in x 13 in		
Front Rails Dimension	3-1/8 in		
Front Flange Dimension	1-3/16 in		
Rear Rails Dimension	1-3/8 in		
Rear Flange Dimension	1-3/16 in		
Steps Dimension	4 in		

Specifications

Feature	Size / Details
Size	4 ft
Style	Single-Sided
Reach Height	8 ft
Max. Standing Height	1 ft 11 in
Load Capacity	300 lbs
Туре	Type IA Duty Rating
Material	Fiberglass
Approx. Width	19-7/8 in
Certifications	ANSI A14.5 (2007); OSHA
Approx. Spread	29 in
Description of Top Features	Paint tray slot, can hook, Lock in accessory sockets, 2 tool holes, drill hole, p int, quart & gallon paint can, 2 parts trays, tape measure slot
Edge Bracing	Heavy
With Pail Shelf	No
Spreader Material	Steel
Approx. Overall Ladder Length (Closed)	4 ft
Approx. Shipping Weight Lbs.	16
Approx. Cu. Ft. Per Unit	3
Performance Rating	***