

VINYL MOLDING




T-Molding (T) is 72" long and transitions different types of flooring of the <u>same</u> <u>height</u>. For example, vinyl to vinyl.




Vinyl, Tiles or Carpet


Multipurpose Reducer (MPR) is 72" long and transitions flooring of <u>different</u> <u>heights</u>. For example, from carpet to vinyl.






Carpet Reducer/Baby Threshold is 72" long and transitions flooring of different heights. For example, from carpet to vinyl. Works with sliding glass doors and fireplaces.





Overlap Stairnose is 94" long. Existing tread bullnose must be cut off.





Snap Trak (Packed with each T, MPR and SN)

- Position track 3/16" away from vinyl floor
- Screw track to subfloor
- Snap molding onto track
- Track is adjustable from 3.0mm to 5.5mm thick vinyl flooring.



Base & Quarter Round is 94" and finishes the perimeter of the floor. Please take notice the Quarter Round should be affixed to the vertical surface and not affixed to the flooring itself.

VINYL MOLDING

100% WATERPROOF! No buckling or bowing from water spills or moisture issues.

Types: 94" Stairnosing, 94" Quarter Round, 72" T-Molding and 72" Multi-purpose Reducers, 72" End Cap/Baby Threshold are available.

Simple SnapTrack Installation: Same concept as Laminate flooring moldings used with Stairnosing, T-Molding, Multipurpose Reducer and End Cap/Baby Threshold.

Adjustable: Stairnosing, Multipurpose Reducer and T-Molding utilize a metal track which allows one sku to work with thicknesses of vinyl from 3.0mm – 5.5mm.

Coordinating: While we call this program "Coordinating", the moldings are designed to match the Vinyl Flooring. The same décor vinyl and wear layer that is used for the flooring is used for the molding.

Warranty: A commercial wearlayer is used for all of the profiles. Warranty will mirror the same as the floors.