

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : Tough Job Remover - Dried Latex Paint, Overspray, Caulk & Adhesive Remover  
 Product code : 771

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Sunnyside Corp  
 225 Carpenter Ave  
 Wheeling, IL 60090 - USA  
 T 800-323-8611 - F 847-541-9043  
[orders@sunnysidecorp.com](mailto:orders@sunnysidecorp.com) - [www.sunnysidecorp.com](http://www.sunnysidecorp.com)

#### 1.4. Emergency telephone number

Country	Organization/Company	Address	Emergency number	Comment
United States	Chemtrec		1-800-424-9300	

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable liquids Category 2  
 Serious eye damage/eye irritation Category 2

Highly flammable liquid and vapor  
 Causes serious eye irritation

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Highly flammable liquid and vapor  
 Causes serious eye irritation

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/Bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/... equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wash hands, forearms and face thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 In case of fire: Use media other than water to extinguish  
 Store in a well-ventilated place. Keep cool  
 Dispose of contents/container to ...

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# Tough Job Remover - Dried Latex Paint, Overspray, Caulk & Adhesive Remover

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
acetone	(CAS-No.) 67-64-1	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 Aquatic Acute 3, H402
benzyl alcohol	(CAS-No.) 100-51-6	< 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapor.
- Reactivity : Highly flammable liquid and vapor.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# Tough Job Remover - Dried Latex Paint, Overspray, Caulk & Adhesive Remover

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

acetone (67-64-1)		
ACGIH	Local name	Acetone
ACGIH	ACGIH TWA (ppm)	500 ppm (Acetone; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	750 ppm (Acetone; USA; Short time value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
benzyl alcohol (100-51-6)		
Not applicable		

#### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

##### Hand protection:

Protective gloves

##### Eye protection:

Safety glasses

##### Skin and body protection:

Wear suitable protective clothing

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : Mixture contains one or more component(s) which have the following colour(s):  
Colourless

# Tough Job Remover - Dried Latex Paint, Overspray, Caulk & Adhesive Remover

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour(s): Aromatic odour Sweet odour Fruity odour Mild odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; >7426 mg/kg bodyweight; Rabbit; Weight of evidence)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
ATE US (oral)	5800 mg/kg body weight

# Tough Job Remover - Dried Latex Paint, Overspray, Caulk & Adhesive Remover

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>acetone (67-64-1)</b>	
ATE US (dermal)	20000 mg/kg body weight
ATE US (gases)	30000 ppmV/4h
ATE US (vapors)	71 mg/l/4h
ATE US (dust, mist)	71 mg/l/4h

<b>benzyl alcohol (100-51-6)</b>	
LD50 oral rat	1620 mg/kg bw/day (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Inconclusive, insufficient data)
ATE US (oral)	500 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after eye contact	: Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

<b>acetone (67-64-1)</b>	
LC50 fish 2	5540 mg/l (LC50; EU Method C.1; 96 h; Salmo gairdneri; Static system; Fresh water; Experimental value)
EC50 Daphnia 2	12600 mg/l (LC50; Other; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)

<b>benzyl alcohol (100-51-6)</b>	
LC50 fish 1	460 mg/l (LC50; EPA OPP 72-1; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)

### 12.2. Persistence and degradability

<b>acetone (67-64-1)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.872 (20 days; Literature study)

<b>benzyl alcohol (100-51-6)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.6 g O <sub>2</sub> /g substance

# Tough Job Remover - Dried Latex Paint, Overspray, Caulk & Adhesive Remover

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>benzyl alcohol (100-51-6)</b>	
Chemical oxygen demand (COD)	2.4 g O <sub>2</sub> /g substance
ThOD	2.5 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

<b>acetone (67-64-1)</b>	
BCF fish 1	0.69 (BCF)
BCF other aquatic organisms 1	3 (BCF; BCFWIN)
Log Pow	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.

<b>benzyl alcohol (100-51-6)</b>	
Log Pow	1-1.1, Experimental value; Other; 20 °C
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

<b>acetone (67-64-1)</b>	
Surface tension	0.0237 N/m

<b>benzyl alcohol (100-51-6)</b>	
Surface tension	0.04 N/m (20 °C)

### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.  
GWPmix comment : No known effects from this product.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1090 Acetone (Solution), 3, II  
UN-No.(DOT) : UN1090  
Proper Shipping Name (DOT) : Acetone  
Solution  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Packing group (DOT) : II - Medium Danger  
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202  
DOT Packaging Bulk (49 CFR 173.xxx) : 242

# Tough Job Remover - Dried Latex Paint, Overspray, Caulk & Adhesive Remover

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Emergency Response Guide (ERG) Number	: 127
Other information	: Limited Quantity Exemption - 1 L (.3 gal) or less.

### TDG

Not applicable

### Transport by sea

Transport document description (IMDG)	: UN 1090 ACETONE, 3, II (-20°C c.c.)
UN-No. (IMDG)	: 1090
Proper Shipping Name (IMDG)	: ACETONE
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 1 L

### Air transport

Transport document description (IATA)	: UN 1090 Acetone, 3, II
UN-No. (IATA)	: 1090
Proper Shipping Name (IATA)	: Acetone
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ	5000 lb
-----------	---------

#### benzyl alcohol (100-51-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

#### benzyl alcohol (100-51-6)

Listed on the Canadian DSL (Domestic Substances List)

# Tough Job Remover - Dried Latex Paint, Overspray, Caulk & Adhesive Remover

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### EU-Regulations

No additional information available

### National regulations

No additional information available

### 15.3. US State regulations

Tough Job Remover - Dried Latex Paint, Overspray, Caulk & Adhesive Remover	
U.S. - California - Proposition 65 - Carcinogens List	Yes
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

### acetone (67-64-1)

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances  
U.S. - Pennsylvania - RTK (Right to Know) List

### benzyl alcohol (100-51-6)

U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H402	Harmful to aquatic life

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*