



## Technical Data Sheet

Ryobi Lithium-Ion Battery Pack

Battery Voltage: 40V

Battery Capacity: 4Ah / 144Wh

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Lithium-Ion Battery — Rechargeable

**Model Number:** OP40404

**Issue Date:** August 2020

Techtronic Industries Power Equipment  
P.O. Box 1288  
Anderson, SC 29622

**Company Phone Number:** 1-800-860-4050

**Emergency Contact Number:**  
**Chemtrec (United States only):** 1-800-424-9300  
**(International):** +1-703-741-5970

### SECTION 2: HAZARDS IDENTIFICATION

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

#### ▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.

### SECTION 3: COMPOSITION/INFORMATION OF INGREDIENTS

Refer to battery cell SDS for more information.

## SECTION 4: FIRST AID MEASURES

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

### ▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.
- No exposure during routine handling of product. Risk of exposure occurs only if the battery is mechanically or electrically abused.
- No effect under routine handling and use to eyes, skin, or if inhaled. Ingestion is not likely, given the physical size and state of the cell. If swallowed, seek medical attention immediately.
- If exposure to internal materials within cell due to damaged outer casing, the following actions are recommended:

#### EYE CONTACT:

Flush with water for 10 minutes without rubbing and immediately seek medical attention.

#### SKIN CONTACT:

Wash area immediately with soap and water. If irritation continues, seek medical attention.

#### INHALATION:

Leave area immediately, move to fresh air, and seek medical attention.

#### INGESTION:

If swallowed, contact POISON CONTROL CENTER immediately.

## SECTION 5: FIRE FIGHTING MEASURES

Refer to battery cell SDS for more information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS:

- Use standard industrial clothing in normal use.
- If handling large containers of cells, wear steel-toed footwear.

### ENVIRONMENTAL PRECAUTIONS:

No special precautions necessary.

### METHODS FOR CONTAINMENT:

- Transport container outdoors.
- Always consult and obey all international, federal, and local environmental laws.

### METHODS FOR CLEANUP:

No data available

### OTHER INFORMATION:

No data available

## SECTION 7: HANDLING AND STORAGE

### HANDLING:

- Use only approved charging equipment.
- Do not disassemble battery or battery pack.
- Do not puncture, crush, or dispose of in fire.

### STORAGE:

To obtain the longest possible battery life, we suggest the following:

- Remove the battery pack from the charger once it is fully charged and ready for use.

For battery pack storage longer than 30 days:

- Store the battery pack where the temperature is below 80°F and away from moisture.
- Store battery packs in a 30%-50% charged condition.
- Every six months of storage, charge the pack as normal.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Refer to battery cell SDS for more information.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Battery pack consists of battery cells assembled in resin enclosure and is a solid odorless product that will burn if incinerated.

## SECTION 10: STABILITY AND REACTIVITY

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

### ▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.

## SECTION 11: TOXICOLOGY INFORMATION

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

### ▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION:

None in routine handling of product.

### TOXICITY:

No data available

### PERSISTENCE AND DEGRADABILITY (BIOPERSISTENCY & BIODEGRADABILITY):

None in routine handling of product.

### POTENTIAL OF BIOACCUMULATION:

None in routine handling of product.

### MOBILITY IN SOIL:

None in routine handling of product.

### OTHER ADVERSE EFFECTS:

No data available

### DISPOSAL:

Follow guidelines in Section 13.

## SECTION 13: DISPOSAL CONSIDERATIONS

This product contains Lithium-ion batteries. Local, state or federal laws may prohibit disposal of batteries in ordinary trash. Consult your local waste authority for information regarding available recycling and/or disposal options.

### DISPOSAL:

- Dispose in accordance with appropriate regulations.
- Always consult and obey all international, federal, provincial/state, and local hazardous waste disposal laws. Some jurisdictions require recycling of this spent product. Battery recycling is encouraged.
- Lithium-ion batteries are safe for disposal in the normal municipal waste stream since they are not defined by the federal government as hazardous waste. However, Lithium-ion batteries are recyclable.
- To preserve natural resources, please recycle or dispose of batteries properly.

### ▲ WARNING:

- Upon removal, cover the battery pack's terminals with heavy-duty adhesive tape.
- Do not attempt to destroy or disassemble battery pack or remove any of its components.
- Batteries must be recycled or disposed of properly.
- Also, never touch both terminals with metal objects and/or body parts as short circuit may result.
- Keep away from children. Failure to comply with these warnings could result in fire and/or serious injury.
- This product does not contain mercury, cadmium or Lithium (metal).
- DO NOT INCINERATE battery cells.

## SECTION 14: TRANSPORTATION INFORMATION

### U.S. DOT Hazardous Material Regulations (Re: Ground Transport)

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries packed with equipment over 101 watt hours when packaged correctly can travel under 49 CFR 173.185 when traveling by ground in the continental U.S. Must have the IACO label (UN3480 for batteries only, UN3481 for batteries packed with equipment).

### Canada Transport Dangerous Goods (Re: Ground Transport)

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries packed with equipment over 101 watt hours when traveling by ground in Canada must be declared as Dangerous Goods. The batteries must be packaged according to Packing Instruction 965. The following labels must be on the package: DG9 diamond, Red Bordered Lithium-ion warning label (ICAO). The package must also include a UN3480 Lithium-ion batteries label with the net weight of the batteries in kgs. The BOL must also state UN3480, Lithium-ion batteries,9,PGII or UN3481 Lithium-ion batteries packed with equipment,9,PGII.

### International Dangerous Goods Regulations (Re: Air, Sea, Ground Transport)

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries over 101 watt hours packed with equipment when shipped by sea will be considered Class 9 Dangerous Goods must be packaged according to Packing Instruction 965, and contain the following labels: DG9 diamond, Red Bordered Lithium-ion warning label (ICAO), and UN3480/3481 label with the kg of lithium label.

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries over 101 watt hours packed with equipment when shipped by air will be considered Class 9 Dangerous Goods must be packaged according to Packing Instruction 965, and contain the following labels: DG9 diamond, Red Bordered Lithium-ion warning label (ICAO), Cargo Aircraft Only, and a label stating the amount of kgs of lithium in the box.

This rechargeable Lithium-ion battery has passed the relevant transportation test requirements as described in the UN Manual of Tests and Criteria, Part III, section 38.3. UN 38.3 Test Reports are maintained by the company.

## SECTION 15: REGULATORY INFORMATION

Compliant with, relevant transportation test requirements as described in the UN Manual of Tests & Criteria, Part III, Sub section 38.3.

### CALIFORNIA PROPOSITION 65

**⚠ WARNING: Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

## SECTION 16: OTHER INFORMATION

The information contained within this document is provided for your information only. In case of any discrepancy, the information provided in the battery cell Safety Data Sheet takes precedence over the information provided in the battery pack Technical Data Sheet.

Prepared by: Techtronic Industries Power Equipment

The batteries referenced herein are considered exempt articles and are not subject to the OSHA Hazard Communication Standard; therefore an SDS is not required. This sheet is being provided as a service to our customers.

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. TECHTRONIC INDUSTRIES POWER EQUIPMENT makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereto.

## MATERIAL SAFETY DATA SHEET

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT IDENTIFICATION

Li-ion battery ICR18650 3.7V 2000mAh

#### MANUFACTURER

JIANGSU TENPOWER LITHIUM CO., LTD

#### ADDRESS

Nangang Rd, Emerging industries Zone, Jinfeng Town,Zhangjiagang,Jiangsu,China

#### COMPANY/UNDERTAKING IDENTIFICATION

Emergency Contacy: 86- 512 – 80159851

### 2. HAZARDS IDENTIFICATION

Lithium ion cells are not hazardous when used according to the instructions of the manufacturer under normal conditions. In case of abuse, there is a risk of rupture, fire, heat, or leakage of internal components, which could release hazardous materials.

#### SYMPTOMS OF EXPOSURE

Skin contact

No effect under routine handling and use.

Skin absorption

No effect under routine handling and use.

Eye contact

No effect under routine handling and use.

Inhalation

No effect under routine handling and use.

#### REPORTED AS CARCINOGEN

Not applicable

### 3. COMPOSITION INFORMATION

| INGREDIENTS       | %   | CAS NUMBER |
|-------------------|-----|------------|
| Cobalt oxide      | <30 | 1307-96-6  |
| Manganese dioxide | <30 | 1313-13-9  |

| INGREDIENTS                       | %    | CAS NUMBER |
|-----------------------------------|------|------------|
| Nickel oxide                      | <30  | 1313-99-1  |
| Carbon                            | <30  | 7440-44-0  |
| Polyvinylidene Fluoride<br>(PVDF) | <10  | 24937-79-9 |
| Aluminum foil                     | 2-10 | 7429-90-5  |
| Copper foil                       | 2-10 | 7440-50-8  |
| Electrolyte(*)                    | <20  |            |
| Aluminium and inert<br>materials  | 5-10 |            |

#### **FURTHER INFORMATION**

For information purposes:

(\*) Main ingredients: Lithium hexafluorophosphate , organic carbonates

Because of the cell structure the dangerous ingredients will not be available if used properly.

During charge process a lithium graphite intercalation phase is formed.

Mercury content: Hg < 0.1mg/kg

Cadmium content: Cd < 1mg/kg

Lead content: Pb< 10mg/kg

#### **4. FIRST-AID MEASURES**

INHALATION, EYE CONTACT, and SKIN CONTACT: Not a health hazard.

##### INGESTION

If swallowed, obtain medical attention immediately.

If exposure to internal materials within cell due to damaged outer casing, the following actions are recommended.

##### INHALATION

Leave area immediately and seek medical attention.

##### EYE CONTACT

Rinse eyes with water for 15 minutes and seek medical attention.

##### SKIN CONTACT

Wash area thoroughly with soap and water and seek medical attention.

##### INGESTION

Drink milk/water and induce vomiting; seek medical attention.

#### **5. FIRE FIGHTING MEASURES**

##### GENERAL HAZARD



Cell is not flammable but internal organic material will burn if the cell is incinerated.

Combustion products include, but are not limited to hydrogen fluoride, carbon monoxide and carbon dioxide.

#### EXTINGUISHING MEDIA

Use extinguishing media suitable for the materials that are burning.

#### SPECIAL FIREFIGHTING INSTRUCTIONS

If possible, remove cell(s) from fire fighting area.

If heated above 120°C, cell(s) can explode/vent.

#### FIREFIGHTING EQUIPMENT

Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

### **6. ACCIDENTAL RELEASE MEASURES**

#### ON LAND

Place material into suitable containers and call local fire/police department.

#### IN WATER

If possible, remove from water and call local fire/police department.

### **7. HANDLING AND STORAGE**

#### HANDLING

No special protective clothing required for handling individual cells.

#### STORAGE

Store in cool, dry place.

### **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### ENGINEERING CONTROLS

Keep away from heat and open flame.

#### PERSONAL PROTECTION

Store in a cool dry place.

Respirator:

Not required during normal operations.  
event of a fire.

SCBA required in the

Eye/face protection:

Gloves:

Foot protection:

Not required beyond safety practices of employer.

Not required for handling of cells.

Steel toed shoes recommended for large container handling.

Product Name: JIANGSU TENPOWER LITHIUM CO., LTD

## 9. PHYSICAL AND CHEMICAL PROPETIES

Appearance

Form: Solid

Color: Various

Odor: Odourless

Important health, safety and environmental information

Test method

|                      |           |
|----------------------|-----------|
| pHValue              | N/A       |
| Flash point          | N/A       |
| Lower explosion      | N/A       |
| Vapor pressure       | N/A       |
| Density              | N/A       |
| Water solubility     | Insoluble |
| Ignition temperature | N/A       |

## 10. STABILITY AND REACTIVITY

REACTIVITY

None

INCOMPATIBILITIES

None during normal operation.

Avoid exposure to heat, open flame, and corrosives.

#### HAZARDOUS DECOMPOSITION PRODUCTS

None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

#### CONDITIONS TO AVOID

Avoid exposure to heat and open flame.

Do not puncture, crush or incinerate.

### 11. TOXICOLOGICAL INFORMATION

Cells are not hazardous when used properly. In case of fire or leakage combustion and decomposition products may cause irritation and toxicity to skin, eye and respiratory systems.

Toxicity data of some substance is listed:

Hydrogen fluoride:

Extremely toxic, May be fatal if inhaled or ingested. Readily absorbed through the skin contact may be fatal. Possible mutagen. LCLO: 50 ppm/30m (human beings), LC50: 1276 ppm/1h (rats).

Carbon and graphite:

Slightly hazards in case of skin contact (irritant), ingestion, inhalation, which will cause chronic damage to upper respiratory tract and cardiovascular system.

Copper:

File No./Rev.: MSDS—163/C

Dust may cause respiratory irritation.

LD50: 3.5 mg kg-1(mouse).

### 12. ECOLOGICAL INFORMATION

Some materials within the cell are bioaccumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

### 13. DISPOSAL INFORMATION

Recommended methods for safe and environmentally preferred disposal :

Product (waste from residues)

Do not throw out a used battery cell. Recycle it through the recycling company.

Contaminated packaging

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery cell contaminates, dispose as industrial wastes subject to special control.

No regulated

Dispose of according to all federal, state, and local regulations.

**14. TRANSPORTATION INFORMATION**

With regard to transport, the following regulations are cited and considered:

The International Civil Aviation Organization (ICAO) Technical Instructions, Packing Instruction 965, Section I B (2015 Edition),

The International Air Transport Association (IATA) Dangerous Goods Regulations, Packing Instruction 965, Section IB (57th Edition, 2016)

The International Maritime Dangerous Goods (IMDG) Code (2018 Edition),  
US Hazardous Materials Regulations 49 CFR(Code of Federal Regulations)

Sections 173-185 Lithium batterie and cells,

The UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria 38.3  
Lithium batteries, Rev.5, Amend.1

The article is not restricted to IMO IMDG code according to special provision 188(SP 188).

Our products are properly classified, described, packaged, marked, and labeled, and are in proper condition for transportation according to all the applicable international and national governmental regulations, not limited to the above mentioned. We further certify that the enclosed products have been tested and fulfilled the requirements and conditions in accordance with UN Recommendations (T1 – T8) on the Transport of Dangerous Goods Model Regulations and the Manual of Testes and Criteria.

Test results of the UN Recommendation on the Transport of Dangerous Goods

| Manual of Test and Criteria(38.3 Lithium battery) |                        | Test results | Remark                                |
|---|------------------------|--------------|---------------------------------------|
| No.   | Test items             |              |                                       |
| T1  | Altitude Simulation    | Pass         |                                       |
| T2  | Thermal Test           | Pass         |                                       |
| T3  | Vibration              | Pass         |                                       |
| T4  | Shock                  | Pass         |                                       |
| T5  | External Short Circuit | Pass         |                                       |
| T6  | Impact                 | Pass         |                                       |
| T7  | Overcharge             | Pass         | For pack and single cell battery only |
| T8  | Forced Discharge       | Pass         |                                       |

**15. REGULATORY INFORMATION**

For shipping regulations see section 14.

**16. OTHER INFORMATION**

**JIANGSU TENPOWER LITHIUM CO., LTD**

**Document No.: TPCM2019-03**

**Issued Date: 2019 .JAN.10**



The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide.

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Jiangsu Tenpower Lithium Co., Ltd. makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it

First Edition : 2011-May-1 Latest Edition: 2019-Jan-10

Prepared and Approved By

Jingsu Tenpower Lithium Co., Ltd

