



12V 5.0Ah REPLACEMENT BATTERY



Model: B LA 12V 5.0A

Specifications

| | |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cells Per Unit | 6 |
| Normal Voltage | 12V |
| Capacity | 5.0Ah @ 20 hour rate to 1.75V per cell @ 77°F |
| Weight | Approx. (145 ± 3%) kg (3.26 lbs) |
| Maximum Discharge Current | 50A (5 sec) |
| Internal Resistance | Approximately 35mΩ full charged @ 77°F |
| Operating Temperature Range | Discharge: -4°F ~ 140°F Charge: 32°F ~ 122°F Storage: -4°F ~ 140°F |
| Nominal Operating Temperature Range | 77°F ± 5°F |
| Float Charging Voltage | 13.7 ~ 13.9 VDC/unit average @ 77°F |
| Maximum Charging Current | 1.50A |
| Equalization and Cycle Service | 14.4V ~ 15.0 VDC/unit average @ 77°F |
| Self Discharge | Valve regulated lead acid (VRLA) batteries can be stored for more than 6 months at 77°F. Self-discharge ratio less than 3% per month at 77°F. Please charge batteries before using. |
| Terminal | F1 (0.187) / F1 (0.187) |
| Container Material | ABS (UL94-HB) |
| Battery Dimensions | 3.5"W x 4.0"H x 2.8"D |

- Rechargeable
- 90-Minute Minimum Emergency Run Time
- Multiple Use, Including Security Systems, Electronics Power Back-Up, Medical Equipment and More!
- Sealed Lead-Calcium
- Non-Spillable
- 1 Year Warranty
- UL Certified



MH62885



**Precision Consumer
Products Group, LLC.**

11024 Balboa Boulevard • Suite 1710
Granada Hills, CA 91344

1-866-237-9983
www.precisioncpg.com