



**RUST-OLEUM®
DECORATIVE COLOR CHIPS**

DESCRIPTION AND USES

Rust-Oleum® Decorative Color Chips are designed for use with Rust-Oleum® concrete floor coatings. When sprinkled onto a freshly coated surface, these decorative chips bond to the wet film to become a permanent part of the coating. Use on garages, basements, carports, laundry rooms, porches, patios and walkways. Rust-Oleum® Decorative Color chips also help to hide dirt and surface imperfections and can be used with water-based or solvent-based concrete coatings.

PRODUCTS

SKU (1-Pound)	DESCRIPTION
301359	Gray Blend
312447	Tan Blend
312449	Glacier Gray Blend
301238	Mocha Blend
301357	Tan Blend (The Home Depot)

INSTRUCTIONS FOR USE

Do not mix Decorative Color Chips into the coating. Apply concrete floor coating (sold separately) in 4'x4' sections. Immediately after completing the final roller passes, begin broadcasting the Decorative Color Chips onto the wet coating. Distribute the Decorative Color Chips by tossing them up into the air above the coating in an underhand manner. This allows the chips to drop directly down onto the surface of the coating. Avoid slinging the chips onto the coating with a sidearm throw.

IMPORTANT: Apply decorative color chips to wet paint only. Move on to the next 4'x4' section and continue until complete. Note: Fresh paint can be applied over the loose chips that lay outside the previously painted area. For a high gloss finish, topcoat the color chipped floor with a clear top coat coating.

COVERAGE

Standard Chip Pattern – 250 square feet per bag
Heavy Chip Pattern – 125 square feet per bag

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.