# SAFETY DATA SHEET

**Klean Strip Kerosene** 

Revision: 05/28/2020 Supersedes Revision: 05/14/2020

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Klean Strip Kerosene

**Company Name:** W. M. Barr **Phone Number:** 

2105 Channel Avenue (901)775-0100

Memphis, TN 38113

Web site address: www.wmbarr.com

**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346

Information: W.M. Barr Customer Service (800)398-3892

Intended Use: Heater Fuel

**Product Code:** GKE83, GKP85, GKP85WS, E08331, EKP85, CKE83, Q0116, CKE83M

## 2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 3

Acute Toxicity: Inhalation, Category 4 Skin Corrosion/Irritation, Category 2

Serious Eye Damage/Eye Irritation, Category 2B

Germ Cell Mutagenicity, Category 1B Toxic To Reproduction, Category 2

Specific Target Organ Toxicity (single exposure), Category 3

Specific Target Organ Toxicity (repeated exposure), Category 2

Aspiration Toxicity, Category 1







**GHS Signal Word:** 

Danger

**GHS Hazard Phrases:** H226: Flammable liquid and vapor.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation. H320: Causes eye irritation. H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H361: Suspected of damaging fertility or the unborn child.

H373: May cause damage to Central Nervous System (CNS) through prolonged or repeated

exposure.

**GHS Precautionary Phrases:** 

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood. P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe gas/mist/vapors/spray. P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P281: Use personal protective equipment as required.

P235: Keep cool.

Revision: 05/28/2020 Supersedes Revision: 05/14/2020

GHS Response Phrases: P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment see label. P331: Do NOT induce vomiting.

**GHS Storage and Disposal** 

P403+233: Store container tightly closed in well-ventilated place.

Phrases:

P405: Store locked up.

P501: Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute

See above.

and Chronic):

**Medical Conditions Generally** 

Diseases of the skin, eyes, liver, kidneys, central nervous system and respiratory system.

Aggravated By Exposure:

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # Hazardous Components (Chemical Name) Concentration

8052-41-3 Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}

80.0 -100.0 %

25551-13-7 Benzene, Trimethyl- 1.0 -5.0 %

Additional Chemical Information Ingredients vary due to variability with petroleum distillates and/or raw material suppliers

#### 4. FIRST AID MEASURES

**Emergency and First Aid** 

Procedures:

Inhalation: If user experiences breathing difficulty, move to air free of vapors, Administer oxygen

or artificial medical assistance can be rendered.

Skin Contact: Wash with soap and large quantities of water and seek medical attention if irritation

from contact persists.

Eye Contact: Flush with large quantities of water for at least 15 minutes and seek immediate

medical attention.

Ingestion: Do not induce vomiting. Call your local poison control center, hospital emergency room

or physician immediately for instructions to induce vomiting.

### 5. FIRE FIGHTING MEASURES

NFPA Class II

**Flash Pt:** > 100.00 F

Explosive Limits: LEL: 0.5 UEL: 6

Autoignition Pt: No data.

Suitable Extinguishing Media: Use carbon dioxide, dry chemical powder, or foam.

Fire Fighting Instructions: Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or

confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or

flame.

Flammable Properties and

Hazards:

Combustible Liquid.

**Hazardous Combustion**Carbon dioxide, carbon monoxide, smoke, fumes, and/or unburned hydrocarbons.

Revision: 05/28/2020 Supersedes Revision: 05/14/2020

Flammability Classification:

Products:

## 6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case

Clean up:

Material Is Released Or Spilled:

Shut off ignition sources; keep flares, smoking or flames out of hazard area.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a

plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

## 7. HANDLING AND STORAGE

Precautions To Be Taken in

Handling:

A static electrical charge can accumulate when this material is flowing through pipes, nozzles or

filters, and when it is agitated.

Precautions To Be Taken in

Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames

or at elevated temperatures.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS#	Chemical Name	Jurisaiction	Recommended Exposure Limits	Notations	
8052-41-3	Stoddard solvent	ACGIH TLV	TLV: 100 ppm		
{Mineral spirits; Aliphatic Petroleum					
Distillates; V	Vhite spirits}				
		OSHA PELs	PEL: 500 ppm		
25551-13-7	Benzene, Trimethyl-	ACGIH TLV	TLV: 25 ppm		

Respiratory Equipment (Specify For OSHA controlled work place and other regular users. Use only with adequate ventilation under

Type):

engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection

against vapors.

**Eye Protection:** Safety glasses, goggles or face shields are recommended to safeguard against potential eye

contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

**Protective Gloves:** Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly

remove clothing that becomes soiled with product.

Other Protective Clothing: Various application methods can dictate use of additional protective safety equipment, such as

impermeable aprons, etc., to minimize exposure.

**Engineering Controls** 

(Ventilation etc.):

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed

or you experience slight dizziness, headache, nausea, or eye-watering - Stop - ventilation is

inadequate. Leave area immediately.

Work/Hygienic/Maintenance

Practices:

A source of clean water should be available in the work area for flushing eyes and skin.

Do not eat, drink, or smoke in the work area.

Wash hands thoroughly after use.

Revision: 05/28/2020

Supersedes Revision: 05/14/2020

9. PHYSICAL AND CHEMICAL PRO	PERTIES

[ ] Gas **Physical States:** [X] Liquid [ ] Solid

Appearance and Odor: Water White / Free and Clear

Odor threshold not determined.

N.D. pH:

**Melting Point:** No data. - N.D. **Boiling Point:** 318.00 F - 385.00 F

> 100.00 F Flash Pt: N.D. **Evaporation Rate:** 

Flammability (solid, gas): No data available.

**Explosive Limits:** LEL: 0.5 UEL: 6 0.3 MM HG at 68.0 F

Vapor Pressure (vs. Air or mm

Hg):

Vapor Density (vs. Air = 1): 5 Air = 1 Specific Gravity (Water = 1): 0.78 Solubility in Water: N.D.

**Solubility Notes:** Very slightly soluble in cold water.

ND

**Octanol/Water Partition** 

Coefficient:

Percent Volatile: 100.0 % by weight. VOC / Volume: 778.0000 G/L **Autoignition Pt:** No data. **Decomposition Temperature:** No data. Viscosity: N.D.

Additional Physical Information ND = not determined.

## **10. STABILITY AND REACTIVITY**

Stability:	Unstable [ 1	Stable [ X ]

Conditions To Avoid - Instability: No data available.

Incompatible with strong acids, alkalies, and oxidizers such as liquid chlorine and oxygen. Incompatibility - Materials To

Avoid:

Decomposition may produce carbon monoxide and carbon dioxide.

**Hazardous Decomposition or** 

Possibility of Hazardous Will occur [ ] Will not occur [X]

Reactions:

**Byproducts:** 

Conditions To Avoid - Hazardous No data available.

Reactions:

Revision: 05/28/2020 Supersedes Revision: 05/14/2020

#### 11. TOXICOLOGICAL INFORMATION

**Toxicological Information:** Refer to section 2 for acute and chronic effects.

CAS# 25551-13-7:

Standard Draize Test, Skin, Species: Rabbit, 500.0 MG, 24 H, Moderate.

Result:

Kidney, Ureter, Bladder: Changes in liver weight.

Endocrine: Changes in thymus weight.

Immunological Including Allergic: Decreased immune response.

- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu

Praha Czechoslovakia, Vol/p/yr: -,24, 1972

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, 24 H, Mild.

Result:

Kidney, Ureter, Bladder: Changes in liver weight. Kidney, Ureter, Bladder: Changes in bladder weight.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu

Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu

Praha Czechoslovakia, Vol/p/yr: -,24, 1972

**Chronic Toxicological Effects:** Teratogenicity: Suspected of damaging the unborn child if inhaled.

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA	
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	n.a.	n.a.	n.a.	n.a.	
25551-13-7	Benzene, Trimethyl-	n.a.	n.a.	n.a.	n.a.	

#### 12. ECOLOGICAL INFORMATION

No data available.

#### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with federal, state, and local regulations.

#### 14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Kerosene

**DOT Hazard Class:** 3 FLAMMABLE LIQUID

UN/NA Number: UN1223 Packing Group: III



Additional Transport Information:

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer

Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed

under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that

subsequent shipments comply with these exceptions.

Revision: 05/28/2020 Supersedes Revision: 05/14/2020

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS # Hazardous Components (Chemical Name) S. 302 (EHS) S. 304 RQ S. 313 (TRI)

8052-41-3 Stoddard solvent {Mineral spirits; Aliphatic No No No No

Petroleum Distillates; White spirits}

25551-13-7 Benzene, Trimethyl- No No No

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

8052-41-3 Stoddard solvent {Mineral spirits; Aliphatic CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -

Petroleum Distillates; White spirits} Inventory; CA PROP.65: No

25551-13-7 Benzene, Trimethyl- CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -

Inventory; CA PROP.65: No

**Additional Regulatory** 

Information

Regulatory Information

Statement:

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

All components of this material are listed on the TSCA Inventory or are exempt.

## **16. OTHER INFORMATION**

**Revision Date:** 05/28/2020

Preparer Name: W.M. Barr and Company, Inc. (901)775-0100

**Additional Information About** 

This Product:

No data available.

Company Policy or Disclaimer: The

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.